

Form 9-881a
Feb. 1961**APPROVED**

DEC 5 1963

RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYBudget Bureau No. 42 R338.4
Approval expires 12/31/63Land Office **Las Cruces**Lease No. **064894-A**Unit **Poker Lake****SUNDRY NOTICES AND REPORTS ON WELLS**

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 13, 1963

Herzog Federal

Well No. 1 is located 1980 ft. from [N] line and 1980 ft. from [E] line of

NE 1/4 of Sec. 17
(1/4 Sec. and Sec. No.)T-25-S
(Twp.)R-30-E
(Range)N. M. P. M.
(Meridian)Undesignated
(Field)Eddy
(County or Subdivision)New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 3229 ft.

KDB Elev. 3230'

Ground Level Elev. 3222'

Top Delaware Sand: 3725 (-495)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On November 10, 1963, rigged up Clarke Well Service unit, pulled rods and pump, dismantled pumping unit, took up flow line. On November 11, 1963, Halliburton spotted 50 sx. regular neat cement at 3757. Estimated top of plug at 3350. Pulled tubing up to 3300', mixed 20 sx. of gel and 2 sx. lime, loaded hole with mud. McCullough Tool Co. located free point; cut off 5 1/2" OD casing at 2820. Pulled 2 joints; shut down over night. On November 12, 1963, finished pulling 5 1/2" OD casing, ran tubing to 2224', spotted 50 sx. regular neat cement. Pulled tubing up to 710', spotted 50 sx. regular neat cement. Laid down all tubing; pumped 25 sx. regular neat cement in top of 8-5/8" OD surface casing. Set 4" pipe marker in the top of the casing. Marker stencilled with the following: "Perry R. Bass - Herzog Federal #1. 1980' FNL & 1980' FEL Sec. 17, T-25-S, R-30-E, Eddy Co."

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **PERRY R. BASS**Address **Box 1178****Monahans, Texas**By **Walter D. Powers**
Title **Asst. Div. Mgr.****RECEIVED**
1963
G. M. C.
ANTHONY OFFICE