

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 7
(Other instructions
reverse side)LICATE*
4 on re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-070341

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Poker Lake Unit

9. WELL NO.

38

10. FIELD AND POOL, OR WILDCAT

Corral Canyon

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 19, T-25S, R-30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Central States Oil Company

3. ADDRESS OF OPERATOR

902 Building of the Southwest

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

900' F&L & 330' FNL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Run surface & production csg.

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 8-3/4" hole 10-15-69 and drilled to 750'.

2. Ran 7" , 20#/ft., J-55 casing and set at 750'. Cemented with 100 sacks Incor, plus 5# Gilsonite and 1/4# Flocele per sack followed by 75 sacks Incor plus 1/4# Flocele per sack plus 2% CC. Cement circulated. Tested casing to 1000#, held OK.

3. Drilled 6-1/4" hole to 3630'. Cored from 3630' to 3682'.

4. Ran 4-1/2", 10.5#/ft., J-55 casing and set at 3679'. Cemented with 150 sacks Incor 2% Gel cement.

RECEIVED

OCT 29 1969

D. C. C.
ARTESIA, OFFICE

RECEIVED

OCT 28 1969

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Don C. BennettTITLE Operations ManagerDATE October 27, 1969

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD PURPOSES

OCT 28 1969
Date

ACTING

District Engineer

*See Instructions on Reverse Side