

COPIES RECEIVED  
DISTRIBUTION  
SANTA FE  
FILE  
U.S.G.S.  
LAND OFFICE  
OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION  
*Go Connect API #*  
MAY 28 1981  
O. C. D.  
ARTESIA, OFFICE

30-015-~~23338~~  
Form C-101  
Revised 1-1-65  
23338

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work  
b. Type of Well DRILL ☒ DEEPEN ☐ PLUG BACK ☐  
OIL WELL ☒ GAS WELL ☐ OTHER ☐ SINGLE ZONE ☒ MULTIPLE ZONE ☐

2. Name of Operator  
Delta Drilling Company

3. Address of Operator  
3100-C North "A" Midland, Texas 79701

4. Location of Well UNIT LETTER K LOCATED 1980 FEET FROM THE South LINE  
AND 2040 FEET FROM THE West LINE OF SEC. 14 TWP. 23S RGE. 28E NMPM

7. Unit Agreement Name  
8. Farm or Lease Name  
Guitar Corn  
9. Well No.  
1  
10. Field and Pool, or Wildcat  
South Culebra (Bone Spring)  
12. County  
Eddy

19. Proposed Depth  
7200'  
19A. Formation  
Bone Spring  
20. Rotary or C.T.  
Rotary

21. Elevations (Show whether DF, RL, etc.)  
3004 GR  
21A. Kind & Status Plug. Bond  
Blanket  
21B. Drilling Contractor  
Delta Drilling Co  
22. Approx. Date Work will start  
July 5, 1981

23. PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
11"	8-5/8"	24	500'	220	Surface
7-7/8"	5-1/2"	17	7200'	1350	Surface

Cement: Cement will be circulated to surface on 5-1/2" casing by the use of a DV tool set at 3000'±.

Mud Program: Drill with native mud to 500'. Drill from 500' to 7200' with 10#/Gal. Brine.

APPROVAL VALID FOR 180 DAYS  
PERMIT EXPIRES 12-3-81  
UNLESS DRILLING UNDERWAY  
6-12-81

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Ron Lechwar Title Division Project Manager Date May 25, 1981

(This space for State Use)  
APPROVED BY W.A. Gussitt TITLE SUPERVISOR, DISTRICT II DATE JUN 03 1981

CONDITIONS OF APPROVAL, IF ANY:  
Cement must be circulated to surface behind 8 7/8" 5 1/2" casing