

RECEIVED BY
Form 9-331
Dec. 1979
AUG 03 1984
O. G. P.
ARTESIA, OFFICE
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Jubilee Energy Corporation ✓
3. ADDRESS OF OPERATOR 79705
4000 N. Big Spring. Suite 109, Midland, TX
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' FWL & 330' FNL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☒ ☒
FRACTURE TREAT ☒ ☒
SHOOT OR ACIDIZE ☒ ☒
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) ☐ ☐

5. LEASE
LC-064894-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Poker Lake
8. FARM OR LEASE NAME
Poker Lake Unit
9. WELL NO.
64
10. FIELD OR WILDCAT NAME
Corral Canyon (Delaware)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 17, 25-S, 30-E
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3210.5' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-05-84 Spud well @ 6:00 p.m.
6-07-84 Drilled to 828' and set 9 5/8" 53.5# casing @ 828' and cemented w/325 sx Class "C". WOC 18 hrs. Test w/1000#. Test okay.
6-11-84 Drilled to 3709' and cut core #1 from 3680' to 3709'.
6-12-84 Reached TD of 3736' and cut core #2 from 3709' to 3736'.
6-13-84 Ran 5 1/2" 15.5 & 17# casing to TD and cemented w/200 sx. 50-50 poz.
6-20-84 Ran logs and perforated from 3688' to 3702'; 3710' to 3720' w/1 shot per foot.
6-22-84 Acidized perforations w/3,000 gallons 7 1/2% acid.
6-28-84 Fraced well w/30,000 gallons 70 Quality foam + 60,000# sand in two 15,000 gallons stages.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE President DATE 7-26-84

ACCEPTED FOR RECORDS (Space for Federal or State office use)

APPROVED BY [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL: ANY: _____

AUG 1 1984

[Signature]

NEW MEXICO

*See Instructions on Reverse Side