

dsr

Form 9-13  
(May 1983)  
Drawer DD  
Artesia, NM 88210

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-064894-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen on the back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for each proposal.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

J. Ray Stewart

3. ADDRESS OF OPERATOR

1610 North J, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

1980' FSL & 330' FWL NW/4 SW/4 Unit L

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3198' GR

7. UNIT AGREEMENT NAME

Poker Lake Unit

8. FARM OR LEASE NAME

9. WELL NO.

66

10. FIELD AND POOL, OR WILDCAT

Corral Canyon - Delaware

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 17, T25S, R30E

12. COUNTY OR PARISH

Eddy

13. STATE

N. Mex.

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Set & cement surface csg.

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded @ 11:30 p.m. on 9/05/84.

Drilled 12 1/4" hole to TD 800'. Ran 18 jts. (775') 8 5/8" 24# J-55 casing. Set casing @ 685'. Ran Texas pattern shoe, insert float & 4 centralizers. Cemented with 250 sx Halliburton Lite 2% CaCl & 1/4# Flocele/sx. Tailed in with 200 sx Class C 2% CaCl. Circulated out 75 sx. Plug down @ 9:05 a.m. on 9/07/84. W.O.C. 12 hours. Installed B.O.P. Tested B.O.P. & casing to 1000 psi for 30 minutes. Held O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Nesh A. Taylor*

ACCEPTED FOR RECORD

TITLE Petroleum Consultant

DATE 9/10/84

(This space for Federal or State office use)

APPROVED BY

*SEP 13 1984*

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*Carlsbad*

NEW MEXICO See Instructions on Reverse Side