

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-064894-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR  
J. Ray Stewart ✓

3. ADDRESS OF OPERATOR  
1610 North J, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980' FSL & 330' FWL NW/4 SW/4 Unit L

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3198' GR

7. UNIT AGREEMENT NAME

Poker Lake Unit

8. FARM OR LEASE NAME

9. WELL NO.

66

10. FIELD AND POOL, OR WILDCAT

Corral Canyon - Delaware

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 17, T25S, R30E

12. COUNTY OR PARISH

13. STATE

Eddy

N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Run & set production csg

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Drld 7 7/8" hole to 3660'. Cored from 3660' to 3720'. Ran Borehole Compensated Sonic log. Drld. 7 7/8" hole to TD of 3780'. Ran 97 jts. (3813') 4 1/2" 11.6# J55 csg. Set csg. @ 3779' KB. Ran guide shoe, float collar & 5 centralizers. Cemented w/200 sx 50/50 Poz Class C, .3 of 1% Halad 9 & 3# salt/sx. Plug down @ 9:45 a.m. on 9/17/84. Float collar held O.K. Rel. rig @ 11:45 a.m. on 9/17/84. Pits will be fenced by 9/25/84. W.O. completion.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Neal A. Taylor*

TITLE

Petroleum Consultant

DATE

9/19/84

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

*SWP*

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY:

SEP 21 1984

*Calabaz*

NEW MEXICO

\*See Instructions on Reverse Side