

4151

NM OIL CONS. COMMISSION

Form 9-88
(May 1988)

Artesia, NM 88210

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-064894-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
J. Ray Stewart

3. ADDRESS OF OPERATOR
1610 North J, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State or Federal law.
See also space 17 below.)
At surface

1980' FSL & 330' FWL NW/4 SW/4 Unit L

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3198' GR

7. UNIT AGREEMENT NAME

Poker Lake Unit

8. FARM OR LEASE NAME

9. WELL NO.

66

10. FIELD AND POOL, OR WILDCAT

Corral Canyon - Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 17, T25S, R30E

12. COUNTY OR PARISH

Eddy

13. STATE

N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Completion

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/25/84 R.U.S.U. Found PBTD @ 3744'. Circ hole clean w/2% Kcl water. Ran Gamma Neutron log from 3200' - 3743'.

9/26/84 Perf. 3673', 3678' - 91' & 3700' - 3709' w/1 shot/ft (23 holes). Acidized w/2000 gals. 7 1/2% MSR acid w/clay stabilizers. Swabbed well down.

9/27 thru 9/30/84 Fraced well w/33,000 gals Quality foam & 41,500# 12/20 sand. S.W.I. 2 1/4 hrs. Started flowing well back. Rec. 92 bbls over load.

10/01/84 Installed B.O.P. Killed well w/10# brine. Pulled tbg. & pkr. Ran production string. Left well flowing to tank on 14/64" choke. W.O. pumping unit.

18. I hereby certify that the foregoing is true and correct

SIGNED

Neal A. Taylor

TITLE Petroleum Consultant

DATE 10/02/84

(This space for Federal or State office use)

APPROVED BY

gwd

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY

OCT 9 1984

Artesia

NEW MEXICO

*See Instructions on Reverse Side