

SUPPLEMENTAL DRILLING DATA

FORTSON OIL COMPANY
SYLVITE FEDERAL NO. 3
990' FNL & 990' FWL
Sec. 6, T20S, R30E
Eddy County, N.M.

The following information is filed in accordance with "Onshore Oil and Gas Order" No.s 1 & 2:

1. Geologic Name of Surface Formation: Permian age
2. Estimated Geological Marker Tops:

Rustler	300'	Yates	1430'
T/Salt	425'	7 Rivers	1550'
B/Salt	1350'	Delaware	3530'

3. Estimated Depths to Water, Oil and Gas:

Water: above Rustler formation at 170'±
Oil & Gas: Delaware formation below 3530'

4. Proposed Casing and Cement Program:

Surface Csg:	20", 94.0#, ST&C casing. Cement with 500 sx Class 'C' with 2% CaCl. Circulate cement to surface.
First Inter:	13 3/8", 48 & 54.5#, H-40, ST&C casing. Cement with 500 sx 50-50 pozmix followed by 250 sx Class 'C' with 2% CaCl. Circulate cement to surface.
Second Inter:	9 5/8", 36.0#, J-55, ST&C casing. Cement with 900 sx 35-65 pozmix. Tie cement to 13 3/8" casing.
Prod. Casing:	7.0", 23 & 26.0#, J-55, ST&C casing. Cement with 500 sx Class 'C' with 1% CaCl. Cement to isolate all oil, gas and water zones.