

Form 1003-3
(1991)

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM

SUBMIT IN PLICATE
(Other instructions on
reverse side)

30-015-27530 C/SF
Form approved
Budget Bureau No. 1004-0136
Expires: December 31, 1991

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1A. TYPE OF WORK

DRILL ☒

DEEPEN ☐

B. TYPE OF WELL

OIL
WELL ☒

GAS
WELL ☐

OTHER ☐

MULTIPLE
BORE ☐

MULTIPLE
BORE ☐

2. NAME OF OPERATOR

Devon Energy Corporation (Nevada)

3. ADDRESS AND TELEPHONE NO.

20 North Broadway Suite 1500 Oklahoma City, OK 73102 (405) 552-4560

4. LOCATION OF WELL (Report location clearly and in compliance with any State requirements.)

At surface

460' FSL & 1935' FWL

At proposed prod. zone

same

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

Approximately 7 miles southeast of Artesia, NM

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST

PROPERTY OR LEASE LINE, FT.

(Also to nearest drg. well line, if any)

460'

16. NO. OF ACRES IN LEASE

40

17. NO. OF ACRES ASSIGNED

TO THIS WELL

40

18. DISTANCE FROM PROPOSED LOCATION*

TO NEAREST WELL, DRILLING, COMPLETION,

OR APPLIC. FOR, OF THIS LEASE, FT.

500'

19. PROPOSED DEPTH

2320'

20. ROTARY OR CABLE TOOL

rotary

21. ELEVATION (Show whether DP, RT, OR, etc.)

3595.2'

22. APPROX. DATE WORK WILL START*

June 30, 1993

PROPOSED CASING AND CEMENTING PROGRAM *

SIZE OF HOLE	CASE, HOSING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
17 1/2"	conductor		30'	Redimix
12 1/4"	8 5/8", J-55	24 ppf	1250'	425 sx Lite + 185 sx Class C
7 7/8"	5 1/2", J-55	15.5 ppf	2320'	115 sx Lite + 185 sx Class C

* Cement will be circulated to surface on all casing strings

Devon Energy plans to drill to 2320'+ to test the San Andres formation for commercial quantities of oil. If the San Andres is deemed non-commercial, the wellbore will be plugged and abandoned per Federal regulations. Programs to adhere to onshore oil and gas regulations are outlined in the following exhibits and attachments.

Drilling Program

Surface Use and Operating Plan

Exhibit #1 and #1-A - Blowout Prevention Equipment

Exhibit #2 - Location and Elevation Plat

Exhibit #3 - Planned Access Roads

Exhibit #4 - Wells Within a One Mile Radius

Exhibit #5 - Production Facilities Plat

Exhibit #6 - Rotary Rig Layout

Exhibit #7 - Casing Program

Exhibit #8 - H₂S Drilling Operations
Plan

Evidence of Bond Coverage

Copy of the Cultural Report

10-1

7-16-93

DC/APR

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout prevention program, if any.

34.

SIGNED Randy Jackson

Randy Jackson

TITLE District Engineer

DATE April 28, 1993

(This space for Federal or State office use)

APPROVAL SUBJECT TO

PERMIT TO DRILL REQUIREMENTS AND

APPROVAL DATE

APPROVAL OF BUREAU OF LAND MANAGEMENT

Application approved and the applicant holds legal or equitable title to these rights in the subject lease which would entitle the applicant to conduct operations thereon.

COMPLETION OF PERMIT, IF ANY:

(ORIG. SGD.) RICHARD L. MANNING

AREA MANAGER

JUL 7 1993

APPROVED BY

TITLE

DATE

*See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations or to use any means which the individual

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated, on all types of lands and leases for appropriate action by either a Federal or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable State or Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plat, separate or on this reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal or State agency offices.

ITEMS 15 AND 16: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective production zone.

ITEM 22: Consult applicable Federal or State regulations, or appropriate officials, concerning approval of the proposal before operations are started.

NOTICE

The Privacy Act of 1974 and the regulation in 43 CFR 2.46(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR Part 3160.

PRINCIPAL PURPOSE: The information is to be used to process and evaluate your application for permit to drill or deepen an oil or gas well.

ROUTINE USES: (1) The analysis of the applicant's proposal to discover and extract the Federal or Indian resources enumerated. (2) The review of procedures and equipment and the projected impact on the land involved. (3) The evaluation of the effects of proposed operation on surface and subsurface water and other environmental impacts. (4)(5) Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions, as well as routine regulatory responsibility.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if the operator elects to initiate drilling operations on an oil and gas lease.

BURDEN HOURS STATEMENT

Public reporting burden for this form is estimated to average 30 minutes per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management, (Albany) Bureau Chief, (WO-711), 1849 C Street, N.W., Washington, D.C. 20240, and the Office of Management and Budget, Paperwork Reduction Project (1004-0136), Washington, D.C. 20503.

The Paperwork Reduction Act of 1980 (44 U.S.C. 3501 et seq) requires us to inform you that:

This information is being collected to allow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases.

This information will be used to analyze and approve applications.

Response to this request is mandatory only if the operator elects to initiate drilling operations on an oil and gas lease.

DRILLING PROGRAM

Attached to Form 3160-3
Devon Energy Corporation
West Red Lake Unit #38
460' FNL & 1935' FEL
Section 4-T18S-R27E
Eddy County, New Mexico

1. Geologic Name of Surface Formation:

Permian

2. Estimated Tops of Important Geologic Markers:

Seven Rivers	280'
Queen	820'
Grayburg	1,200'
San Andres	1,480'

3. Estimated Depths of Anticipated Fresh Water, Oil or Gas:

Water

Upper Permian: Surface - 820'

Oil

Grayburg:	1,370' - 1,480'
San Andres:	1,930' - 2,295'

No other formations are expected to yield oil, gas or fresh water in measurable volumes. The surface fresh water sands will be protected by setting 8 5/8" casing at 1250' and circulating cement back to surface. The Grayburg and San Andres intervals will be isolated by setting 5-1/2" casing to total depth (2320'±) and circulating cement to surface.

WEST RED LAKE UNIT #38
DRILLING PROGRAM
PAGE 2

4. Casing Program:

<u>Hole Size</u>	<u>Interval</u>	<u>Csg OD</u>	<u>Weight, Grade, Type</u>
17 1/2"	0-30'	13 3/8"	Conductor, 0.30" wall
12-1/4"	0-1250'	8-5/8"	24#, J-55 ERW or seamless ST&C R-3
7-7/8"	0-TD	5-1/2"	15.5# J-55, ERW FBN or seamless ST&C, R-3

Casing Program:

13 3/8" Conductor Casing: Cemented with redimix to surface.

8 5/8" Surface Casing: Cemented to surface with 425 sks 35:65 (Poz:Class C) + 6% gel + 2% CaCl₂ + 1/4 lb/sk cellophane flakes and 185 sks Class C + 2% CaCl₂ + 1/4 lb/sk cellophane flakes.

5-1/2" Production: Cemented to surface with 115 sks 35:65 (Poz:Class C) + 6% gel + 10% salt + 1/4 lb/sk cellophane flakes and 185 sks Class C + 3% salt + 0.3% fluid loss additive + 1/4 lb/sk cellophane flakes.

The above cement volumes could be revised pending the caliper measurement from the open hole logs. The top of cement is designed to reach surface.

5. Minimum Specifications for Pressure Control:

The blowout preventor equipment (BOP) shown in Exhibit #1 will consist of a (3M system) double ram type (3000 psi WP) preventor and a bag-type (Hydril) preventor (3000 psi WP). Both units will be hydraulically operated and the ram type preventor will be equipped with blind rams on top and 4-1/2" drill pipe rams on bottom. Both BOP's will be installed on the 8 5/8" surface casing and utilized continuously until total depth is reached. As per BLM Drilling Operations Order #2, prior to drilling out the 8-5/8" casing shoe, the BOP's and Hydril will be function tested.

Pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These functional tests will be documented on the daily drillers log. A 2" kill line and 3" choke line will be incorporated in the drilling spool below the ram-type BOP. Other accessory BOP equipment will include a kelly cock, floor safety valve, choke lines and choke manifold having 3000 psi WP rating.

WEST RED LAKE UNIT #38
DRILLING PROGRAM
PAGE 3

6. Types and Characteristics of the Proposed Mud System:

The well will be drilled to total depth using brine, cut brine and polymer mud systems. Depths of systems are as follows:

<u>Depth</u>	<u>Type</u>	<u>Weight (ppg)</u>	<u>Viscosity (1/sec)</u>	<u>Water Loss (cc)</u>
0 - 1250'	Fresh Water	8.6-8.8	34-36	No Control
1250' - T.D.	Cut Brine Polymer	10.0-10.1	28-30	10-20

The necessary mud products for weight addition and fluid loss control will be on location at all times.

7. Auxiliary Well Control and Monitoring Equipment:

- A. A kelly cock will be in the drill string at all times.
- B. A full opening drill pipe stabbing valve having the appropriate connections will be on the rig floor at all times.

8. Logging, Testing and Coring Program:

- 1 A. No drillstem tests are planned.
- B. The open hole electrical logging program will be:
 - T. D. to 1250': Dual Laterolog-Micro SFL with Gamma Ray, Caliper and SP
 - T.D. to 1250': Compensated Neutron-Litho Density with Gamma Ray and Caliper
 - T. D. to surface: Gamma Ray/Neutron
- C. No cores are planned.

- D. Additional testing will be initiated subsequent to setting the 5 1/2" production casing. Specific intervals will be targeted based on log evaluation, geological sample shows and drill stem tests.

9. Abnormal Pressures, Temperatures and Potential Hazards:

No abnormal pressures or temperatures are foreseen. The anticipated bottom hole temperature at total depth is 104 degrees and maximum bottom hole pressure is 800 psig. No major loss circulation intervals have been encountered in adjacent wells. An H₂S Drilling Operations Plan is included as Exhibit #8.

10. Anticipated Starting Date and Duration of Operations:

Notice of Staking (NOS) was sent to the Carlsbad, New Mexico BLM office on February 9, 1993. Barry Hunt of that office has reviewed the proposed pad site for the location. A Cultural Resources Examination has been completed by New Mexico Archaeological Services, Inc and a copy forwarded to the Carlsbad, New Mexico BLM office.

Road and location preparation will not be undertaken until approval has been received from the BLM. The anticipated spud date is approximately June 30, 1993. The drilling operation should require approximately 10 days. If the well is deemed productive, completion operations will require, at minimum, an additional 30 days of testing to ascertain whether permanent production facilities will be constructed.

SURFACE USE AND OPERATING PLAN

Attachment to Form 3160-3
Devon Energy Corporation
West Red Lake Unit #38
460' FSL & 1935' FWL
Section 4-T18S-R27E
Eddy County, New Mexico

1. **Existing Roads:**

- A. The well site and elevation plat for the proposed West Red Lake Unit #38 is reflected on Exhibit #2. It was staked by John West Engineering, Hobbs, New Mexico.
- B. All roads into the location are depicted in Exhibit #3. Chalk Bluff Road will be used to access the location. No upgrades to roads other than the access into location from the exiting lease road will be necessary.
- C. Directions to location: Turn right (south) off Highway 82 onto Chalk Bluff Road and go to the end of the road. Chalk Bluff Road turns east. Continue east on Chalk Bluff Road for 0.3± miles and then turn right (south) onto lease road. Continue 600± to the proposed WRLU #38 entry road. Turn left (east) into location.

2. **Proposed Access Road:**

Exhibit #3 shows the new access road to be constructed from the existing lease road. It will be constructed as follows:

- A. The maximum width of the road will be fifteen (15) feet.
- B. It will be crowned and made of 6 inches of rolled and compacted caliche. Water will be deflected, as necessary, to avoid accumulation and prevent surface erosion.
- C. Surface material will be native caliche. This material will be obtained from a BLM approved pit nearest in proximity to the location.
- D. The average grade will be approximately 1%.

WEST RED LAKE UNIT #38
SURFACE USE AND OPERATING PLAN
PAGE 2

- E. No cattleguards, grates or fence cuts will be required.
- F. No turnouts are planned.

3. Location of Existing Wells:

Exhibit #4 shows all existing wells within a one-mile radius of the proposed West Red Lake Unit #38. There are 65 total wells which include 14 active Queen/Grayburg/San Andres producers, 11 inactive Queen/Grayburg/San Andres wells, 21 active Abo producers, 11 inactive Abo wells, 2 inactive Penn wells, 1 active Wolfcamp producer, 1 active Atoka producer, 1 inactive Morrow well and 3 drilled and abandoned wells. A list of the wells is depicted on Exhibit #4 attachment.

4. Location of Existing and/or Proposed Facilities:

- A. Devon Energy Corporation operates two production facilities in this unit. The West Red Lake Unit Battery is in Section 7 and the West Red Lake Unit Satellite Battery is in Section 8.
- B. In the event the well is found productive, it will be added to the West Red Lake Satellite Battery (refer to Exhibit #5).
- C. The well will be operated by means of an electric motor.
- D. If the well is productive, rehabilitation plans are as follows:
 - a. The reserve pit will be back-filled after the contents of the pit are dry (within 120 days after completion, weather permitting).
 - b. Caliche from unused portions of the drill pad will be removed. The original topsoil from the wellsite will be returned to the location. The drill site will then be contoured to the original natural state.

WEST RED LAKE UNIT #38
SURFACE USE AND OPERATING PLAN
PAGE 3

5. Location and Type of Water Supply:

The West Red Lake Unit #38 will be drilled using a combination of brine and fresh water mud systems (outlined in Drilling Program). The water will be obtained from the existing water line presently supplying fresh water to the unit. Additionally, produced salt water from lease gathering tanks may be used. No water well will be drilled on the location.

6. Source of Construction Materials:

All caliche utilized for the drilling pad and proposed access road will be obtained from a existing BLM approved pit. All roads will be constructed of 6" rolled and compacted caliche.

7. Methods of Handling Water Disposal:

- A. Drill cuttings will be disposed into the reserve pit.
- B. Drilling fluids will be contained in steel mud tanks or lined earthen pits and the reserve pit. The reserve pit will contain excess drilling fluid or fluid from the well during drilling, cementing, and completion operations. The reserve pit will be an earthen pit roughly 70' x 70' x 5', or smaller, in size.
- C. The reserve pit will be fenced on three sides throughout drilling operations and will be totally isolated upon removal of the rotary rig. The pit will be lined using a 5-7 mil plastic to minimize loss of drilling fluids.
- D. Water produced from the well during completion operations will be disposed into a steel tank or reserve pit, if volumes prove excessive. After placing the well on production through the production facilities, all water will be collected in tanks and injected into the water injection system. Produced oil will be separated into steel stock tanks until sold.
- E. A portable chemical toilet will be available on the location for human waste during the drilling operations.

WEST RED LAKE UNIT #38
SURFACE USE AND OPERATING PLAN
PAGE 4

- F. Garbage, trash and waste paper produced during drilling operations will be collected in a contained trailer and disposed at a approved landfill. All waste material will be contained to prevent scattering by the wind. All water, fluids, salt or other chemicals will be disposed into the reserve pit. No toxic waste or hazardous chemicals will be generated by this operation.
- G. All waste material will be removed within 30 days after the well is either completed or abandoned. The reserve pit will be completely fenced until it has dried. At the point the reserve pit is found sufficiently dry, it will be backfilled and reclaimed as per BLM specifications. Only the portion of the drilling pad used by the production equipment (pumping unit) will remain in use. If the well is deemed non-commercial, only a dry hole marker will remain.

8. Ancillary Facilities:

No campsite or other facilities will be constructed as a result of this well.

9. Well Site Layout:

- A. The drill pad is shown on Exhibit #6. Approximate dimensions of the pad, pits and general location of the rig equipment is displayed. Top soil will be stored adjacent to the pad until reclamation efforts are undertaken. Only modest cuts will be necessary to build the pad which will be covered with 6" of compacted caliche.
- B. No permanent living facilities are planned, but temporary trailers for the toolpusher, drilling foreman and mud logger may be on location throughout drilling operations.
- C. The reserve pit and earthen mud pits will be lined using plastic sheeting of 5-7 mil thickness.

WEST RED LAKE UNIT #38
SURFACE USE AND OPERATING PLAN
PAGE 5

10. Plans for Restoration of Surface:

- A. After concluding the drilling and/or completion operations, if the well is found non-commercial, the caliche will be removed from the pad and transported to the original caliche pit or used for other drilling locations. The road will be reclaimed as directed by the BLM. The reserve pit area will be broken out and leveled after drying to a condition where these efforts are feasible. The original top soil will again be returned to the pad and contoured, as close as possible, to the original topography.
- B. The pit lining will be buried or hauled away in order to return the location and road to their pristine nature. All pits will be filled and location leveled, weather permitting, within 120 days after abandonment.
- C. The location and road will be rehabilitated as recommended by the BLM.
- D. The reserve pit will be fenced on three sides throughout drilling operations. After the rotary rig is removed, the reserve pit will be fenced on the fourth side to preclude endangering wildlife. The fencing will be in place until the pit is reclaimed.
- E. If the well is deemed commercially productive, the reserve pit will be restored as described in 10 (A) within 120 days subsequent to the completion date. Caliche from areas of the pad site not required for operations will be reclaimed. The original top soil will be returned to the area of the drill pad not necessary to operate the well. These unused areas of the drill pad will be contoured, as close as possible, to match the original topography.

11. Surface Ownership:

The wellsite is owned by the Bureau of Land Management.

WEST RED LAKE UNIT #38
SURFACE USE AND OPERATING PLAN
PAGE 6

12. Other Information:

- A. The area surrounding the well site is gypsiferous with limestone outcroppings. The vegetation is moderately sparse with Chihuahuan desert scrub.
- B. There is permanent water (Pecos River) approximately 1.8 miles W/SW of the location.
- C. A Cultural Resources Examination has been completed by Archaeological Survey Consultants and forwarded to the Carlsbad, New Mexico BLM office. The report references no cultural areas on either the access road or drilling pad.

13. Lessees's and Operator's Representative:

The Devon Energy Corporation representatives responsible for assuring compliance of the surface use plan are:

Randy Jackson
District Engineer

20 North Broadway
Suite 1500
Oklahoma City, OK 73102

(405) 552-4560 (office)
(405) 340-8939 (home)

Dan Talley
Production Foreman

422 West Main
Suite F
Artesia, NM 88210

(505) 748-3371 (office)
(505) 748-3671 (home)

Certification:

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access road; that I am familiar with the conditions that presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Devon Energy Corporation (Nevada) and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.

Date: April 28, 1993

Signed: Randy Jackson
Randy Jackson
District Engineer

MINIMUM BLOWOUT PREVENTER REQUIREMENTS

3,000 psi Working Pressure

3 MWP

West Red Lake Unit #38
Eddy County, New Mexico
Exhibit #1


STACK REQUIREMENTS

No.	Item	Min. I.D.	Min. Nominal
1	Flowline		
2	Fill up line		2"
3	Drilling nipple		
4	Annular preventer		
5	Two single or one dual hydraulically operated rams		
6a	Drilling spool with 2" min. kill line and 3" min choke line outlets		
6b	2" min. kill line and 3" min. choke line outlets in ram. (Alternate to 6a above.)		
7	Valve Gate <input type="checkbox"/> Plug <input type="checkbox"/>	3-1/8"	
8	Gate valve—power operated	3-1/8"	
9	Line to choke manifold		3"
10	Valves Gate <input type="checkbox"/> Plug <input type="checkbox"/>	2-1/16"	
11	Check valve	2-1/16"	
12	Casing head		
13	Valve Gate <input type="checkbox"/> Plug <input type="checkbox"/>	1-13/16"	
14	Pressure gauge with needle valve		
15	Kill line to rig mud pump manifold		2"

OPTIONAL

16	Flanged valve	1-13/16"	
----	---------------	----------	--

CONFIGURATION A



CONTRACTOR'S OPTION TO FURNISH:

1. All equipment and connections above bradenhead or casinghead. Working pressure of preventers to be 3,000 psi, minimum.
2. Automatic accumulator (80 gallon, minimum) capable of closing BOP in 30 seconds or less and, holding them closed against full rated working pressure.
3. BOP controls, to be located near drillers position.
4. Kelly equipped with Kelly cock.
5. Inside blowout preventer or its equivalent on derrick floor at all times with proper threads to fit pipe being used.
6. Kelly saver-sub equipped with rubber casing protector at all times.
7. Plug type blowout preventer tester.
8. Extra set pipe rams to fit drill pipe in use on location at all times.
9. Type RX ring gaskets in place of Type R.

MEC TO FURNISH:

1. Bradenhead or casinghead and side valves.
2. Wear bushing, if required.

GENERAL NOTES:

1. Deviations from this drawing may be made only with the express permission of MEC's Drilling Manager.
2. All connections, valves, fittings, piping, etc., subject to well or pump pressure must be flanged (suitable clamp connections acceptable) and have minimum working pressure equal to rated working pressure of preventers up through chokes. Valves must be full opening and suitable for high pressure mud service.
3. Controls to be of standard design and each marked, showing opening and closing position.
4. Chokes will be positioned so as not to hamper or delay changing of choke beans. Replaceable parts for adjustable choke, other bean sizes, retainers, and choke wrenches to be conveniently located for immediate use.
5. All valves to be equipped with handwheels or handles ready for immediate use.
6. Choke lines must be suitably anchored.

7. Handwheels and extensions to be connected and ready for use.
8. Valves adjacent to drilling spool to be kept open. Use outside valves except for emergency.
9. All seamless steel control piping (3000 psi working pressure) to have flexible joints to avoid stress. Hoses will be permitted.
10. Casinghead connections shall not be used except in case of emergency.
11. Do not use kill line for routine fill-up operations.


Attachment to Exhibit #1
NOTES REGARDING BLOWOUT PREVENTORS
West Red Lake Unit #38
Eddy County, New Mexico

1. Drilling nipple will be constructed so it can be removed mechanically without the aid of a welder. The minimum internal diameter will equal BOPE bore.
2. Wear ring will be properly installed in head.
3. Blowout preventor and all associated fittings will be in operable condition to withstand a minimum 3000 psi working pressure.
4. All fittings will be flanged.
5. A full bore safety valve tested to a minimum 3000 psi W.P. with proper thread connections will be available on the rotary rig floor at all times.
6. All choke lines will be anchored to prevent movement.
7. All BOP equipment will be equal to or larger in bore than the internal diameter of the last casing string.
8. Will maintain a kelly cock attached to the kelly.
9. Hand wheels and wrenches will be properly installed and tested for safe operation.
10. Hydraulic floor control for blowout preventor will be located as near in proximity to driller's controls as possible.
11. All BOP equipment will meet API standards and include a minimum 40 gallon accumulator having two independent means of power to initiate closing operation.

MINIMUM CHOKE MANIFOLD
3,000, 5,000 and 10,000 PSI Working Pressure

3 MWP - 5 MWP - 10 MWP

West Red Lake Unit #38
Eddy County, New Mexico
Exhibit #1-A



MINIMUM REQUIREMENTS										
No.		3,000 MWP			5,000 MWP			10,000 MWP		
		I.D.	NOMINAL	RATING	I.D.	NOMINAL	RATING	I.D.	NOMINAL	RATING
1	Line from drilling spool		3"	3,000		3"	5,000		3"	10,000
2	Cross 3"x3"x3"x2"			3,000			5,000			
	Cross 3"x3"x3"x3"									10,000
3	Valves(1) Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000
4	Valve Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	1-13/16"		3,000	1-13/16"		5,000	1-13/16"		10,000
4a	Valves(1)	2-1/16"		3,000	2-1/16"		5,000	3-1/8"		10,000
5	Pressure Gauge			3,000			5,000			10,000
6	Valves Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000
7	Adjustable Choke(3)	2"		3,000	2"		5,000	2"		10,000
8	Adjustable Choke	1"		3,000	1"		5,000	2"		10,000
9	Line		3"	3,000		3"	5,000		3"	10,000
10	Line		2"	3,000		2"	5,000		3"	10,000
11	Valves Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000
12	Lines		3"	1,000		3"	1,000		3"	2,000
13	Lines		3"	1,000		3"	1,000		3"	2,000
14	Remote reading compound standpipe pressure gauge			3,000			5,000			10,000
15	Gas Separator		2'x5'			2'x5'			2'x5'	
16	Line		4"	1,000		4"	1,000		4"	2,000
17	Valves Gate <input type="checkbox"/> Plug <input type="checkbox"/> (2)	3-1/8"		3,000	3-1/8"		5,000	3-1/8"		10,000

(1) Only one required in Class 3M.

(2) Gate valves only shall be used for Class 10M.

(3) Remote operated hydraulic choke required on 5,000 psi and 10,000 psi for drilling.

EQUIPMENT SPECIFICATIONS AND INSTALLATION INSTRUCTIONS

1. All connections in choke manifold shall be welded, studded, flanged or Cameron clamp of comparable rating.
2. All flanges shall be API 6B or 6BX and ring gaskets shall be API RX or BX. Use only BX for 10 MWP.
3. All lines shall be securely anchored.
4. Chokes shall be equipped with tungsten carbide seats and needles, and replacements shall be available.
5. Choke manifold pressure and standpipe pressure gauges shall be available at the choke manifold to assist in regulating chokes. As an alternate with automatic chokes, a choke manifold pressure gauge shall be located on the rig floor in conjunction with the standpipe pressure gauge.
6. Line from drilling spool to choke manifold should be as straight as possible. Lines downstream from chokes shall make turns by large bends or 90° bends using butt plugged tees.
7. Discharge lines from chokes, choke bypass and from top of gas separator should vent as far as practical from the well.

OIL CONSERVATION DIVISION

EXHIBIT #2

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL LOCATION AND ACREAGE DEDICATION PLAT


All Distances must be from the outer boundaries of the section

Operator DEVON ENERGY			Lease WEST RED LAKE UNIT		Well No. 38
Unit Letter N	Section 4	Township 18 SOUTH	Range 27 EAST	County EDDY	
Actual Footage Location of Well: 460 feet from the SOUTH line and 1935 feet from the WEST line					
Ground Level Elev. 3595.2'	Producing Formation San Andres		Pool West Red Lake		Dedicated Acreage: 40 Acres

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interest of all owners been consolidated by communitization, unitization, force-pooling, etc.?
☐ Yes ☐ No If answer is "yes" type of consolidation _____

If answer is "no" list of owners and tract descriptions which have actually been consolidated. (Use reverse side of this form necessary.)

No allowable will be assigned to the well unit all interests have been consolidated (by communitization, unitization, forced-pooling, otherwise) or until a non-standard unit, eliminating such interest, has been approved by the Division.



OPERATOR CERTIFICATION

I hereby certify the information contained herein is true and complete to the best of my knowledge and belief.

Signature
Charles W. Horsman
Printed Name
Charles W. Horsman
Position
District Engineer
Company
Devon Energy Corporation (Nevada)
Date
January 25, 1993

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed
DECEMBER 5, 1992
Signature & Seal of Professional Surveyor
John W. West
Certificate No. **JOHN W. WEST, 676**
RONALD J. EDSON, 3238
GARY J. JONES, 7977


92-11-1843

R 26 E

R 27 E

T 17 S

T 18 S




devcon

WEST RED LAKE UNIT

DEER COUNTY, NEBRASKA

WELLS WITHIN ONE MILE RADIUS
OF THE P.D.
EXHIBIT 4



Attachment to Exhibit #4

STATUS OF WELLS WITHIN ONE MILE RADIUS

West Red Lake Unit #38
Section 4 - T18S-R27E
Eddy County, New Mexico

Sec. 3 - T18S - R27E

ARCO Oil & Gas Corp.

Empire Abo Unit J #9	Unit E	Abo	(Active)
Empire Abo Unit K #9	Unit L	Abo	(Active)
Empire Abo Unit L #9	Unit M	Abo	(Active)
Empire Abo Unit L #10	Unit N	Abo	(Active)

Sec. 4 - T18S - R27E

Devon Energy Corp.

Hondo Fed. #2	Unit A	Qn - Grbg - SA	(Active)
Hondo Fed. #1	Unit G	Qn - Grbg - SA	(Active)
Hondo B Fed. #1	Unit H	Qn - Grbg - SA	(Active)
West Red Lake Unit #29	Unit K	Qn - Grbg - SA	(Active)
West Red Lake Unit #27	Unit M	Qn - Grbg - SA	(Active)
West Red Lake Unit #30	Unit N	Qn - Grbg - SA	(Inactive)

ARCO Oil & Gas Corp.

Empire Abo Unit K #8	Unit I	Abo	(Inactive)
Empire Abo Unit K #7	Unit J	Abo	(Inactive)
Empire Abo Unit L #5	Unit M	Abo	(Inactive)
Empire Abo Unit L #6	Unit N	Abo	(Inactive)
Empire Abo Unit L #7	Unit O	Abo	(Inactive)
Empire Abo Unit L #8	Unit P	Abo	(Inactive)

Merit Energy Corp.

Federal BA Gas Com. #1	Unit E	Wolfcamp	(Active)
------------------------	--------	----------	----------

Attachment to Exhibit #4 (cont.)

Mann #6	Unit G		D & A
Hondo Oil & Gas			
Federal EG	Unit K	Qn-Grbg-SA	(Inactive)
Amoco Production Co.			
Federal BA Gas Com #1	Unit K	Morrow	(Inactive)
<u>Sec. 5 - T18S - R27E</u>			
Breck Operating Corp.			
Carter Collier Federal #1	Unit G	Qn - Grbg - SA	(Active)
Eaton Federal #1	Unit K	Qn - Grbg - SA	(Inactive)
Julia A Federal #1	Unit L	Qn - Grbg - SA	(Active)
Petroleum Corp. of Texas			
Yates Collier Federal #1	Unit J	Qn - Grbg - SA	(Inactive)
R. D. Compton			
Brainard #3	Unit P	Qn - Grbg - SA	(Inactive)
Brainard Fed. "A" #6	Unit P		(D & A)
Brainard #7	Unit P	Qn - Grbg - SA	(Inactive)
Brainard #8	Unit P	Qn - Grbg - SA	(Inactive)
Brainard #24	Unit P		(D & A)
Exxon Co. USA			
Chalk Bluff Unit P #1	Unit K	Penn.	(Inactive)

Attachment to Exhibit #4 (cont.)

Sec. 8 - T18S - R27E

Devon Energy Corp.

West Red Lake Unit #25	Unit A	Qn - Grbg - SA	(Inactive)
West Red Lake Unit #33	Unit A	Qn - Grbg - SA	(Active)
West Red Lake Unit #21	Unit B	Qn - Grbg - SA	(Inactive)
West Red Lake Unit #22	Unit B	Qn - Grbg - SA	(Inactive)
West Red Lake Unit #23	Unit G	Qn - Grbg - SA	(Active)
West Red Lake Unit #32	Unit H	Qn - Grbg - SA	(Active)
West Red Lake Unit #26	Unit I	Qn - Grbg - SA	(Active)

Julian E. Simon

Compton #4	Unit A	Qn - Grbg - SA	(Inactive)
------------	--------	----------------	------------

ARCO Oil & Gas Co.

Empire Abo Unit N #4	Unit H	Abo	(Active)
Empire Abo Unit O #4	Unit I	Abo	(Active)

Pan American Corp.

Chalk Bluff Draw Unit	Unit H	Penn.	(Inactive)
-----------------------	--------	-------	------------

Sec. 9 - T18S - R27E

ARCO Oil & Gas Co.

Empire Abo Unit M #8	Unit A	Abo	(Active)
Empire Abo Unit M #7	Unit B	Abo	(Active)
Empire Abo Unit M #6	Unit C	Abo	(Active)
Empire Abo Unit N #5	Unit E	Abo	(Active)
Empire Abo Unit N #6	Unit F	Abo	(Inactive)
Empire Abo Unit N #701	Unit G	Abo	(Active)
Empire Abo Unit N #7	Unit G	Abo	(Inactive)
Empire Abo Unit N # 801	Unit H	Abo	(Active)

Attachment to Exhibit #4 (cont.)

Sec. 9 - T18S - R27E

Empire Abo Unit N #8	Unit H	Abo	(Inactive)
Empire Abo Unit O #8	Unit I	Abo	(Active)
Empire Abo Unit O #7	Unit J	Abo	(Active)
Empire Abo Unit O #6	Unit K	Abo	(Active)
Empire Abo Unit O #5	Unit L	Abo	(Active)
Empire Abo Unit P #6	Unit N	Abo	(Active)
Empire Abo Unit P #7	Unit O	Abo	(Inactive)
Empire Abo Unit P #701	Unit O	Abo	(Active)


Devon Energy Corp.

West Red Lake Unit #31	Unit C	Qn - Grbg - SA	(Active)
West Red Lake Unit #34	Unit C	Qn - Grbg - SA	(Active)
West Red Lake Unit #28	Unit D	Qn - Grbg - SA	(Active)
Mann Federal #1	Unit F	Atoka	(Active)

Sec. 10 - T18S - R27E

ARCO Oil & Gas Co.

Empire Abo Unit M #9	Unit D	Abo	(Active)
Empire Abo Unit M #901	Unit D	Abo	(Inactive)
Empire Abo Unit N #9	Unit E	Abo	(Active)
Empire Abo Unit N #901	Unit E	Abo	(Active)



FILE: WRLU-38

devon
ENERGY CORPORATION

WEST RED LAKE UNIT


EDDY COUNTY, NEW MEXICO

SCHEMATIC DIAGRAM
EXISTING WRLU SATELLITE BATTERY
WEST RED LAKE UNIT #38

EXHIBIT 5

CH

3/93




FILE: WRLU-38



WEST RED LAKE UNIT

EDDY COUNTY, NEW MEXICO

DRILLING PAD FOR
WEST RED LAKE UNIT #38
EXHIBIT 6



CH

3/93

DEVON ENERGY

Operator: DEVON ENERGY CORP	Well Name: WEST RED LAKE #38
Project ID:	Location: SEC 7 - T18S -R27E

Design Parameters:

Mud weight (9.00 ppg) : 0.468 psi/ft
 Shut in surface pressure : 1092 psi
 Internal gradient (burst) : 0.100 psi/ft
 Annular gradient (burst) : 0.000 psi/ft
 Tensile load is determined using air weight
 Service rating is "Sweet"

Design Factors:

Collapse : 1.125
 Burst : 1.00
 8 Round : 1.80 (J)
 Buttress : 1.60 (J)
 Body Yield : 1.50 (B)
 Overpull : 0 lbs.

Length (feet)		Size (in.)	Weight (lb/ft)	Grade	Joint	Depth (feet)	Drift (in.)	Cost	
1	1,250	8-5/8"	24.00	J-55	ST&C	1,250	7.972		
	Collapse Load (psi)	Strgth (psi)	S.F.	Burst Load (psi)	Min Int Strgth (psi)	Yield S.F.	Tension Load (kips)	Strgth (kips)	S.F.
1	584	1370	2.346	1110	2950	2.66	30.00	244	8.13 J

Prepared by : R. JACKSON, Oklahoma City, OK
 Date : 04-26-1993
 Remarks :

Minimum segment length for the 1,250 foot well is 900 feet.

Surface/Intermediate string:

Next string will set at 2,320 ft. with 10.10 ppg mud (pore pressure of 1,217 psi.) The frac gradient of 1.000 at the casing seat results in an injection pressure of 1,250 psi. Effective BHP (for burst) is 1,110 psi.

The minimum specified drift diameter is 4.825 in.

NOTE: The design factors used in this casing string design are as shown above. As a general guideline, Lone Star Steel recommends using minimum design factors of 1.125 - Collapse (with evacuated casing), 1.0 - Burst, 1.8 - 8 Round Tension, 1.6 - Buttress Tension, and 1.5 - Body Yield. Collapse strength under axial tension was calculated based on the Westcott, Dunlop and Kemler curve. Engineering responsibility for use of this design will be that of the purchaser. Costs for this design are based on a 1990 pricing model. (Version 1.0G)

DEVON ENERGY

Operator: DEVO ENERGY CORP	Well Name: WEST RED LAKE #38
Project ID:	Location: SEC 4 - T18S -R27E

Design Parameters:

Mud weight (10.10 ppg) : 0.525 psi/ft
 Shut in surface pressure : 985 psi
 Internal gradient (burst) : 0.100 psi/ft
 Annular gradient (burst) : 0.000 psi/ft
 Tensile load is determined using air weight
 Service rating is "Sweet"

Design Factors:

Collapse : 1.125
 Burst : 1.00
 8 Round : 1.80 (J)
 Buttress : 1.60 (J)
 Body Yield : 1.50 (B)
 Overpull : 0 lbs.

Length (feet)		Size (in.)	Weight (lb/ft)	Grade	Joint	Depth (feet)	Drift (in.)	Cost	
1	2,320	5-1/2"	15.50	J-55	ST&C	2,320	4.825		
	Load (psi)	Collapse Strgth (psi)	S.F.	Burst Load (psi)	Min Int Strgth (psi)	Yield S.F.	Load (kips)	Tension Strgth (kips)	S.F.
1	1217	4040	3.320	1217	4810	3.95	35.96	202	5.62 J

Prepared by : R. JACKSON, Oklahoma City, OK

Date : 04-26-1993

Remarks :

Minimum segment length for the 2,320 foot well is 1,500 feet.

The mud gradient and bottom hole pressures (for burst) are 0.525 psi/ft and 1,217 psi, respectively.

NOTE: The design factors used in this casing string design are as shown above. As a general guideline, Lone Star Steel recommends using minimum design factors of 1.125 - Collapse (with evacuated casing), 1.0 - Burst, 1.8 - 8 Round Tension, 1.6 - Buttress Tension, and 1.5 - Body Yield. Collapse strength under axial tension was calculated based on the Westcott, Dunlop and Kemler curve. Engineering responsibility for use of this design will be that of the purchaser. Costs for this design are based on a 1990 pricing model. (Version 1.0G)

DEVON ENERGY CORPORATION

HYDROGEN SULFIDE DRILLING OPERATIONS PLAN

A. Hydrogen Sulfide Training

All rig crews and company personnel will receive training from a qualified instructor in the following areas prior to penetrating any hydrogen sulfide bearing formations during drilling operations:

1. The hazards and characteristics of hydrogen sulfide (H₂S).
2. The proper use and maintenance of the H₂S safety equipment and of personal protective equipment to be utilized at the location such as H₂S detection monitors, alarms and warning systems, and breathing equipment. Briefing areas and evacuation procedures will also be discussed and established.
3. Proper rescue techniques and procedures will be discussed and established.

In addition to the above, supervisory personnel will be trained in the prevention of oil and gas well blowouts in accordance with Minerals Management Service Standards Subpart - 0 - 250 - 212.

Prior to penetrating any known H₂S bearing formation, H₂S training will be provided at the rig sight for all rig crews and company personnel that have not previously received such training. This instruction will be provide by a qualified instructor with each individual being required to pass a 20 question test regarding H₂S safety procedures. All contract personnel employed on an unscheduled basis will be required to have received appropriate H₂S training.

This Hydrogen Sulfide Drilling And Operations Plan shall be available at the wellsite during drilling operations.

B. H₂S Safety Equipment And Systems

All H₂S safety equipment and systems will be installed, tested, and operational when drilling operations reaches a depth approximately 500' above any known or probable H₂S bearing formation. The safety systems to be utilized during drilling operations are as follows:

1. Well Control Equipment

- (a) Double ram BOP with a properly sized closing unit and pipe rams to accommodate all pipe sizes in use.
- (b) A choke manifold with a minimum of one remote choke.

Note: BOP's will be in place prior to drilling out surface casing.

2. H2S Detection And Monitoring Equipment

- (a) Three (3) H2S detection monitors will be placed in service at the location. One monitor will be placed near the bell nipple on the rig floor; one will be placed at the rig substructure; and, one will be at the working mud pits or shale shaker. This monitoring system will have warning lights and audible alarms that will alert personnel when H2S levels reach 20 ppm.
- (b) One (1) Sensidyne Pump with the appropriate detection tubes will also be available to perform spot checks for H2S concentrations in any remote or isolated areas.

3. Protective Equipment For Essential Personnel

Protective equipment will consist of the following:

- (a) Four (4) - five minute escape packs located at strategic points around the rig.
- (b) Four (4) - thirty minute rescue packs to be located at the designated briefing areas.
- (c) Breathing air cascade manifold system complete with 10 - 300 cubic feet air cylinders with four hose line work units.

4. Visual Warning System

Visual warning system will consist of the following:

- (a) Two wind direction indicators.
- (b) One condition / warning sign which will be posted on the road providing direct access to the location. The sign will contain lettering of sufficient size to be readable at a reasonable distance from the

immediate location. The sign will inform the public that a hydrogen sulfide gas environment could be encountered be at the location.

5. Mud Program

- (a) The mud program has been designed to minimize the volume of H₂S circulated to surface. Proper mud weight and safe drilling practices (for example, keeping the hole filled during trips) will minimize hazards when drilling in H₂S bearing formations.

6. Metallurgy


- (a) All drill strings, casings, tubing, wellhead, blowout preventers, drilling spools, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.

7. Communication

- (a) Two way radio and cellular telephone communication will be available in company vehicles.

C. Diagram Of Drilling Location

1. Attached is a diagram representing a typical location layout as well as the location of H₂S monitors, briefing areas, and wind direction indicators.



- △ H2S MONITORS WITH ALARMS AT THE BELL NIPPLE, SUBSTRUCTURE, AND SHALE SHAKER
- ▲ WIND DIRECTION INDICATORS
- SAFE BRIEFING AREAS WITH CAUTION SIGNS AND PROTECTIVE BREATHING EQUIPMENT




FILE: WRLU-38

devon
ENERGY CORPORATION

WEST RED LAKE UNIT

EDDY COUNTY, NEW MEXICO



4/93

JUN 20 1989

Land

ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION

GARREY CARRUTHERS
GOVERNOR

June 14, 1989

POST OFFICE BOX 2088
STATE LAND OFFICE BUILDING
SANTA FE, NEW MEXICO 87500
(505) 827-5800

Devon Energy Corporation
1500 Mid-America Tower
20 North Broadway
Oklahoma City, Oklahoma 73102-8260

Attention: Charlene Newkirk


Re: \$50,000 Blanket Plugging Bond
Devon Energy Corporation, Principal
Bond No. 56-0130-11003-82-1

Dear Ms. Newkirk:

The Oil Conservation Division hereby acknowledges receipt of and approves the rider to the above-captioned bond changing the name of principal as follows:

DEVON ENERGY CORPORATION (NEVADA)

Sincerely,


WILLIAM J. LEMAY,
Director

dr/

cc: Oil Conservation Division
Hobbs, Artesia, Aztec

DEVON
ENERGY
CORPORATION

1500 Mid-America Tower
20 North Broadway
Oklahoma City, Oklahoma 73102-8260

405/235-3611
TWX 910-831-3277

May 5, 1989

State of New Mexico
Oil & Gas Conservation Commission
State Capitol Building
Santa Fe, NM 87504

Re: Blanket Plugging Bond
State of New Mexico
No. 56-0130-11003-87

Gentlemen:

Devon Energy Corporation formerly Devon Corporation has changed its name to Devon Energy Corporation (Nevada). In this regard, enclosed is a Rider for the referenced bond to include both company names. Please amend your records.

Very truly yours,

Charlene
Charlene Newkirk
Lease Records Supervisor

encls

cc: Carolyn Wilson
McEldowney McWilliams

R I D E R

To be attached to and become a part of Bond No. 56-0130-11003-87-1
issued by the United States Fidelity and Guaranty Company, on
behalf of Devon Energy Corporation
as Principal, and in favor of State of New Mexico
as Obligor, in the penalty of Fifty thousand and no/100 - - - - -
Dollars (\$ 50,000.00) for Blanket plugging bond

It is hereby understood and agreed that effective on the
February 10, 1989 the Principal in this
bond shall be Devon Energy Corporation (Nevada)

However, the liability of the Surety in the aggregate to the
Obligor for any and all defaults of the Principal, whether occurring
before or after or partly before and partly after this rider
become effective, shall in no event exceed the penalty stated
in the bond.

Signed, Sealed, and Dated this 3rd day of March 1989.

ATTEST:

Quinn Armstrong
Asst. Secretary

Devon Energy Corporation (Nevada)

M. C. Lunde, Jr.
By: MARVIN C. LUNDE, JR.
Vice President

UNITED STATES FIDELITY AND GUARANTY COMPANY

By: Marcia C. Brejda Attorney-in-fact

ARCHAEOLOGICAL SURVEY OF DEVON ENERGY CORPORATION's West Red Lake Unit Well No. 38, 460' FSL, 1935' FWL, and access road, Section 4, West Red Lake Unit Well No. 39, 1300' fNL, 1080' FEL, and access road, West Red Lake Unit Well No. 40, 1780' FSL, 230' FEL, and access road, Section 7, T18S, R27E, NMPM, Eddy County, NM

FEDERAL LAND SURFACE

MAP REFERENCE: USGS SPRING LAKE QUADRANGLE, 7.5 Minute Series, 1985, Prov. Ed.

REPORT NUMBER: 93-NMAS-15-M

by Dr. J. Loring Haskell, Principal Investigator

NEW MEXICO ARCHAEOLOGICAL SERVICES, INC.
P.O. Box 1341, Carlsbad, New Mexico 88221-1341
(505) 887-7646

PERMIT NUMBER: 14-2920-92-M

12 March 1993

Prepared for: DEVON ENERGY CORPORATION
20 North Broadway-Suite 1500
Oklahoma City, Oklahoma 73102

Attention: Debby O'Donnell

Distribution: DEVON ENERGY CORPORATION (1)
Bureau of Land Management (2)

NEW MEXICO ARCHAEOLOGICAL SERVICES, INC.
PERMIT NUMBER: 14-2920-92-M

CULTURAL RESOURCES EXAMINATION
REPORT NUMBER: NMAS-93-15-M

ABSTRACT: CLASS III SURVEY OF DEVON ENERGY CORPORATION's proposed West Red Lake Unit Well No. 38, 400' X 400', 4.44 acres. West Red Lake Unit Well No. 39, 400' X 400', 4.44 acres and access road, 100' X 200', 0.46 acre. West Red Lake Unit Well No. 40, 400' X 400', 4.44 acres. TOTAL SURVEYED AREA 13.78 ACRES. No cultural resources were recorded during these surveys. Clearance is suggested for all proposed work.

West Red Lake Unit Well No. 38

LEGAL LOCATION: SE $\frac{1}{4}$ SW $\frac{1}{4}$, (460' FSL, 1935' FWL), Section 4, T18S, R27E, NMPM, Eddy County, NM

MAP REFERENCE: USGS SPRING LAKE QUADRANGLE, 7.5 Minute Series, 1955, Photorevised 1975.

LAND STATUS: BLM, Roswell District, Carlsbad Resource Area, NM

PROJECT DESCRIPTION: Location, 400' X 400', 4.44 acres.

TOPOGRAPHY/FLORAL FORMATION: The proposed location will be situated on a gypsiferous landform whose surface is broken by a series of highly weathered, relict limestone outcroppings. Local soils are supportive of a desert scrub formation. ELEVATION: 3595'.

EXAMINATION PROCEDURE: Zigzag transects, 8.0 m wide, close interval (15° or less). FIELD TIME: 1½ hours. AREA DELINEATION: Staked by client. VISIBILITY: 75 to 90%. WEATHER: Sunny, partly cloudy conditions.

FINDINGS: BLM Records, Arita K. Slate, 25 February 1993, Section 4 (no archaeological sites), T18S, R27E, NMPM, Eddy County, NM
No cultural resources were recorded during this survey.

RECOMMENDATIONS: NMAS usggests clearance for DEVON ENERGY CORPORATION's West Red Lake Unit Well No. 38 (Fig. 1).

TIME AND DATE OF INVESTIGATION: Late morning, 8 March 1993.




Fig. 1. USGS SPRING LAKE QUADRANGLE, 7.5 Minute Series, 1:24,000, 1955, Photorevised 1975, showing DEVON ENERGY CORPORATION's West Red Lake Unit Well No. 38, 460' FSL, 1935' FWL, Section 4, T18S, R27E, West Red Lake Unit Well No. 39, 1300' FNL, 1090' FEL, and access road, Section 7, and West Red Lake Unit Well No. 40, 1780' FSL, 230' FEL, Section 7, T18S, R27E, NMPM, Eddy County, NM

West Red lake Unit Well No. 39

LEGAL LOCATION: NE $\frac{1}{4}$ NE $\frac{1}{4}$, Section 7, and access road, SE $\frac{1}{4}$ NE $\frac{1}{4}$, Section 7, T18S, R27E, NMPM, Eddy County, NM

MAP REFERENCE: USGS SPRING LAKE QUADRANGLE, 7.5 Minute Series, 1955, Photorevised 1975.

PROJECT DESCRIPTION: Location, 400' x 400', 4.44 acres, and access road, 100' X 200', 0.46 acres.

TOPOGRAPHY/FLORAL FORMATION: The proposed location will be situated on a ragged, gypsiferous landform due east of the Pecos River. Overall, the coeval surface is subject to strong sheetwash. Associated soils are supportive of a desert scrub formation. ELEVATION: 3366'.

EXAMINATION PROCEDURE: Zigzag transects, 8.0 m wide, close interval (15° or less). The access road was walked in two, 15 m wide, zigzag transects. FIELD TIME: 1½ hours. AREA DELINEATION: Staked by client. VISIBILITY: 75 to 90%. WEATHER: Sunny, partly cloudy conditions.

FINDINGS: BLM Records, Arita K. Slate, 25 February 1993, Section 7 (one archaeological site), T18S, R27E, NMPM, Eddy County, NM
Section 7, T18S, R27E.

*LA 38295 (*Incorrectly located*)
No cultural resources were recorded during this survey.

RECOMMENDATIONS: NMAS suggests clearance for DEVON ENERGY CORPORATION's West Red Lake Unit Well No. 39 and access road (Fig. 1).

TIME AND DATE OF INVESTIGATION: Mid-day, 8 March 1993.

West Red Lake Unit Well No. 40

LEGAL LOCATION: NE $\frac{1}{4}$ SE $\frac{1}{4}$, (1780' FSL, 230' FEL), Section 7, T18S, R27E, NMPM, Eddy County, NM

MAP REFERENCE: USGS SPRING LAKE QUADRANGLE, 7.5 Minute Series, 1955, Photorevised 1975.

LAND STATUS: BLM, Roswell District, Carlsbad Resource Area, NM

PROJECT DESCRIPTION: Location, 400' X 400', 4.44 acres.

TOPOGRAPHY/FLORAL FORMATION: The proposed location will be situated on the crest of a gypsiferous ridge due east of the Pecos River. Local soils are supportive of a desert scrub/grassland formation. ELEVATION: 3371'.

EXAMINATION PROCEDURE: Zigzag transects, 8.0 m wide, close interval (15° or less). FIELD TIME: three hours. AREA DELINEATION: Staked by client. VISIBILITY: 75 to 90%. WEATHER: Sunny, partly cloudy conditions, 8 March 1993, and sunny conditions, 10 March 1993.

FINDINGS: BLM Records, Arita K. Slate, 25 February 1993, Section 7 (one archaeological site), T18S, R27E, NMPM, Eddy County, NM
Section 7, T18S, R27E.

**LA 38295 (Site is incorrectly located; its location is unknown)*

No cultural resources were recorded during this survey.

RECOMMENATIONS: NMAS suggests clearance for DEVON ENERGY CORPORATION's West Red Lake Unit Well No. 40.

TIME AND DATE OF INVESTIGATION: Mid-afternoon, 8 March 1993,
Mid-morning, 10 March 1993.