

AUXILIARY EQUIPMENT

DRAWWORKS BDW 650M 650 HP, with Parmac Hydromatic brake

ENGINES Two Caterpillar D-353 diesels rated at 425 HP each

ROTARY Ideco 23", 300 ton capacity

MAST/SUB Ideal 132', 550,000 lb rated static hook load with 10 line
Wagner 15' high substructure

TRAVELLING EQUIPMENT Gardner-Denver, 300 ton, 5 sheave w/ BJ 250 ton hook.
Brewster Model 7 SX 300 ton swivel.

PUMPS Continental-EMSCO DC-700 and DB-550, 5 1/2 X 16" Duplex, Compound driven.

PIT SYSTEM 1-Shale Pit 6X7X35', 1-Settling Pit 6X7X38', 1-Suction Pit 6X7X34' w/ 5 mud agitators.
Two centrifugal mud mixing pumps and a Double Screen Shale Shaker.

LIGHT PLANT Two CAT 3306 diesel electric sets 180 KW prime power.

BOP EQUIP 13 5/8" 5000 psi WP double ram and 13 5/8" 5000 psi WP Shaffer Annular
Preventer. Choke manifold rated at 5000 psi. Valvcon 5-station 80 gallon closing unit.

Exhibit D
Santa Fe Energy Operating Partners, L.P.
Sterling Silver "33" Fed. No.9
Section 33, T-23S, R-31E
Eddy County, New Mexico

DDR:SS33-9.PMT