

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

RECEIVED

AUG 24 1994

O. C. D.
ARTESIA, OFFICE ☐ AMENDED REPORT

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address. Yates Petroleum Corp. 105 S. 4th St. Artesia, NM 88210		OGRID Number 25575
Property Code 15790	Property Name ALTO "AOL" COM	API Number 30-015-28149
		Well No. 1

Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
H	21	19S	25E		1980	North	660	East	Eddy

Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Proposed Pool 1 N. Dagger Draw Upper Penn 15472					Proposed Pool 2 N/A				

Work Type Code N	Well Type Code O	Cable/Rotary R	Lease Type Code P	Ground Level Elevation 3472'
Multiple No	Proposed Depth 8300'	Formation Canyon	Contractor Not Determined	Spud Date ASAP

Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
14 3/4"	9 5/8"	36# J-55	1150'	1100 sx	Circulated
8 3/4"	7"	23#, 26#	TD	1350 sx	Post ID-1
		J-55, N-80			12-14-94
					New log & API

Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Yates Petroleum Corporation wishes to drill and test the Canyon and intermediate formation. Approximately 1150' of surface casing will be set and cement circulated to shut off gravel and cavings. If commercial, production casing will be run and cemented, will perforate and stimulate as needed for production.

MUD PROGRAM: FW GEL/LCM TO 1150'; FW TO 5200'; CUT BRINE/KCL to 7200'; CUT BRINE/KCL/STARCH TO TD.

BOP PROGRAM: BOP'S AND HYDRIL WILL BE INSTALLED ON THE 9 5/8" CASING AND TESTED DAILY. TIME TO WITNESS CEMENTING THE 9 5/8" CASING

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.
Signature: Ken Beardemphl

Printed name: Ken Beardemphl

Title: Landman

Date: 8/24/94

Phone: 748-1471

OIL CONSERVATION DIVISION

Approved: Mark Behlitz

Title: GEOLOGIST

Approval Date: 10-7-94

Expiration Date: 4-7-95

Conditions of Approval:

Attached ☐

District I
PO Box 1980, Hobbs, NM 88240-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-102
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-015-28149	² Pool Code 15472	³ Pool Name DAGGER DROW, UPPER PENN, NORTH
⁴ Property Code ALTO AOL COM	⁵ Property Name	⁶ Well Number 1
⁷ OGRID No.	⁸ Operator Name YATES PETROLEUM CORPORATION	⁹ Elevation 3472.

¹⁰ Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
H	21	19S	25E		1980	NORTH	660	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County

¹² Dedicated Acres 160	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

16		¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief. Signature: <i>Ken Beardemphl</i> Printed Name: KEN BEARDEMPHL Title: LANDMAN Date: 8/24/94
		¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. Date of Survey: AUGUST 23, 1994 Signature and Seal of Professional Surveyor: <i>[Signature]</i> Certificate Number: 5412 NM PES NO. 5412

YATES PETROLEUM CORPORATION




EXHIBIT B

THE FOLLOWING CONSTITUTES THE MINIMUM BLOWOUT PREVENTER REQUIREMENTS FOR 3000 PSI WP SYSTEMS

1. All preventers to be hydraulically operated with secondary manual controls installed prior to drilling out from under casing.
2. Choke outlet to be a minimum of 3" diameter.
3. Kill line to be of all steel construction of 3" minimum diameter.
4. All connections from operating manifolds to preventers to be all steel. Hole or tube to be a minimum of one inch in diameter.
5. The available closing pressure shall be at least 15% in excess of that required with sufficient volume to operate the B.O.P.'s.
6. All connections to and from preventer to have a pressure rating equivalent to that of the B.O.P.'s.
7. Inside blowout preventer to be available on rig floor.
8. Operating controls to be located a safe distance from the rig floor.
9. Hole must be kept filled on trips below intermediate casing.