



**DRILLING CONTROL
CONDITION II-B 3000 WP
FOR AIR DRILLING OR
WHERE NITROGEN OR AIR BLOWS ARE EXPECTED**

H₂S TRIM REQUIRED
YES _____ NO _____



DRILLING CONTROL

MATERIAL LIST - CONDITION II - B

- A Texaco Wellhead
- B 3000 W.P. drilling spool with a 2" minimum flanged outlet for kill line and 3" minimum flanged outlet for choke line.
- C 3000 W.P. Seal ram type preventer, hydraulic operated with 1" steel, 3000 W.P. control lines (where sub-structure height is adequate, 1 - 3000 W.P. single ram type preventers may be utilized).
- D Rotating Head with fill up outlet and extended blow line.
- 1,3,4, 2" minimum 3000 W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve.
- 7,8, 2" minimum 3000 W.P. back pressure valve.
- 9 3" minimum 3000 W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve.
- 12 3" minimum schedule 80, Grade "B", seamless line pipe.
- 13 2" minimum x 3" minimum 3000 W.P. flanged cross.
- 10,11 2" minimum 3000 W.P. adjustable choke bodies.
- 14 Cameron Mud Gauge or equivalent (location optional in choke line).
- 15 2" minimum 3000 W.P. flanged or threaded full opening steel gate valve, or Halliburton Lo Torc Plug valve.



TEXACO, INC.
WOLFE DIVISION
HOUSTON, TEXAS



SCALE	DATE	REV	NO	DRW NO
DRAWN BY				
CHECKED BY				

EXHIBIT

C