



**DRILLING CONTROL  
CONDITION II-B 3000 WP  
FOR AIR DRILLING OR  
WHERE NITROGEN OR AIR BLOWS ARE EXPECTED**

H<sub>2</sub>S TRIM REQUIRED  
YES \_\_\_\_\_ NO \_\_\_\_\_



**ILLEGIBLE**

DRILLING CONTROL

MATERIAL LIST - CONDITION II - B

- |            |                                                                                                                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| A          | Texaco Wellhead                                                                                                                                                                                     |
| B          | 3000# W.P. drilling spool with a 2" minimum flanged outlet for kill line and 3" minimum flanged outlet for choke line.                                                                              |
| C          | 3000# W.P. Dual ram type preventer, hydraulic operated with 1" steel, 3000# W.P. control lines (where sub-structure height is adequate, 2 - 3000# W.P. single ram type preventers may be utilized). |
| D          | Rotating Head with fill up outlet and extended Blooe Line.                                                                                                                                          |
| 1,3,4,7,8, | 2" minimum 3000# W.P. flanged full opening steel gate valve, or Malliburton Lo Torc Plug valve.                                                                                                     |
| 2          | 2" minimum 3000# W.P. back pressure valve.                                                                                                                                                          |
| 5,6,9      | 3" minimum 3000# W.P. flanged full opening steel gate valve, or Malliburton Lo Torc Plug valve.                                                                                                     |
| 12         | 3" minimum schedule 60, Grade "B", seamless line pipe.                                                                                                                                              |
| 13         | 2" minimum x 3" minimum 3000# W.P. flanged cross.                                                                                                                                                   |
| 10,11      | 2" minimum 3000# W.P. adjustable choke bodies.                                                                                                                                                      |
| 14         | Cameron Mud Gauge or equivalent ( location optional in choke line).                                                                                                                                 |
| 15         | 2" minimum 3000# W.P. flanged or threaded full opening steel gate valve, or Malliburton Lo Torc Plug valve.                                                                                         |



**TEXACO, INC.**  
MIDLAND DIVISION  
MIDLAND, TEXAS



| SCALE       | DATE | EST. NO. | DRG. NO. |
|-------------|------|----------|----------|
| DRAWN BY    |      |          |          |
| CHECKED BY  |      |          |          |
| APPROVED BY |      |          |          |

**EXHIBIT C**