DISTRICT P.O. 5ox 1980, Hobbs, NM 88241-1980

DISTRICT IL P.O. Box Drawer DD, Artesia, NM 88211-0719

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV

State of New Mexico Energy, Minerals and Natural Resources Depart

Revised February 10,1994 Instructions on back

■ AMENDED REPORT

Submit to Appropriate District Office

State Lease - 6 Copies Fee Lease - 5 Copies

3

## OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

P.O. Box 2088, Santa Fe, NM 87504-2088 APPLICATION FOR PERM	AIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR	ADD A ZONE
<sup>1</sup> Operator Name a		<sup>2</sup> OGRID Number 022351
TEXACO EXPLORATION & PRODUCTION INC.	etr dige	3
P.O. Box 3109, Midland Texas 79702	Olegen a v	API Number 30-015 - 28423
<sup>4</sup> Property Code	<sup>5</sup> Property Name	<sup>6</sup> Weli No.

Surface Location

Surface Location									
Ul or lot no.	Section	Township	Range	Lot.ldn	Feet From The	North/South Line	Feet From The	East/West Line	County
UI OF IOU NO.	19	23-S	30-E	Location	660	SOUTH	660	WEST	EDDY
	19	25-3		1	l .				

REMUDA BASIN '19' STATE

<sup>8</sup> Proposed Bottom Hole Location If Different From Surface

Ul or lot no.	Section	Township	Range	Lot.ldn	Feet From	The	North/South Line	Feet From The	East/West Line	County
	UN	9 Proposed DESIGNATED B		-10	035 dect:	Ge	4	<sup>10</sup> Proposed Poo JNDESIGNATED BO		

11 Work Type Code	12 WellType Code	Rotary or C.T.	14 Lease Type Code S	15 Ground Level Elevation 3041'	
N 16 Multiple	17 Proposed Depth	18 Formation	19 Contractor	<sup>20</sup> Spud Date	
No	7500′	BRUSHY CAN/BONE SPG.		4/1/95	

**Proposed Casing and Cement Program** 

SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
8 5/8	24#	400'	200 SACKS	SURFACE
	15.5#	7500'	1650 SACKS	SURFACE
			PostIl	)-/
			4-7-9	1 .
			Murlar	APF
	SIZE OF CASING 8 5/8 5 1/2	8 5/8 24\$	8 5/8 24# 400'	8 5/8 24# 400' 200 SACKS 5 1/2 15.5# 7500' 1650 SACKS

22 Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zoneend proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

**CEMENTING PROGRAM:** 

SURFACE CASING: 200 SACKS CLASS C (14.8 PPG, 1.34 CF/S, 6.31 GW/S).

PRODUCTION CASING: 1st STG - 300 SACKS 35/65 POZ H w/ 6% GEL, 5% SALT, 1/4# FC (12.4 PPG, 2.14 CF/S, 11.9 GW/S). F/B 450 SACKS 50/50 POZ H w/ 2% GEL, 5% SALT, 1/4# FC (14.2 PPG, 1.35 CF/S, 6.3 GW/S).

DV TOOL @ 4500": 2nd STG - 800 SACKS 35/65 POZ H w/ 6% GEL, 5% SALT, 1/4# FC (12.4 PPG, 2.14 CF/S, 11.9 GW/S). F/B 100 SACKS CLASS H w/ 2% CC (15.6 PPG, 1.19 CF/S, 5.2 GW/S).

THERE ARE NO OTHER OPERATORS IN THIS QUARTER QUARTER SECTION.

23 I hereby certify that the rules and regulations of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief.	OIL CONSERVATION DIVISION			
Signature C. Wolfe Howard  Printed Name C. Wade Howard	Approved By: ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR Title:			
Title Eng. Assistant	Approval Date: MAR 3 0 1995 Expiration Date: 9-30-95			
Date 2/28/95 Telephone 688-4606	Conditions of Approval: Attached			