

DISTRICT I

P.O. Box 1890, Hobbs, NM 88241-1890

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88211-0719

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV

P.O. Box 2088, Santa Fe, NM 87504-2088

State of New Mexico

Energy, Minerals and Natural Resources Dep. ent

Form C-101

Revised February 10, 1994

Instructions on back

Submit to Appropriate District Office

State Lease - 6 Copies

Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUG BACK, OR ADD A ZONE

RECEIVED

1 Operator Name and Address TEXACO EXPLORATION & PRODUCTION INC. P.O. Box 3109, Midland Texas 79702		2 OGRID Number 022351
4 Property Code 18891		5 Property Name OIL CON. DIV. REMUDA BASIN '19' STATE SWD DIST. 2
		3 API Number 30-015-28957
		6 Well No. 1

7 Surface Location									County
UI or lot no. F	Section 19	Township 23-S	Range 30-E	Lot.Idn	Feet From The 2625	North/South Line NORTH	Feet From The 1500	East/West Line WEST	Edmon

8 Proposed Bottom Hole Location If Different From Surface									
UI or lot no.	Section	Township	Range	Lot.Idn	Feet From The	North/South Line	Feet From The	East/West Line	County
9 Proposed Pool 1 UNDESIGNATED-BELL CANYON					10 Proposed Pool 2 96100 SWD, Delaware				

11 Work Type Code N	12 WellType Code S	13 Rotary or C.T. ROTARY	14 Lease Type Code S	15 Ground Level Elevation 3045'
16 Multiple No	17 Proposed Depth 3900'	18 Formation BELL CANYON	19 Contractor NABORS	20 Spud Date 5/1/96

21 Proposed Casing and Cement Program					
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
12 1/4	8 5/8	24#	400'	300 SACKS	SURFACE
7 7/8	5 1/2	15.5#	3200'	600 SACKS	SURFACE
				Part ID-1 5-3-96 New Lee & APZ	

22 Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

CEMENTING PROGRAM:

SURFACE CASING - 300 SACKS CLASS C w/ 2% CACL2 (14.8, 1.34 CF/S, 6.3 GW/S).

PRODUCTION CASING - 500 SACKS 35/65 POZ CLASS H w/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.4 PPG, 2.14 CF/S, 11.9 GW/S). F/B 100 SACKS CLASS H (15.6 PPG, 1.18 CF/S, 5.2 GW/S).

SALT WATER DISPOSAL WELL: OPEN HLOE COMPLETION FROM 3200' TO 3900'.

THERE ARE NO OTHER OPERATORS IN THIS QUARTER QUARTER SECTION.

Notify N.M.O.C.C. in sufficient time to witness cementing the 5 1/2" casing

NISK-SWD-626

23 I hereby certify that the rules and regulations of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief.		OIL CONSERVATION DIVISION	
Signature C. Wade Howard		Approved By: ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR	
Printed Name C. Wade Howard		Title:	
Title Eng. Assistant		Approval Date: 4-30-96 Expiration Date: 4-30-97	
Date 4/8/96	Telephone 688-4606	Conditions of Approval: Attached ☐	

APPLICATION EXPIRED 4-30-97