

- B. The average grade will be less than 1%.
- C. No turnouts are planned.
- D. No additional cattleguards or gates are needed.
- E. Surfacing material will consist of native caliche. Caliche will be obtained from the nearest approved caliche pit. Any additional materials that are required will be purchased from the dirt contractor.
- F. The proposed access road is shown in Exhibit #3. It is +/- 500' long and will be included in the archeological survey.

3. Location of Existing Wells:

Exhibit #4 shows all existing wells within a one-mile radius of this well.

4. Location of Existing and/or Proposed Facilities:

- A. If the well is productive, contemplated facilities will be constructed on the existing site of the Santa Nina Federal #1 Battery.
- B. If the well is productive, contemplated facilities will be as follows:
  - 1. Two inch (2") SDR-11 plastic flowline will be laid beside proposed access road to the existing battery as shown in Exhibit #5.
  - 2. Power will be required if the well is productive. Proposed powerline right-of-way is shown on Exhibit #5.
- C. If the well is productive, rehabilitation plans are as follows:
  - 1. The reserve pit will be back-filled after the contents of the pit are dry (within 120 days after the well is complete).
  - 2. Topsoil removed from the drill site will be used to re-contour the pit area to the original natural level, as nearly as possible, and re-seeded as per BLM specifications.