

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(Other instructions on
N. M. OIL CONS. DIVISION
1ST ST
ARTESIA, NM 86211

FORM APPROVED
OMB NO. 1004-0136
Expires: February 28, 1995

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. TYPE OF WORK

DRILL ☒

DEEPEN ☐

b. TYPE OF WELL

OIL WELL ☒

GAS WELL ☐

OTHER

SINGLE ZONE ☒

MULTIPLE ZONE ☐

2. NAME OF OPERATOR

POGO PRODUCING COMPANY

(RICHARD WRIGHT 915-685-8140) 17891

3. ADDRESS AND TELEPHONE NO.

P.O. BOX 10340 MIDLAND, TEXAS 79702-7340 915-685-8100

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

1980' FNL & 990' FEL SEC. 26 T22S-R31E EDDY CO. NM
At proposed prod. zone SAME

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE

Unit H

15. DISTANCE FROM PROPOSED

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drilg. unit line, if any)

990'

16. NO. OF ACRES IN LEASE

640

17. NO. OF ACRES ASSIGNED
TO THIS WELL

40

18. DISTANCE FROM PROPOSED LOCATION
TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

1320'

19. PROPOSED DEPTH

8500'

20. ROTARY OR CABLE TOOLS

ROTARY

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3538' GR.

22. APPROX. DATE WORK WILL START
As soon as approved

SECRETARY'S POTASH

R-111-P POTASH

CANON CONTROLLED WATER BASIN

SIZE OF HOLE	GRADE SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
25"	CONDUCTOR 20"	NA	40'	Cement to surface with Redi-mix
14 3/4"	10 3/4"	32.75	800'	750 Sx. circulate to surface
9 7/8"	7 5/8"	26.4	4300'	1000 Sx. Circulate to surface
6 3/4"	4 1/2"	11.6	8500'	1500 Sx. Circulate to surface.

1. Drill 25" hole to 40'. Set 40' of 20" conductor pipe and cement to surfave with Redi-mix.
2. Drill 14 3/4" hole to 800'. Run and set 800' of 10 3/4" 32.75# H-40 ST&C casing. Cement with 750 Sx. of Class "C" cement + additives, circulate cement to surface.
3. Drill 9 7/8" hole to 4300' Run and set 4300' of 7 5/8" 26.4# J-55 ST&C casing. Cement with 1000 Sx. of Class "C" cement + additives, circulate cement to surface.
4. Drill 6 3/4" hole to 8500'. Run and set 8500' of 4 1/2" 11.6# J-55 ST&C casing. Cement with 1500 Sx. of Class "H" = additives. Set DV Tools at 6000'± & 4000'±, circulate cement to surface.

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS

Notify OCD at SPUD & TIM
to witness cementing the
10 3/4" 7 5/8" casing.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Attach map showing location of well if any.

SIGNED Test Garcia TITLE Agent

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

DATE 01/27/00

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. CONDITIONS OF APPROVAL IF ANY:

APPROVED BY 15/Carsten F Goff

TITLE Acting State Director

DATE

4-13-00
APPROVED FOR 1 YEAR

*See Instructions On Reverse Side

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.