

## AUXILIARY EQUIPMENT

DRAWWORKS	BDW 650 HP, with Parmac Hydromatic brake
ENGINES	Two Caterpillar D-353 diesels rated at 425 HP each
ROTARY	Ideco 23", 300 ton capacity
MAST/SUB	Ideal 132', 550,000 lb. rated static hook load with 10 lines. Wagner 15' high substructure
TRAVELING EQUIPMENT	Gardner-Denver, 300 ton, 5 sheave w/BJ 250 ton hook Brewster Model 7 SX 300 ton swivel
PUMPS	Continental-EMSCO DC-700 and DB-550, 5-1/2 X 16" Duplex, Compound driven.
PIT SYSTEM	1-Shale Pit 6X7X35', 1-Setting Pit 6X7X38', 1-Suction Pit 6X7X34' w/5 mud agitators, Two Centrifugal mud mixing pumps and a Double Screen Shale Shaker.
LIGHT PLANT	Two CAT 3306 diesel electric sets 18 KW prime power
BOP EQUIP.	13-5/8" 5000 psi WP double ram and 13-5/8" 5000 psi WP Shaffer Annular Preventer. Choke manifold rated at 5000 psi. Valvcon 5-station 80 gallon closing unit.

Exhibit "D"  
Santa Fe Snyder Corp.  
Old Ranch Knoll "8" Fed #6  
Section 8, T-22-S, R-24-E  
Eddy County, New Mexico