

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT APPLICATION
(Other instructions on
reverse side)

FORM APPROVED
OMB NO. 1004-0136
Expires February 28, 1995

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. TYPE OF WORK

Drill

☒

Deepen

☐

b. TYPE OF WELL

Oil Well

☒

Gas Well

☐

Other

Single Zone

☐

Multiple Zone

☐

2. NAME OF OPERATOR

Shahara Oil, LLC

3. ADDRESS AND TELEPHONE NO.

207 W. McKay
Carlsbad, NM 88220

Phone: 505-885-5433
Fax: 505-885-4989

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements *)

At surface

2080' FNL & 1300' FWL, Unit E

At proposed prod. zone

Same **SUBJECT TO LIKE APPROVAL BY STATE**

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE *

1.5 miles southeast of Loco Hills, NM

15. DISTANCE FROM PROPOSED *

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.

1360'

(Also to nearest drlg. unit line, if any)

18. DISTANCE FROM PROPOSED LOCATION*

TO NEAREST WELL, DRILLING, COMPLETED,

760'

OR APPLIED FOR, ON THIS LEASE, FT.

21. ELEVATIONS (Show whether DF, RT, GR, etc)

3633' GR

SIZE OF HOLE

GRADE, SIZE OF CASING

WEIGHT PER FOOT

SETTING DEPTH

QUANTITY OF CEMENT

12 1/4"

8 5/8"

24# K-55

500'

300 sx - circulate

7 7/8"

5 1/2"

15.5# J-55

3600'

600 sx -

100' above 8 5/8" csg shoe

The operator proposes to drill to a depth sufficient to test the Queen, Grayburg and Upper San Andres for oil. Specific programs are outlined in the following attachments:

SURFACE USE AND OPERATING PLAN

EXHIBIT A - ROAD MAP

EXHIBIT B - EXISTING WELL MAP

EXHIBIT C - LOCATION AND ACREAGE DEDICATION PLAT

EXHIBIT C-1 - TOPO MAP

EXHIBIT D - DRILLING AND RIG LAYOUT

EXHIBIT E - 3M BOP EQUIPMENT

Permit Controlled Water Basin

**APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS
ATTACHED**

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

TITLE

DATE

2/2/01

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

TITLE

DATE

FIELD MANAGER

5-14-01

*See Instructions On Reverse Side

APPROVAL FOR 1 YEAR

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

RECEIVED

FEB 05 '01

RECEIVED, NM

DRILLING PROGRAM

Shahara Oil, LLC
Grayburg Jackson PSU AD No. 15
2080' FNL & 1300' FWL, Unit E
Section 27, T17S, R30E
Eddy County, New Mexico
Lease No. NM-060528

In connection with Form 3160-3, Application for Permit to Drill subject well, Shahara Oil, LLC. submits the following items of pertinent information in accordance with BLM requirements:

1. Geologic Name of Surface Formation: Permian
2. Estimated Tops of Important Geologic Markers and

<u>Formation</u>	<u>Depth</u>
Top of Salt	525'
Base of Salt	1300'
Queen	2400'
Grayburg	2800'
San Andres	3250'
Total Depth	3600'

3. Estimated Depths of Fresh Water, Oil and Gas:

There is little if any fresh water in this area. Oil is expected in the 7 Rivers, Queen, Grayburg and San Andres below 1900'. No other formations are expected to give up oil, gas or fresh water in measurable quantities. Any surface fresh water sands will be protected by setting 8 5/8" casing at approximately 500' into the anhydrite just above the top of salt and circulating cement to surface. 5 1/2" production casing will be set at TD and cemented to 100' above the 8 5/8" casing shoe.

The pore pressure gradient is normal (± 8.4 ppg) down through the San Andres. No abnormal pressures are anticipated.

4. Casing and Cement Program

<u>Hole Size</u>	<u>Casing</u>		<u>Casing OD</u>	<u>Weight, Grade, Coupling, Cond.</u>
	<u>From</u>	<u>To</u>		
12 1/4"	0'	500'	8 5/8"	24# K-55 STC New
7 7/8"	0'	TD	5 1/2"	15.5# J-55 LTC New

Minimum Design Factors: Collapse 1.125, Burst 1.1, Tension 1.7.

8 5/8" Surface Casing Set at 500'

Cement to surface with 300 sx of Class C with additives.

5 1/2" Production Casing Set at TD

Cement with 600 sx of Class C with additives. Will bring top of cement 100' above the 8 5/8" casing shoe.

5. Minimum Specifications for Pressure Control:

7 7/8" Hole - The following BOP equipment will be nipped up on the 8 5/8" casing and used continuously until TD is reached for the 7 7/8" hole.

The blowout preventer equipment (BOP) shown in Exhibit "E" will consist of a 3000 psi WP double ram type preventer and a 3M annular (bag type) preventer with rotating head. Both BOP's will be hydraulically operated. At the drilling contractor's option, 5M BOP's may be substituted. H₂S trim will not be required.

Before drilling out from under the 8 5/8" surface casing, all BOP's and accessory equipment will be tested to 1000 psi with the rig pump. Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

BLM method to calculate minimum BOP requirements:

$$(0.052)(8.4 \text{ ppg})(3600') - (0.22 \text{ psi/ft})(3600') = 780 \text{ psi}$$

Minimum BOP requirements: 2M BOP stack and manifold system

6. Proposed Mud System:

The well will be drilled to TD with a combination of fresh water and 10# brine. The applicable depths and properties of this system are as follows:

<u>Depth</u>	<u>Type</u>	<u>Weight (ppg)</u>	<u>Viscosity (sec)</u>	<u>Water Loss cc</u>
0-500'	Fresh water	8.4	28	NC
500-3600'	Brine	10.0	29	NC

Sufficient mud materials to maintain mud properties and meet minimum lost circulation requirements will be kept at the well site at all times.

7. Auxiliary Well Control and Monitoring Equipment:

- A kelly cock will be kept in the string at all times.
- A full opening drill pipe stabbing valve (TIW/inside BOP) with proper drill pipe connections will be on the rig floor at all times.
- An electronic pit volume totalizer system will NOT be used. The drilling fluids system will be visually monitored at all time.

8. Logging, Testing and Coring Programs:

- a) Drillstem tests will not be run.
- b) The electric logging program will consist of:
 - GR-DLL-MSFL-Cal - TD-1600'
 - GR-CNL-CDL-Cal - TD-1600'
 - GR-CNL-Cal - TD-Surface
- c) No cores are planned.
- d) Further testing procedures will be determined after the 5 1/2" production casing has been cemented at TD.

9. Abnormal Conditions, Pressures, Temperatures and Potential Hazards:

No abnormal pressures, temperatures, or other potential hazards are anticipated.

No or very little hydrogen sulfide or other hazardous gases or fluids have been encountered, reported, or are known to exist at this depth in this area. No major lost circulation zones have been reported in offsetting wells.

The maximum anticipated bottom hole pressure is approximately 1559 psi.
(3600' x .433 psi/ft = 1559 psi)

The maximum anticipated bottom hole temperature is 100 degrees F.

10. Anticipated Starting Date and Duration of Operations:

Road and location work will not begin until approval has been received from the BLM. The anticipated spud date is July 1, 2001. Once commenced, the drilling operation should be complete in 10 days. If the well is productive, an additional 20 days will be required for completion, testing, and installation of permanent facilities.

SURFACE USE AND OPERATING PLAN

Shahara Oil, LLC
Grayburg Jackson PSU AD No. 15
2080' FNL & 1300' FWL, Unit E
Section 27, T17S, R30E
Eddy County, New Mexico
Lease No. NM-060528

This plan is submitted with the Application for Permit to Drill the above described well. The purpose of the plan is to describe the location of the proposed well, the proposed construction activities, and the operations plan to be followed in rehabilitating the surface after completion of the operation so that a complete appraisal can be made of the environmental effects associated with the operations.

<u>Located:</u>	1.5 miles southeast of Loco Hills, New Mexico
<u>Federal Lease Number:</u>	NM-060528
<u>Lease Issued:</u>	N/A
<u>Acres in Lease (Unit):</u>	960 acres
<u>Record lessee:</u>	Phillips Petroleum Company
<u>Surface Ownership:</u>	Federal
<u>Grazing Permittee:</u>	Charles Martin, Inc.
<u>Pool:</u>	Grayburg Jackson 7R-QN-GB-SA
<u>Pool Rules:</u>	This well is being drilled as a producing well in the Grayburg Jackson Premier Sand Unit waterflood to be completed only in the unitized Premier Sand of the Grayburg formation under Oil Conservation Division Order No. R-2749.
<u>Exhibits:</u>	"A" Road Map "B" Existing Wells Map "C" Well Location and Acreage Dedication Plat "C-1" Topo Map (Location Verification Map) "D" Drilling Rig Layout Diagram "E" BOP Equipment

1. **Existing Roads:**

- a) The well site and elevation plat for the proposed well is shown in Exhibit "C". It was staked by John West Engineering, Hobbs, NM.
- b) All roads to the location are shown on Exhibit "A". The existing roads are illustrated in yellow and are adequate for travel during drilling and production operations. Upgrading of the road prior to drilling will be done where necessary as determined during the on-site inspection.
- c) Directions to location: From Loco Hills, go south on County Road 217 (Hagerman Cut-off Road) 0.3 miles, go southeast staying on main caliche road 1 ¼ miles, go northeast 0.4 miles, go southeast 0.15 miles to location on left.
- d) Routing grading and maintenance of existing roads will be conducted as necessary to maintain their condition as long as any operations continue on this lease.

2. **Proposed Access Road:**

No access road necessary.

3. **Location of Existing Wells:**

Exhibit "B" shows all existing wells within a one-mile radius of this well.

4. **Location of Existing and/or Proposed Facilities:**

- a) Shahara Oil, LLC operates a production facility on the Grayburg Jackson WFU.
- b) If the oil well proves to be commercial, the necessary production facilities will be installed on the drilling pad and flow lines will be installed to the production facilities and storage tanks. Flowlines will follow access roads and tie in to existing flowlines where possible.
- c) An electric powerline will be required. Central Valley Electric Cooperative, Inc. of Artesia is currently engineering the plans. A Sundry Notice will be submitted concerning the electric powerlines as soon as possible.

5. **Location and Type of Water Supply:**

The well will be drilled with a combination of brine and fresh water mud system as outlined in the drilling program.

The water necessary for drilling operations will be purchased and trucked to the wellsite, or will be moved to the well site by way of a temporary pipeline laid on the ground along existing and proposed roads.

*W/ Sundry
APPROVAL
TSU*

6. **Source of Construction Materials:**

Caliche needed for the road and well pad will be taken from the proposed reserve pit. An alternate plan will be to obtain caliche from a borrow pit located within the 400' x 400' archaeologically cleared tract at the proposed well site. If sufficient quality or quantity of caliche is not available, it will be transported to the proposed road and well site from an existing BLM approved caliche pit. The BLM will be notified and consulted if caliche must be obtained off location.

7. **Method of Handling Waste Disposal:**

- a) Drill cuttings will be disposed into the reserve pit.
- b) Drilling fluids will be contained in the reserve pit. The reserve pit will be an earthen pit, approximately 150' x 150' x 6' deep and fenced on three sides prior to drilling. The fourth side will be fenced immediately following rig removal. The reserve pit will be lined with plastic (5-7 mil thickness) to minimize loss of drilling fluids.
- c) Water produced from the well during completion may be disposed into the reserve pit or a steel tank (depending upon rates).
- d) Drilling fluids will be allowed to evaporate in the drilling pits until the pits are dry.
- e) Oil produced during testing will be stored in steel test tanks until sold.
- f) Trash, waste paper, garbage and junk will be placed in a trash bin located on the drill site pad. it will be transported to an approved landfill for disposal within 30 days after completion of drilling and/or completion of operations. All waste material will be contained to prevent scattering by the wind.
- g) A portable chemical toilet will be provided on the location for human waste during the drilling and completion operations.

8. **Ancillary Facilities:**

No other facilities will be built as a result of the operations on this well.

9. **Well Site Layout:**

- a) Exhibit "D" shows the relative location and dimensions of the well pad, mud pits, reserve pit, location of the major rig components, and location of parking area.
- b) Cut and fill requirements will be minor, but clearing and leveling of the well site will be necessary. Top soil, if available, will be stockpiled per BLM specifications as determined at the on-site inspection.

- c) The reserve pit will be lined with a high quality plastic sheeting (5-7 mil thickness).
- d) The pad and pit area are staked and flagged.

10. **Plans for Reclamation of the Surface:**

- a) After completion of drilling and/or completion of operations, all equipment and other material not needed for operations will be removed. The pit area will be allowed to dry before reclamation. If the borrow pit is constructed, the cuttings in the reserve pit will be deep buried in the borrow pit, and the reserve pit and borrow pit will be broken out, filled, and leveled. The location will be cleaned of all trash and junk to leave the well site in an aesthetically pleasing condition as possible.
- b) Three sides of the reserve pit will be fenced prior to and during drilling operations. The borrow pit will be fenced on all four sides after the location is built. At the time the rig is removed, the reserve pit will be fenced on the fourth side to prevent livestock or wildlife from being entrapped in the pit. The fencing will remain in place until the pits are cleaned up and leveled.
- c) After abandonment, all equipment, trash and junk will be removed and the well site will be cleaned.
- d) Topsoil removed from the drill site will be used to recontour the pit area to the original natural level. The disturbed area will be revegetated by reseeding during the proper growing season with a seed mixture of native grasses as recommended by the BLM.

11. **Other Information:**

- a) Topography: The land surface in the area is undulating with small sand dunes. In the immediate area of the well site, the land slope is to the southwest.
- b) Soil: Top soil at the well site is loamy sand.
- c) Flora and Fauna: The vegetation cover is moderate. It includes range grasses, weeds, scrub oak bushes, and mesquite bushes. Wildlife in the area is that typical of a semi-arid desert land and includes coyotes, rabbits, rodents, reptiles, hawks, dove, quail and other small birds.
- d) Ponds and Streams: There are no rivers or streams within a mile of this proposed location.
- e) Residences and Other Structures: There are no occupied dwellings within a mile of this location.
- f) Archaeological, Historical, or Other Cultural Sites: None are known in the area. An archaeological survey has been conducted by Geo-Marine Inc.

h) Surface Ownership: Federal

12. **Operator's Representative:**


Perry L. Hughes, Executive Officer
Shahara Oil, LLC
207 W. McKay
Carlsbad, NM 88220

Phone: 505-885-5433
Fax: 505-885-4989

13. **Certification:**

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operations proposed herein will be performed by Shahara Oil, LLC and its contractors and sub-contractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of false statement.

2/2/01
Date


Perry L. Hughes, Executive Officer

HYDROGEN SULFIDE DRILLING OPERATIONS PLAN

APPLICABILITY:

The provisions of this plan are effective when drilling operations are conducted in areas where zones may be penetrated that are known to contain, or may be reasonably expected to contain, hydrogen sulfide gas in concentrations of 100 parts per million or more.

TRAINING REQUIREMENTS:

- A. When conducting drilling operations in an area where hydrogen sulfide gas might be encountered, all personnel at the well site will have had proper training in the following areas:
 - 1. The hazards and characteristics of hydrogen sulfide gas (H₂S).
 - 2. Toxicity of hydrogen sulfide and sulfur dioxide.
 - 3. Hydrogen sulfide gas detectors, warning systems, evacuation procedures, and proper use and maintenance of personal protective equipment.
 - 4. Proper rescue procedures, first aid, and artificial respiration.
- B. In addition, supervisory personnel will be trained in the following areas:
 - 1. The effects of hydrogen sulfide on metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
 - 2. Corrective action and shut-in procedures when drilling or reworking a well, and blowout prevention and well control procedures.
 - 3. The contents and requirements of the Hydrogen Sulfide Drilling Operations Plan and the Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable hydrogen sulfide zone (within 3 days or 500 feet) and weekly hydrogen sulfide and well control drills for all personnel in each crew. The initial training session will include a review of the site specific Hydrogen Sulfide Drilling Operations Plan and the Public Protection Plan. This plan will be available at the well site. All personnel will be required to carry documentation that they have received the proper training.

WELL SITE DIAGRAM:

A. Attached is a detailed well site diagram showing:

1. Drilling rig orientation
2. Prevailing wind direction (Southwest)
3. Location of briefing areas
4. Location of Caution/Danger signs
5. Location of hydrogen sulfide monitors
6. Location of wind direction indicators

HYDROGEN SULFIDE SAFETY EQUIPMENT:

- A. All safety equipment and systems will be installed, tested, and deemed operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone reasonably expected to contain hydrogen sulfide.
- B. During drilling operations, a flare line will be routed from the BOP manifold to the reserve pit. Should suspected sour gas be vented through the flare line, a flare pistol will be used to ignite the flare.
- C. Protective equipment for essential personnel will be installed and maintained as follows:
1. 30-minute air packs will be maintained on the rig floor and near the briefing area.
 2. 30-minute work units will be maintained at the H₂S trailer and/or on the rig floor.
 3. 30-minute escape units will be maintained on the rig floor.
 4. 300 cubic ft. air cylinders will be maintained in the H₂S trailer.
 5. Associated breathing air equipment will also be installed and maintained.
 6. Hydrogen sulfide monitor will be located in the dog house on the rig floor with sensors placed on the rig floor, at the bell nipple, the shale shaker, and in the pit areas.
 7. An audible/visual alarm will be located near the dog house on the rig floor.

VISUAL WARNING SYSTEMS:

- A. High visibility Caution/Danger signs will be posted on roads providing direct access to the well location.
- B. Green, yellow and red conditions flags to be displayed to denote Normal Conditions, Potential

Danger and Danger, H₂S present.

- C. Wind socks to be located at the protection center and in the pit area to continuously indicate wind direction.

CIRCULATING MEDIUM:

- A. Drilling fluid to be conditioned to minimize the volume of H₂S circulated to the surface.

SPECIAL WELL CONTROL EQUIPMENT:

- A. In addition to the normal BOP stack and choke manifold, a drilling head will be used to help control and H₂S contaminated drilling fluid.

WELL TESTING:

- A. Drill stem testing of zones known, or reasonably expected, to contain H₂S in concentrations of 100 ppm or more will use the closed chamber method of testing.

COMMUNICATION:

- A. Radio communication will be available at the drilling rig and also in company vehicles.


ADDITIONAL INFORMATION:

- A. Additional information concerning Emergency Reaction Steps, Ignition Procedures, Training Requirements and Emergency Equipment Requirements will be available on location at the well site.


Exhibit "A"

Road Map

Shahara Oil, LLC
Grayburg Jackson PSU AD No. 15
2080' FNL & 1300' FWL, Unit E
Section 27, T17S, R30E
Eddy County, New Mexico
Lease No. LC-060528



Shahara Oil, LLC
Grayburg Jackson PSU AD No. 15
 2080' FNL & 1300' FWL, Unit E
 Section 27, T17S, R30E
 Eddy County, New Mexico
 Lease No. LC-060528

 Proposed Well

DISTRICT I
P.O. Box 1980, Hobbs, NM 88241-1980

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised February 10, 1994
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

DISTRICT II
P.O. Drawer DD, Artesia, NM 88211-0719

DISTRICT III
1000 Rio Brazos Rd., Artesia, NM 87410

DISTRICT IV
P.O. BOX 2088, SANTA FE, N.M. 87504-2088

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	Pool Code	Pool Name
Property Code	Property Name GRAYBURG JACKSON PSU AD	Well Number 15
OGRID No.	Operator Name SHAHARA OIL, LLC	Elevation 3633

Surface Location




UL or lot No. E	Section 27	Township 17-S	Range 30-E	Lot Idn	Feet from the 2080	North/South line NORTH	Feet from the 1300	East/West line WEST	County EDDY
--------------------	---------------	------------------	---------------	---------	-----------------------	---------------------------	-----------------------	------------------------	----------------

Bottom Hole Location If Different From Surface


UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
---------------	---------	----------	-------	---------	---------------	------------------	---------------	----------------	--------

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
-----------------	-----------------	--------------------	-----------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	OPERATOR CERTIFICATION I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief.  Signature Perry L. HUGHES Printed Name E.O. Title 1/18/01 Date	
	SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. JANUARY 6, 2001 Date Surveyed AWB Signature & Seal of Professional Surveyor  00-11-1381	
	Certificate No. RONALD J. EIDSON 3239 GARY EIDSON 12641	

VICINITY MAP



SCALE: 1" = 2 MILES

SEC. 27 TWP. 17-S RGE. 30-E

SURVEY N.M.P.M.

COUNTY EDDY

DESCRIPTION 2080'FNL & 1300'FWL

ELEVATION 3633

OPERATOR SHAHARA OIL, LLC

LEASE GRAYBURG JACKSON PSU AD

JOHN WEST SURVEYING
HOBBS, NEW MEXICO
(505) 393-3117

LOCATION VERIFICATION MAP



SCALE: 1" = 2000'

CONTOUR INTERVAL: 10'
LOCO HILLS N.M.

SEC. 27 TWP. 17-S RGE. 30-E

SURVEY _____ N.M.P.M.

COUNTY _____ EDDY

DESCRIPTION 2080'FNL & 1300'FWL

ELEVATION _____ 3633

OPERATOR _____ SHAHARA OIL, LLC

LEASE GRAYBURG JACKSON PSU AD

U.S.G.S. TOPOGRAPHIC MAP
LOCO HILLS N.M.

Exhibit "C-1"

Location Verification Map

Shahara Oil, LLC

Grayburg Jackson PSU AD No. 15

2080' FNL & 1300' FWL, Unit E

Section 27, T17S, R30E


Eddy County, New Mexico

Lease No. LC-060528


Exhibit "D"

RIG LAYOUT

Shahara Oil, LLC
 Grayburg Jackson PSU AD No. 15
 2080' FNL & 1300' FWL, Unit E
 Section 27, T17S, R30E
 Eddy County, New Mexico
 Lease No. LC-060528



Prevailing Wind Direction
 Southwest



~~ACCESS ROAD~~
 TSD

- ◆ - H2S Monitors with alarms at the bell nipple and shale shaker
- △ - Wind Direction Indicators
- - Safe Briefing areas with caution signs and protective breathing equipment. Min. 150 ft from wellhead.

7 MINIMUM BLOWOUT PREVENTER REQUIREMENTS

3,000 psi Working Pressure

3 MWP

STACK REQUIREMENTS

No.	Item	Min. I.D.	Min. Nominal
1	Flowline		
2	Fill up line		2"
3	Drilling nipple		
5	Two single or one dual hydraulically operated rams		
6a	Drilling spool with 2" min. kill line and 3" min choke line outlets		
6b	2" min. kill line and 3" min. choke line outlets in ram. (Alternate to 6a above.)		
7	Valve Gate <input type="checkbox"/> Plug <input type="checkbox"/>	3-1/8"	
8	Gate valve—power operated	3-1/8"	
9	Line to choke manifold		3"
10	Valves Gate <input type="checkbox"/> Plug <input type="checkbox"/>	2-1/16"	
11	Check valve	2-1/16"	
12	Casing head		
13	Valve Gate <input type="checkbox"/> Plug <input type="checkbox"/>	1-13/16"	
14	Pressure gauge with needle valve		
15	Kill line to rig mud pump manifold		2"

OPTIONAL

16	Flanged valve	1-13/16"	
----	---------------	----------	--

Exhibit "E"

BOP Equipment

Shahara Oil, LLC

Grayburg Jackson PSU AD No. 15


2080' FNL & 1300' FWL, Unit E

Section 27, T17S, R30E

Eddy County, New Mexico

Lease No. LC-060528

CONFIGURATION



CONTRACTOR'S OPTION TO FURNISH:

1. All equipment and connections above bradenhead or casinghead. Working pressure of preventers to be 3,000 psi. minimum.
2. Automatic accumulator (80 gallon, minimum) capable of closing BOP in 30 seconds or less and, holding them closed against full rated working pressure.
3. BOP controls, to be located near drillers position.
4. Kelly equipped with Kelly cock.
5. Inside blowout preventer or its equivalent on derrick floor at all times with proper threads to fit pipe being used.
6. Kelly saver-sub equipped with rubber casing protector at all times.
7. Plug type blowout preventer tester.
8. Extra set pipe rams to fit drill pipe in use on location at all times.
9. Type RX ring gaskets in place of Type R.

MEC TO FURNISH:

1. Bradenhead or casinghead and side valves.
2. Wear bushing, if required.

GENERAL NOTES:

1. Deviations from this drawing may be made only with the express permission of MEC's Drilling Manager.
2. All connections, valves, fittings, piping, etc., subject to well or pump pressure must be flanged (suitable clamp connections acceptable) and have minimum working pressure equal to rated working pressure of preventers up through choke. Valves must be full opening and suitable for high pressure mud service.
3. Controls to be of standard design and each marked, showing opening and closing position.
4. Chokes will be positioned so as not to hamper or delay changing of choke beans. Replaceable parts for adjustable choke, other bean sizes, retainers, and choke wrenches to be conveniently located for immediate use.
5. All valves to be equipped with handwheels or handles ready for immediate use.
6. Choke lines must be suitably anchored.

7. Handwheels and extensions to be connected and ready for use.
8. Valves adjacent to drilling spool to be kept open. Use outside valve except for emergency.
9. All seamless steel control piping (3000 psi working pressure) to have flexible joints to avoid stress. Hoses will be permitted.
10. Casinghead connections shall not be used except in case of emergency.
11. Do not use kill line for routine fill-up operations.