

2. Well Control Systems

A. Blowout Prevention Equipment

Equipment includes but is not limited to:

- a. pipe rams to accommodate all pipe sizes
- b. blind rams
- c. choke manifold
- d. closing unit

Auxiliary equipment added as appropriate includes:

- | | | |
|----|----------------------------------|-----------|
| a. | annular preventor | <u>NA</u> |
| b. | rotating head | <u>NA</u> |
| c. | mud-gas separator | <u>NA</u> |
| d. | flare line and means of ignition | <u>NA</u> |
| e. | remote operated choke | <u>NA</u> |

B. Communication

The rig contractor will be required to have a two-way communication capability. Chevron U.S.A. Inc. will have either land-line or mobile telephone capabilities.

C. Mud Program

The mud program has been designed to minimize the volume of H₂S circulated to surface. Proper mud weight, safe drilling practices, and the use of H₂S scavengers when appropriate will minimize hazards when penetrating H₂S bearing formations.

D. No Drill Stem Tests are planned.

III. WELL SITE DIAGRAM

A complete well site diagram including the following information is attached.

- 1. Rig orientation
- 2. Briefing areas
- 3. Ingress and egress
- 4. Pits and flare lines
- 5. Caution and danger signs
- 6. Wind indicators and prevailing wind direction