

| | |
|------------------------|-------------------------------------|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | <input checked="" type="checkbox"/> |
| FILE | <input checked="" type="checkbox"/> |
| U.S.G.S. | |
| LAND OFFICE | <input checked="" type="checkbox"/> |
| OPERATOR | <input checked="" type="checkbox"/> |

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED BY
FEB 10 1984

O. C. D.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SF
Stamps

"TITE HOLE"

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|--|--|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry P&A'd | 5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/> |
| 2. Name of Operator Phillips Petroleum Company ✓ | 5. State Oil & Gas Lease No. Lg 5491 |
| 3. Address of Operator P. O. Box 2920, Casper, Wyoming 82602 | 7. Unit Agreement Name |
| 4. Location of Well UNIT LETTER F 2130 FEET FROM THE North LINE AND 2260 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 29S RANGE 15W NMPM. | 8. Farm or Lease Name Iverson Estate-A |
| 15. Elevation (Show whether DF, RT, GR, etc.) 4484' GL, 4512.5' RKB | 9. Well No. 1-36 |
| | 10. Field and Pool, or Wildcat Wildcat |
| | 12. County Hidalgo |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

October 31, 1983 through November 2, 1983 -

Well was Plugged as Follows:

WIH w/open-ended DP to plug, could not get below 5000'. Mike B. Williams, NM State Engineer, approved plugging at 5000'. All plugs witnessed and approved by same.
Set plugs as follows:

100 sx Class H Cmt Plug, 15.2 ppg, at 5000',
50 sx Class H Cmt Plug, 15.2 ppg, at 3017',
175 sx Class H Cmt Plug, 2% CaCL, at 2116',
WOC. Tag plug at 1860' w/wireline,
100 sx Class H Cmt Plug at 1424',
LDDP. ND BOP. Magnafluxed all DC's, tuboscoped all DP.
25 sx Class H Cmt Plug at Surface.

Installed Dry Hole Marker. Well Plugged & Abandoned 11/2/83.

3-NM O&G CC, Artesia, NM
1-File

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. E. Stuart TITLE Area Manager DATE February 3, 1984

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE FEB 15 1984

CONDITIONS OF APPROVAL, IF ANY: