Fresh 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires July 31, 1996

Lease Serial No.

NMSF-078359

Do not use this form for proposals to drill or reenter an

SUNDRY NOTICES AND REPORTS ON WEL

6. If Indian. Allottee or Tribe Name

abandoned well. Use Form 3160-3 (APD)	for such proposals.31 AN 10: 5	,
SUBMIT IN TRIPLICATE – Other instru		7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well X Oil Well Gas Well Other 2. Name of Operator		Well Name and No. Marcus A-1
Elm Ridge Resources, Inc.		9. API Well No.
3a. Address PO Box 189, Farmington, NM 87499	3b. Phone No. (include area code) 505-632-3476	30-039-23850
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1650 FSL & 660 FWL Sec. 8-T23N-R6W	JAN 2003	Counselors Gallup Dakota County or Parish, State Rio Arriba, New Mexico
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE	OF NOTICE, REPORT, OR OTHER DA	AA
TYPE OF SUBMISSION TYPE OF ACTION		
Notice of Intent Acidize Alter Casing	Deepen Production (Fracture Treat Reclamation	Start/Resume) Water Shut-Off Well Integrity
Subsequent Report Casing Repair Change Plans	New Construction Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete Recomplete	Other
Final Abandonment Notice Convert to Injection	Plug Back Water Dispo	sal
3. Describe Proposed or Completed Operations (clearly state all pertinent deta If the proposal is to deepen directionally or recomplete horizontally, give s Attach the Bond under which the work will be performed or provide the I Following completion of the involved operations if the operation results in Testing has been completed. Final Abandonment Notices shall be filed or	subsurface locations and measured and true vertical Bond No. on file with BLM/BIA. Required sub- a multiple completion or recompletion in a new	el depths of all pertinent markers and zones.

Elm Ridge Resources Inc. intends to plug the well in accordance with regulations. Production equipment will be removed and well will be plugged as specified. Perforate and squeeze will be used unless casing can be recovered over the specified intervals or there is evidence cement is in place behind the casing: Proposed Procedure as follows: Notify BLM office at 505-599-8907 24-hours prior to commencement of plugging operations. Pull all retrievable downhole production equipment. Set a CIBP @ 5100'. Spot 50' plug on top of CIBP. Set a 200' cement plug from 2750' to 2950' across the top of the Mesa Verde inside and outside of 4-1/2 casing. Set a 200' cement plug from 1850' to 2050' across Pictured Cliffs top inside and outside of 4-1/2 casing. Set a 200' cement plug from 1300' to 1500' across top of Ojo Alamo inside and outside of 4-1/2 casing. Set a 270' cement plug from surface to 270' inside and outside of casing. Cut off wellhead. Install dry hole markers. Clear and remediate location.

Certified Peturn Possint # 7001 0220 0002 6707 2047

determined that the site is ready for final inspection.)

	ann receipt # 7001		707 2047			
14. I hereby cert	ify that the foregoing is tru	e and correct				
Name (Printed/Typed)		Title	;			
Trudy Grubelnik		ŀ	Production Technician			
Signature	Medle	land	Date	Date December 27, 2002		
	N. S.	Ţ	HIS SPACE FOR FEI	DERAL OR ST.	ATE USE	
Approved by				Title	Date	
Original Signed: Stephen Mason		1	1/13/03			
certify that the app	oval, if any, are attached. A licant holds legal or equital e the applicant to conduct o	Approval of this no ole title to those ri	otice does not warrant or ghts in the subject lease	Office		
70'-1 10 TT C C C	1004					

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT FARMINGTON FIELD OFFICE

1235 LA PLATA HIGHWAY FARMINGTON, NEW MEXICO 87401

Attachment to notice of

Re: Permanent Abandonment

Intention to Abandon:

Well: 1 Marcus A

CONDITIONS OF APPROVAL

- 1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
- 2. Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 599-8907.
- 3. The following modifications to your plugging program are to be made:
- a) Place the Mesaverde plug from 3472' 3272' inside and outside 4 ½" casing.
- b) Add a Fruitland plug from 1804' 1704'.
- c) Place the Ojo Alamo plug from 1571' 1275'.
- d) Place the Surface plug from 320' to surface inside and outside 4 ½" casing.

You are also required to place cement excesses per 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.