Form 3160-5 *(December 1989)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: September 30, 1990

 Lease Designation and Serial No. SF 079001 A

6. If Indian, Allottee or Tribe Name

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

SUNDRY NOTICES AND REPORTS ON WELLS

ſ	Do not use this form for proposals to drill, deepen or reentry to a different reservoir.
>	Use 'APPLICATION FOR PERMIT" for such proposals

				7. If Unit or CA, Agmt. Design.:
SUBMIT IN TRIPLICATE				Northeast Blanco Unit
1. Type of Well:	oil well	gas well X	other	8. Well Name and No.:
2. Name of Operator:	Devon Energ	N.E.B.U. 419		
3. Address of Operator:	3300 N. Butl	9. API Well No.:		
4. Location of Well: (Footage, Sec., T., R., M., or Survey Description)				30-039-24355
•				10. Field & Pool/Exploratory Area:
				Basin Dakota/Mesaverde
825' FSL, 1750' FWL - Section 3, T30N, R7W				11. County or Parish, State:
				Rio Arriba, New Mexico
12.	CHECK APPROPRIATE	BOX(s) TO INDIC	ATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SUBMISSION				E OF ACTION
	Notice of Intent		Abandonment	Change of Plans
			Recompletion	New Construction
X	Subsequent Report	İ	Plugging Back	Non-Routine Fracturing
		İ	X Casing Repair	Water Shut-Off
	Final Abandonment Notic	e	Altering Casing	Conversion to Injection
]	Other:	

13. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Work commenced on 11/29/2002 to re-cavitate the NEBU 419. The 5 1/2" liner was found parted, and three jts of liner were removed from the well bore. Consulted Jim Lovato with the BLM and the decision was made to side track the well. A CIBP was set @ 3006' in the 7" csg. The 7" csg was pressure tested to 1500 psi. A 5 1/2" 3 degree whipstock assymbly was set and a window cut in the 7" csg with the top @ 2995' and the bottom @ 3003'. The side tracked well bore was drilled with a 6 1/4" bit to a TD of 3258' before getting returns of 75% coal, 20% Shale, and 5% salt / pepper sandstone showing PC top. Original TD was 3233'. Surveys were ran @ 3042' (3 deg), 3103' (7 deg), 3165' (4 deg), 3227' (2.5 deg). The hole was under reamed to 9 1/2", and the well was cavitated and cleaned up. A 4 1/2" liner was run in the well with the hanger @ 2881, and bottom of liner, bit sub and bit @ 3249'. The liner was perforated from 3040' - 3240' with 420 .66 holes w/ 4 spf in 5 intervals. 2 3/8" tbg was landed in the well @ 3226'.

Work was completed on 12/29/2002, and to 14. I hereby certify that the foregoing is true and correct. Signed:	he well was return	Title: RRODUCTION FOREMAN JAN 1 7 2003	THE CHARLES AND THE PARTY OF TH
(This space for Federal or State office use)		Ma and	
Approved byConditions of approval, if any:	Title	Date	