Form 3160-5 (August 1999)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135

SUNDRY NOTICES AND		1 1 3 3 3 3 3	7 1 1		
	REPORTS ON V	/ELLS	5. Lease Serial I SF07870	_	
Do not use this form for proposals to abandoned well. Use form 3160-3 (A	drill or to re-ente	MAR -3	AM Mindian Allot	tee or Tribe Name	
SUBMIT IN TRIPLICATE-Other ins	tanta ita en esta		nton. NM		
Type of Well	ucuons on re	A STATE OF THE STA	7. If Unit or CA/A	greement, Name, and/or No.	
Oil Well X Gas Well Other	(3)	(56/897)			
2. Name of Operator		MAR 2003	8 Well Name ar	(4)	
3a. Address and Telephone No.		(include area code)	9. API Well No.	. # 10	
5802 HIGHWAY 64, FARMINGTON, NM 874		2-8056	30-045-	31068	
4. LOCATION OF WEI L (Footage, Sec., T., R., M., or Survey I	Description)	· ·	10 Field and Poo	I, Or Exploratory Area	
01-2 1300 FNL & 840 FWL - UL " "	T. Comments	2000 00 10 V	BLANCO	MESA VERDE/BASIN DAKOTA	
ok → <del>1300'</del> FNL & <del>840'</del> FWL - UL " " SEC. 13, T31N, R13W		action of the	11. County or Par		
	·			AN COUNTY, NEW MEXICO	
12. CHECK APPROPRIATE BO	OX(ES) TO INDICA			T, OR OTHER DATA	****
TYPE OF SUBMISSION		TYP	E OF ACTION		
Notice of Intent	Acidize	Fract	ure Treat	Recomplete	
	Alter Casing	New	Construction	Temporarily Abandon	
X Subsequent Report	Casing Repai	r Plug	and Abandon	Water Disposal	
	Change Plans	Plug	Back	Water Shut-Off	
Final Abandonment Notice	Convert to Inj	ection Produ	uction (start/resume	Well Integrity	
	Deepen	Recla	mation	X Other Commence Drilling	
				164	
	pertinent details, includin	ed and true vertical depth	is of all pertinent mark	pletion of the involved operations. If the operation	
deepen directionally or recomplete horizontally, give subsurfation be performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a	Required subsequent reproval, a Form 3160-4 shall	be filed once testing has	been completed. Fin	al Abandonment Notices snall be filed only after all )	
deepen directionally or recomplete horizontally, give subsurfative performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW	Required subsequent reprival, a Form 3160-4 shall and the operator has dete	be filed once testing has rmined that the site is rea	been completed. Fin dy for final inspection.	)	
deepen directionally or recomplete horizontally, give subsurfa be performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RIF	Required subsequent reproal, a Form 3160-4 shall and the operator has dete	be filed once testing has mined that the site is rea shoe (thread locke	been completed. Fin dy for final inspection.	oat (thread locked on top & welded on	
deepen directionally or recomplete horizontally, give subsurfative performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW 02/21/03 Spud 12-1/4' surface hole. RIF-bottom), 5 jts 9-5/8", 36# J55 S	Required subsequent reprival, a Form 3160-4 shall and the operator has detended by the world with the subsequent reprivate the subsequent reprivate the subsequent reprivate the subsequent reprivate reprivat	be filed once testing has mined that the site is rea shoe (thread locket Land csg @ 284.10	been completed. Fin idy for final inspection.  d), 1 jt w/insert fl  KB & float @ 2	oat (thread locked on top & welded on 38.35' KB w/landing jt.	
deepen directionally or recomplete horizontally, give subsurfative performed or provide the Bond No. on file with BLMBIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RIH bottom), 5 jts 9-5/8", 36# J55 SCmt csg w/25 bfw, 220 sx (46 b	Required subsequent reprival, a Form 3160-4 shall and the operator has detended by the subsequent reprivate forms of the subsequent reprivate forecreate forms of the subsequent reprivate forms of the subsequent	be filed once testing has mined that the site is real shoe (thread locke Land csg @ 284.10	been completed. Fin idy for final inspection.  d), 1 jt w/insert fl  'KB & float @ 2 phane mixed to 1	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx.	
deepen directionally or recomplete horizontally, give subsurfative performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW 02/21/03 Spud 12-1/4' surface hole. RIF-bottom), 5 jts 9-5/8", 36# J55 S	Required subsequent reprival, a Form 3160-4 shall and the operator has detended by the subsequent reprivate forms of the subsequent reprivate forecreate forms of the subsequent reprivate forms of the subsequent	be filed once testing has mined that the site is real shoe (thread locke Land csg @ 284.10	been completed. Fin idy for final inspection.  d), 1 jt w/insert fl  'KB & float @ 2 phane mixed to 1	oat (thread locked on top & welded on 38.35' KB w/landing jt.	
deepen directionally or recomplete horizontally, give subsurfative performed or provide the Bond No. on file with BLMBIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RIH bottom), 5 jts 9-5/8", 36# J55 SCmt csg w/25 bfw, 220 sx (46 b	Required subsequent reprival, a Form 3160-4 shall and the operator has detended by the subsequent reprivate forms of the subsequent reprivate forecreate forms of the subsequent reprivate forms of the subsequent	be filed once testing has mined that the site is real shoe (thread locke Land csg @ 284.10	been completed. Fin idy for final inspection.  d), 1 jt w/insert fl  'KB & float @ 2 phane mixed to 1	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx.	
deepen directionally or recomplete horizontally, give subsurfative performed or provide the Bond No. on file with BLMBIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RIH bottom), 5 jts 9-5/8", 36# J55 SCmt csg w/25 bfw, 220 sx (46 b	Required subsequent reprival, a Form 3160-4 shall and the operator has detended by the subsequent reprivate forms of the subsequent reprivate forecreate forms of the subsequent reprivate forms of the subsequent	be filed once testing has mined that the site is real shoe (thread locke Land csg @ 284.10	been completed. Fin idy for final inspection.  d), 1 jt w/insert fl  'KB & float @ 2 phane mixed to 1	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx.	
deepen directionally or recomplete horizontally, give subsurfa be performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new inte requirements, including reclamation, have been completed, a  APD/ROW  02/21/03 Spud 12-1/4' surface hole. RII- bottom), 5 jts 9-5/8", 36# J55 S  Cmt csg w/25 bfw, 220 sx (46 t  18 bfw to displace plug. Float in	Required subsequent reproval, a Form 3160-4 shall and the operator has detended by the control of the control o	be filed once testing has mined that the site is real shoe (thread locke Land csg @ 284.10	been completed. Fin idy for final inspection.  d), 1 jt w/insert fl  'KB & float @ 2 phane mixed to 1	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx.	
deepen directionally or recomplete horizontally, give subsurfative performed or provide the Bond No. on file with BLMBIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RIH bottom), 5 jts 9-5/8", 36# J55 SCmt csg w/25 bfw, 220 sx (46 b	Required subsequent reproval, a Form 3160-4 shall and the operator has detended by the control of the control o	be filed once testing has mined that the site is real shoe (thread locke Land csg @ 284.10	been completed. Fin idy for final inspection.  d), 1 jt w/insert fl  'KB & float @ 2 phane mixed to 1	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx.	
deepen directionally or recomplete horizontally, give subsurfs be performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RII-bottom), 5 jts 9-5/8", 36# J55 S Cmt csg w/25 bfw, 220 sx (46 that 18 bfw to displace plug. Float 14. I hereby certify that the foregoing is true and correct	Required subsequent reproval, a Form 3160-4 shall and the operator has detended by the control of the control o	be filed once testing has mined that the site is real shore (thread locket and csg @ 284.10 Cl2 & 1/4# sx cellowed cmt. WOC.	been completed. Fin idy for final inspection.  d), 1 jt w/insert fl  'KB & float @ 2 phane mixed to 1	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx. t to 1100 psi. Held OK.	
deepen directionally or recomplete horizontally, give subsurfs be performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RII-bottom), 5 jts 9-5/8", 36# J55 SCmt csg w/25 bfw, 220 sx (46 to 18 bfw to displace plug. Float in 18 bfw to displace plug. Float in 18 bfw to displace plug. Float in 19 learned (Printed/Typed)  KAY S. ECKSTEIN	Required subsequent reproval, a Form 3160-4 shall and the operator has detended by the second of the	be filed once testing has mined that the site is real shore (thread locket and csg @ 284.10 Cl2 & 1/4# sx cellowed cmt. WOC.	been completed. Fin idy for final inspection. id), 1 jt w/insert fl D' KB & float @ 2 phane mixed to 1 Test BOP. Tes	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx. t to 1100 psi. Held OK.	
deepen directionally or recomplete horizontally, give subsurfs be performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RII-bottom), 5 jts 9-5/8", 36# J55 SCmt csg w/25 bfw, 220 sx (46 to 18 bfw to displace plug. Float in 18 bfw to displace plug. Float in 19 keys to the surface of the s	Required subsequent reproval, a Form 3160-4 shall and the operator has detended by the second of the	shoe (thread locket and csg @ 284.10 Cl2 & 1/4# sx cello ol cmt. WOC.	been completed. Fin idy for final inspection.  Id), 1 jt w/insert flow the wind inspection.  If the wind the wind the wind inspection.  Test BOP. Test BOP. Test BOP. Test BOP. Test BOP.	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx. t to 1100 psi. Held OK.	
deepen directionally or recomplete horizontally, give subsurfs be performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RII-bottom), 5 jts 9-5/8", 36# J55 SCmt csg w/25 bfw, 220 sx (46 to 18 bfw to displace plug. Float in the surface of the s	Required subsequent reproval, a Form 3160-4 shall and the operator has determined the operator has determined the operator has determined to the operator h	shoe (thread locket and csg @ 284.10 Cl2 & 1/4# sx cello ol cmt. WOC.	been completed. Fin idy for final inspection.  d), 1 jt w/insert fl b' KB & float @ 2 phane mixed to 1 Test BOP. Test  FEDURAL FINAL	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx. t to 1100 psi. Held OK.	
deepen directionally or recomplete horizontally, give subsurfs be performed or provide the Bond No. on file with BLM/BIA. results in a multiple completion or recompletion in a new interequirements, including reclamation, have been completed, a APD/ROW  02/21/03 Spud 12-1/4' surface hole. RII-bottom), 5 jts 9-5/8", 36# J55 SCmt csg w/25 bfw, 220 sx (46 to 18 bfw to displace plug. Float in 18 bfw to displace plug. Float in 19 keys to the surface of the s	Required subsequent reproductively a Form 3160-4 shall and the operator has detended by the control of the cont	shoe (thread locket and csg @ 284.10 Cl2 & 1/4# sx cello ol cmt. WOC.	been completed. Fin idy for final inspection.  Id), 1 jt w/insert flow the wind inspection.  If the wind the wind the wind inspection.  Test BOP. Test BOP. Test BOP. Test BOP. Test BOP.	oat (thread locked on top & welded on 38.35' KB w/landing jt. 5.6 ppg and yielding 1.18 cu ft/sx. t to 1100 psi. Held OK.	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and wilfully to make any department or agency of the United States any false, fictitious or fraudulen statements or representations as to any matter within its jurisdiction.