

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells **RECEIVED**

1. Type of Well  
GAS

704 MAR 29 PM 1:43

070 Farmington, NM


- 5. Lease Number  
NMNM-02861
- 6. If Indian, All. or Tribe Name
- 7. Unit Agreement Name

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
990' FNL, 990' FEL, Sec.19, T-27-N, R-9-W, NMPM

- 8. Well Name & Number  
Lodewick #4
- 9. API Well No.  
30-045-06417
- 10. Field and Pool  
Fulcher Kutz Pict Cliffs
- 11. County and State  
San Juan Co, NM



12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

3-3-04 MIRU. TIH w/3 1/2" gauge ring to 2280'. TOOH. TIH w/3 1/2" CIBP, set @ 2274'. ND WH. NU BOP. PT BOP to 2000 psi, OK. TIH, tag CIBP @ 2274'. Load csg w/18 bbl wtr. Circ hole clean. PT csg to 500 psi/15 min, OK. Plug #1: pump 12 sx Class "B" neat cmt inside csg @ 1999-2274' to cover Pictured Cliff perfs & Fruitland top. TOOH. SDON.

3-4-04 TIH, tag TOC @ 2000'. TOOH. TIH, perf 4 sqz holes @ 1600'. Load csg w/4 bbl wtr. Attempt to establish injection. (Gabriel Trujillo BLM, approved change of plans). Plug #2: pump 18 sx Class "B" neat cmt inside csg @ 1245-1658' to cover Kirtland & Ojo Alamo tops. TOOH. TIH, perf 2 sqz holes @ 200'. Circ 6 bbl wtr down csg & out 3 1/2" x 5 1/2" annulus. Establish circ down csg & out bradenhead w/9 bbl wtr. Plug #3: pump 68 sx Class "B" neat cmt down 3 1/2" csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cmt @ surface in 3 1/2" & 5 1/2" csg. Cut off WH. Install dry hole marker w/20 sx Class "B" neat cmt. RD. Rig released. (Gabriel Trujillo BLM on location)

Well plugged and abandoned 3-4-04.

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Oltemanus Title Senior Staff Specialist Date 3/26/04

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_ **FOR RECORD**

CONDITION OF APPROVAL, if any:

AR 30 2004

NMOCDD

FARMINGTON FIELD OFFICE  
Jm