

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

850' FSL, 1450' FEL, Sec. 35, T-28-N, R-9-W, NMPM

5. Lease Number  
NMNM-042096. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name & Number  
Hancock A #39. API Well No.  
30-045-0695410. Field and Pool  
So Blanco Pict Cliffs11. County and State  
San Juan Co, NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment

## Type of Action

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other -☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection

## 13. Describe Proposed or Completed Operations

- 2-27-04 MIRU. ND WH. NU BOP. PT BOP to 2000 psi, OK. TIH, tag up @ 2142'. Pump 12 bbl wtr down tbq & out bradenhead. Plug #1: pump 18 sx Class "B" neat cmt w/2% calcium chloride inside csg @ 1598-2142' to cover Pictured Cliffs perms & Fruitland top. TOOH to 1550'. SD for weekend.
- 3-1-04 TIH, tag TOC @ 1748'. TOOH. Attempt to PT csg, failed. TIH, perf 3 sqz holes @ 1300'. TOOH. TIH w/2 7/8" cmt retainer, set @ 1250'. Attempt to PT csg, failed. Establish injection. Plug #2: pump 78 sx Class "B" neat cmt w/2% calcium chloride outside csg below cmt retainer @ 1076-1300'. Pump 9 sx Class "B" neat cmt w/2% calcium chloride on top of cmt retainer inside csg @ 1046-1250' to cover Kirtland & Ojo Alamo tops. TOOH. WOC. SDON.
- 3-2-04 TIH, tag TOC @ 751'. Circ hole clean. PT csg to 500 psi/15 min, OK. TOOH. TIH, perf 2 sqz holes @ 157'. Circ 4 bbl wtr down csg & out bradenhead. Plug #3: pump 72 sx Class "B" neat cmt w/2% calcium chloride down csg & out bradenhead. WOC. ND BOP. TOC in 2 7/8" csg @ surface. Cut off WH. Cmt top in 2 7/8" x 9 5/8" annulus down 2'. Install dry hole marker & fill annulus w/20 sx Class "B" neat cmt w/2% calcium chloride. RD. Rig released.

Well plugged and abandoned 3-2-04.

## 14. I hereby certify that the foregoing is true and correct.

Signed Nancy Oltmanns Title Senior Staff Specialist Date 3/26/04

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date APR 30 2004

CONDITION OF APPROVAL, if any:

NMOC

FARMINGTON FIELD OFFICE  
SM