Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

	NOTICES AND REPORT S form for proposals to				NMSF079029		
abandoned wel	II. Use form 3160-3 (API	D) for such pro	posals	123	6. If Indian, Allottee or	Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.				PA 2004	If Unit or CA/Agreen	nent, Name and/or No.	
1. Type of Well				-:)	8: Well Name and No.		
Oil Well Gas Well 🛛 Oth		1 3 1 J. 1.					
2. Name of Operator Contact: PATSY CLUG- CONOCOPHILLIPS COMPANY E-Mail: plclugs@				1. J. (2)	9/API Well No. 30-045-32118-00-X1		
3a. Address 3b. Phone No. (include are 5525 HWY Ph: 505.599.3454 FARMINGTON, NM 87401 5525 HWY Fx: 505-599-3442				de)	10. Field and Pool, or E BASIN FRUITLAI		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				×	11. County or Parish, and State		
Sec 21 T31N R8W SWNW 1790FNL 895FWL 36.88526 N Lat, 107.68616 W Lon					SAN JUAN COUNTY, NM		
12. CHECK APPI	ROPRIATE BOX(ES) TO) INDICATE N	IATURE O	F NOTICE, R	EPORT, OR OTHER	DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
- Notice of Intent	☐ Acidize	Deepe	Deepen		tion (Start/Resume)	☐ Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat Reclamation		ation	☐ Well Integrity		
Subsequent Report	☐ Casing Repair	New Construction Recomplete		olete	Other Drilling Operations		
☐ Final Abandonment Notice	Change Plans	Plug a	g and Abandon		rarily Abandon	Drilling Operations	
	Convert to Injection			☐ Water I	☐ Water Disposal		
Description of cement job to fincluding the Ojo Alamo formation Date - 3/28/04; Time started - Hole size - 8-3/4"; Casing - 7 Turbo Centralizers - 2318', 22 Spring Type centralizers - 317 Preflush - 30 bbls FW w/dye i Stage 1: Lead - 415 sx (1083. 0.25#/sx Cellophane flake, 0.1 sx (127 cf - 22.6 bbl slurry) 50 0.25#/sx Cellophane flake, &	ulfill the requirements for ation as per NTL-FRA-90-1530 hrs; Time Complete", 20#, J-55 ST&C casing 75', 2231' 78', 3099', 3012', 2925', 20 n last 10 bbls. 2 cf - 192.9 bbl slurry) Cl: 05 g/sx Antifoam & 0.2% b/50/G/POZ cement w/2% 0.1% antifoam agent.	·1. ed - 1700 hrs (new) Set @ 3 838', 2751', 213 ass G cement vall purpose ant	188'. 3', 83', 39' w/3% Chemi ifoam agent.	ical extender, . Tail - pumpe	d 100		
14. Thereby certify that the foregoing is	strue and correct. Electronic Submission # For CONOCOPH mitted to AFMSS for proces	IILLIPS COMPA	ŇY, sent to t	the Farmingtor	1		
Name (Printed/Typed) PATSY CLUGSTON			Title AUT	HORIZED REI	PRESENTATIVE		
Signature (Electronic	Submission)		Date 03/2 9	9/2004			
	THIS SPACE FO	OR FEDERAL	OR STAT	E OFFICE U	SE		
Approved By ACCEPTED				NNE GARCIA LEUM ENGIN	EER	Date 03/30/2004	
Conditions of approval, if any, are attache certify that the applicant holds legal or eq which would entitle the applicant to cond	e subject lease	Office Farmington					
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a statements or representations as	crime for any per to any matter wit	son knowingly nin its jurisdict	and willfully to raion.	nake to any department or	agency of the United	

Additional data for EC transaction #29021 that would not fit on the form

32. Additional remarks, continued

Volume circulated - 37 bbls; Displaced w/20 bbls FW & 107.3 bbls slight polymerized drilled water.

Average pressure -655 psi; Average rate - 2 bpm; Bumped plug w/1470 psi