Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5.	Lease Serial No.	
	NMSF078423	

6	If Indian	Allottee or Tribe Name	

SUBMIT IN TRIE		7. If Unit or CA/Agreement, Name and/or No.							
Type of Well Oil Well			8. Well Name and No. SAN JUAN 29-7 UNIT 80B						
2. Name of Operator BURLINGTON RESOURCES	br-inc.com		9. API Well No. 30-039-27021-00-X1						
3a. Address 3401 EAST 30TH FARMINGTON, NM 87499	Ph: 505.326 Fx: 505.326.				OINT LOOKOUT				
4. Location of Well (Footage, Sec., T Sec 9 T29N R7W SWNW 154		n)			11. County or Parish, a				
12. CHECK APPE	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF	F NOTICE, RI	EPORT, OR OTHE	R DATA			
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION								
Notice of Intent	☐ Acidize☐ Alter Casing	_	ure Treat	□ Reclam		☐ Water Shut-Off ☐ Well Integrity			
☐ Subsequent Report ☐ Final Abandonment Notice	☐ Casing Repair☐ Change Plans☐ Convert to Injection	□ Plug	Construction and Abandon Back	☐ Recomp ☐ Tempor ☐ Water I	arily Abandon	Other Change to Original A PD			
Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) It is intended to alter the approved surface casing and cement program as follows: Hole size: 12 1/4" Depth interval: 1-120' Casing size: 9 5/8" Weight: 32.3# Grade: H-40 9 5/8" surface casing - cement with 32 sacks Class A, B Portland Type I, II cement (38 cu.ft. of slurry, bring cement to surface through 3/4" line) or equivalent. Wait on cement for 24 hours for pre-set holes or 8 hours for conventionally set holes before pressure testing or drilling out from under surface casing.									
14. Thereby certify that the foregoing is	s true and correct. Electronic Submission For BURLINGTON R mmitted to AFMSS for pro	ESOURCES OF	kG CO LP. sei	nt to the Farmi	n System ngton	C Managaga pilan eri			
Name (Printed/Typed) PEGGY C		Title REG	ULATORY AD	MINISTRATOR					
Signature (Electronic	Submission)		Date 01/1:	3/2003					
	THIS SPACE F	OR FEDERA	L OR STAT	E OFFICE U	SE				
Approved By DENIED		JIM LO	VATO LEUM ENGIN	EER	Date 01/15/2003				
Conditions of approval, if any, are attached certify that the applicant holds legal or eqwhich would entitle the applicant to conditions.	uitable title to those rights in tuct operations thereon.	Office Farmington							
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it statements or representations	a crime for any peas to any matter w	erson knowingly ithin its jurisdict	and willfully to r	nake to any department of	r agency of the United			