Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
OMB No. 1004-0135
Expires: January 31 2004

FORE	M APPKI	ソリピロ
OMB	No. 1004	L-0135
		31, 2004
Lapitos.	Januai y	31, 2004

	V NOTICES AND BED			/	5. Lease Se	rial l	Vo.	
Do not use th	Y NOTICES AND REP	okison w	ELLS Lontor an	, DE0E*	NMSF-07			
abandoned we	ils form for proposals to ell. Use Form 3160-3 (AP	D) for such p	roposals.	RH()HN	6. If Indian	, Allo	ttee or Tribe Name	
	•			F Enterior Sugar Sussain S	N/A			
SUBMIT IN TR	IPLICATE - Other inst	ructions on I	reverse sid	83 JAN 16	17. If Unit of	CA/	Agreement, Name and/or No.	
1. Type of Well			^	70 5	N/A,			
Oil Well Gas Well	Other	· · · · · · · · · · · · · · · · · · ·	U	70 Farmingt	8. Well Wa	me ar	nd No.	
2. Name of Operator					F-RPC 19	#4		
Richardson Operating Company 3a. Address		10. 5.			9. API We	li No.		
	3b. Phone No. (include area code)				30-045-31152			
3100 La Plata Highway Farming		505-564-310	00				l, or Exploratory Area	
4. Location of Well (Footage, Sec., 746' FSL & 665' FEL	T, R., M., or Survey Description	m)			Fruit Coal & W Kutz PC Ext			
Sec 19 T29N R13W					11. County	or Pai	rish, State	
					San Juan,	New	Mexico	
12. CHECK API	PROPRIATE BOX(ES) T	O INDICATE	NATURE C	F NOTICE, RI				
TYPE OF SUBMISSION	•			F ACTION				
-	Acidize	Deepen Deepen		Production (Start/	Resume)		Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Ti	reat 🔲	Reclamation	ĺ	ō	Well Integrity	
Subsequent Report	Casing Repair	☐ New Const	ruction 🔲	Recomplete			Other See below	
_	Change Plans	Plug and A	bandon 🔲	Temporarily Aba	ndon	_		
Final Abandonment Notice	Convert to Injection	Plug Back		Water Disposal				
determined that the site is ready in 1-10-03 Spud 8 3/4" surface hole celloflake; 15.6# slurry. Circ. cen	c. Drill to 130'. Ran 4 its. 7" 2	0# casing; set at	125' KB. Cen	nented with 50 sx	(59 cf) Clas	ss 'B'	w/ 2 % CaCl, 1/4#/sk	
1-11-03 Install and test BOP to 60	•	t surface casing	to 600 psi, 30	min; test good. D)rill 6 1/4" he	ole to	450'. SDFN (Weekend)	
1-13-03 Drill 6 1/4" hole to 1150'.							• • • • • • • • • • • • • • • • • • • •	
1-14-03 Drill 6 1/4" to 1310'; TD. with 2% metasilicate, 1/4# cellofle cmt to surface.	Tally and run 31 joints 4.5" ake; 12.6# slurry and 55 sx (K-55 10,5# casi (65 cf) Class 'H'	ng; set guide s with 1/4#/sk c	shoe at 1305.64' k elloflake;15.6# sl	KB. Cemente lurry . Bump	d wit ed pli	h 75 sx (155 cf) Class 'B' ug to 800 psi. Circ. 7 bbl	
	•		18		· ·			
					<u> </u>			
			AY .	CO02 144	[L.]			
			isi .	Mile Are	42)			
14. I hereby certify that the foregoing	g is true and correct		1-3	· · · · · · · · · · · · · · · · · · ·	<u> </u>			
Name (PrintedlTyped)	g is the and correct	i		the party of	(O)			
Drew Carnes			Title Operation	ns Manager	્રે ∤			
Signature			Date 1-16-03	Mualla La	/			
	THIS SPACE I	Company of the Compan	The state of the s	OFFICE USE				
Approved by (Signature)			Name (Printed/T)			Title	CCEPTED FOR RECOR	
Conditions of approval if any are	attached Annroval of this	ce does not		pou)			Date	
Conditions of approval, if any, are a certify that the applicant holds lega which would entitle the applicant to compare the conditions of	onduct operations thereon.	nts in the subject	lease				JAN 2 3 2003	