


State of New Mexico
Energy, Minerals & Natural Resources

Form C-101
Revised March 17, 1999

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. 1st Street, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division
1220 S. St. Francis Dr.
Santa Fe, NM 87505

Submit to appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies



☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

¹ Operator Name and Address XTO Energy Inc. 2700 Farmington Ave., Bldg. K. Ste 1		² OGRID Number 167067
⁴ Property Code 22821	⁵ Property Name State Gas Com "BE"	³ API Number 30- 045 32286
		⁶ Well No. #4

⁷ Surface Location									
UL or lot no. M	Section 16	Township 30N	Range 13W	Lot. Idn	Feet from the 730'	North/South Line South	Feet from the 745'	East/West line West	County San Juan

⁸ Proposed Bottom Hole Location If Different From Surface									
UL or lot no.	Section	Township	Range	Lot. Idn	Feet from the	North/South Line	Feet from the	East/West line	County
⁹ Proposed Pool 1 Basin Fruitland Coal					¹⁰ Proposed Pool 2				

¹¹ Work Type Code N	¹² Well Type Code G	¹³ Cable/Rotary Rotary	¹⁴ Lease Type Code State	¹⁵ Ground Level Elevation 5,415' Ground Level
¹⁶ Multiple N	¹⁷ Proposed Depth 1,650'	¹⁸ Formation Fruitland Coal	¹⁹ Contractor Stewart Bros.	²⁰ Spud Date Summer 2004

²¹ Proposed Casing and Cement Program					
Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
8-3/4"	7"	20.0#, J-55, STC	200'	75 sx	Surface
6-1/4"	4-1/2"	10.5#, J-55, STC	1,650'	170 sx	Surface

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Surface: 75 sx of Type III cement w/2% CC & 1/4#/sx cello (14.8 ppg, 1.39 cuft). Circ to surface.

Production: 100 sx Type III with 8% gel & 1/4#/sx cello mixed at 11.4 ppg & 3.03 cuft/sx followed by 70 sx Type III cmt w/1% CC & 1/4#/sx cello mixed at 14.5 ppg & 1.41 cuft/sx. Circ to surface.

Remarks: Use 40% excess over volume calculated from op hole logs to determine final cement volume.

BOP diagram is attached.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.		OIL CONSERVATION DIVISION	
Signature: <i>Jeffrey W. Patton</i> 4/8/04		Approved by: <i>[Signature]</i>	
Printed name: Jeffrey W. Patton		Title: DEPUTY OIL & GAS INSPECTOR, DIST. 8	
Title: Drilling Engineer		Approval Date: APR 12 2004 Expiration Date: APR 12 2005	
Date:	Phone:	Conditions of Approval:	
		Attached <input type="checkbox"/>	

DISTRICT I
1825 N. French Dr., Hobbs, N.M. 88240

DISTRICT II
1301 W. Grand Ave., Artesia, N.M. 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, N.M. 87410

DISTRICT IV
1220 South St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102

Revised June 10, 2003

Submit to Appropriate District Office

State Lease - 4 Copies

Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-045-32286		² Pool Code 711029		³ Pool Name Basin Fruitland Coal	
⁴ Property Code 22821		⁵ Property Name STATE GAS COM B E			⁶ Well Number 4
⁷ OGRI No. 167067		⁸ Operator Name XTO ENERGY INC.			⁹ Elevation 5415'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	16	30-N	13-W		730	SOUTH	745	WEST	SAN JUAN

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
¹² Dedicated Acres 320 S12					¹³ Joint or Infill I		¹⁴ Consolidation Code		¹⁵ Order No.

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

<p>16</p>	<p>17 OPERATOR CERTIFICATION</p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.</p> <p><i>Kelly K Small</i> Signature Kelly K Small Printed Name Drilling Assistant Title 4/8/04 Date</p> <p>18 SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>Date of Survey Signature and Seal of Professional Surveyor Certificate Number</p>
-----------	--

BOP SCHEMATIC FOR DRILLING OPERATIONS CLASS 1 (2M) NORMAL PRESSURE

ROTATING HEAD
OR STRIPPING
(DIVERTING)
HEAD

FILL UP LINE

FLOW LINE
TO PIT

BLIND
RAMS

PIPE
RAMS

SCREW ON
DRILLING FLANGE

FILL-UP /
KILL LINE
2" dia min.

** Remove check or ball
from check valve and
press test to same press
as BOP's. **

Fig. 92 (typical)
CASINGHEAD
(SCREW-IN)

CASING COLLAR
(LOOKING UP)

TO
ADJUSTABLE
CHOKE
MANIFOLD
2" dia min.

See Choke Manifold drawing for
specifications

1. Test BOP after installation:

Pressure test BOP to 200-300
psig (low pressure) for 5 min.

Test BOP to Working Press or
to 70% internal yield of surf csg
(10 min).

2. Test operation of (both) rams on every trip.

3. Check and record Accumulator pressure on every tour.

4. Re-pressure test BOP stack after changing out rams.

5. Have kelly cock valve with handle available.

6. Have safety valve and subs to fit all sizes of drill string.

TESTING
PROCEDURE

CHOKE MANIFOLD SCHEMATIC FOR DRILLING OPERATIONS CLASS 1 (2M) NORMAL PRESSURE

1. Stake all lines from choke manifold to pit.
2. Pressure test choke manifold after installation.
3. Pressure test manifold at the same time with the BOP Stack. Test manifold to the same test pressures.

TESTING PROCEDURE

