UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED

Sundry Notices	
Dana2, 1.001000	and Reports on Wells 70% 100 12 PM N: 07
	5. Lease Number
	NMSF078439
Type of Well	070 Farmington, New If Indian, All. or
GAS	Tribe Name
	CE 37 19 10 50
	Unit Agreement Name
Name of Operator	
BURLINGTON	APR 2004
RESCURCES OIL & GAS COM	PANY
,	8. Well Name & Number
Address & Phone No. of Operator	Johnston Federal 2
PO Box 4289, Farmington, NM 874	
No.	30-045-32082-00-X1
Location of Well, Footage, Sec.,	
1840'FNL, 790'FEL, Sec. 35, T31N,	R9W, NMPM Basin Fruitland Co
	San Juan Co, NM
	TE NATURE OF NOTICE, REPORT, OTHER DATA
Type of Submission	Type of Action
Notice of Intent	Abandonment Change of Plans
X Subsequent Report	Recompletion New Construction Plugging Back Non-Routine Fracturing
X Subsequent Report	Casing Repair Water Shut off
Final Abandonment	Altering Casing Conversion to Injection
	Other - Drilling Operations
	d Operations
13.Describe Proposed or Completed 14.	d Operations
14.	
14. 3/5/04 Drill to intermediate T	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 td w/305 sxs Type III cmt w/0.25 pps celloflake, 1% oss (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1%
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 cd w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cflake,0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 35
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 cd w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% oflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 35 CP & csg to 1500 psi/30 mins, OK. Drilling ahead.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD @	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 cd w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% oflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 35 CP & csg to 1500 psi/30 mins, OK. Drilling ahead. 3 2877'. Circ hole clean. TOOH. TIH w/underreamer.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 4" hole to TD @ Underream hole from 6 4" to 9 2	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 cd w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% oflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 35 CP & csg to 1500 psi/30 mins, OK. Drilling ahead.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD @ Underream hole from 6 ¼" to 9 ½ TD after underreaming.	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 cd w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% oflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 35 CP & csg to 1500 psi/30 mins, OK. Drilling ahead. 3 2877'. Circ hole clean. TOOH. TIH w/underreamer. 2" from 2603' to 2877'. TOOH w/underreamer. Circ well
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD @ Underream hole from 6 ¼" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB.	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 td w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% oflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 35 OP & csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. 2" from 2603' to 2877'. TOOH w/underreamer. Circ well .5# K-55 LT&C liner. Top of liner @ 2550', bottom of 1000 cm.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD @ Underream hole from 6 ¼" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB. 3/8/04 Run 90 jts 2 3/8" 4.7#,	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 td w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 350P & csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. from 2603' to 2877'. TOOH w/underreamer. Circ well. 5# K-55 LT&C liner. Top of liner @ 2550', bottom of J-55 EUE tbg landed @ 2847'KB.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD @ Underream hole from 6 ¼" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB.	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 td w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 350P & csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. from 2603' to 2877'. TOOH w/underreamer. Circ well. 5# K-55 LT&C liner. Top of liner @ 2550', bottom of J-55 EUE tbg landed @ 2847'KB.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD @ Underream hole from 6 ¼" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB. 3/8/04 Run 90 jts 2 3/8" 4.7#,	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 td w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 350P & csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. from 2603' to 2877'. TOOH w/underreamer. Circ well. 5# K-55 LT&C liner. Top of liner @ 2550', bottom of J-55 EUE tbg landed @ 2847'KB.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD @ Underream hole from 6 ¼" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB. 3/8/04 Run 90 jts 2 3/8" 4.7#,	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 td w/305 sxs Type III cmt w/0.25 pps celloflake, 1% css (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 350P & csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. from 2603' to 2877'. TOOH w/underreamer. Circ well. 5# K-55 LT&C liner. Top of liner @ 2550', bottom of J-55 EUE tbg landed @ 2847'KB.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD @ Underream hole from 6 ¼" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB. 3/8/04 Run 90 jts 2 3/8" 4.7#, 3/9/04 ND BOP. NU WH. RD Rig r	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 td w/305 sxs Type III cmt w/0.25 pps celloflake, 1% cleans (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 350P & csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. cm from 2603' to 2877'. TOOH w/underreamer. Circ well. 5# K-55 LT&C liner. Top of liner @ 2550', bottom of I J-55 EUE tbg landed @ 2847'KB. released.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid lo calcium chloride, .25 pps cello bbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD @ Underream hole from 6 ¼" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB. 3/8/04 Run 90 jts 2 3/8" 4.7#,	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 td w/305 sxs Type III cmt w/0.25 pps celloflake, 1% cleans (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 350P & csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. cm from 2603' to 2877'. TOOH w/underreamer. Circ well. 5# K-55 LT&C liner. Top of liner @ 2550', bottom of I J-55 EUE tbg landed @ 2847'KB. released.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid localcium chloride, .25 pps cellobbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD 6 Underream hole from 6 ½" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB. 3/8/04 Run 90 jts 2 3/8" 4.7#, 3/9/04 ND BOP. NU WH. RD Rig r	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 td w/305 sxs Type III cmt w/0.25 pps celloflake, 1% cleans (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cflake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 350P & csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. cm from 2603' to 2877'. TOOH w/underreamer. Circ well. 5# K-55 LT&C liner. Top of liner @ 2550', bottom of I J-55 EUE tbg landed @ 2847'KB. released.
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid localcium chloride, .25 pps cellobbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD 6 Underream hole from 6 ¼" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB. 3/8/04 Run 90 jts 2 3/8" 4.7#, 3/9/04 ND BOP. NU WH. RD Rig r	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 and w/305 sxs Type III cmt w/0.25 pps celloflake, 1% cleans (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cellake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 350 ps csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. cm from 2603' to 2877'. TOOH w/underreamer. Circ well. 5# K-55 LT&C liner. Top of liner @ 2550', bottom of Included the content of the cleased. Title Regulatory Specialist Company of the content of
3/5/04 Drill to intermediate T J-55, ST&C csg set @ 2588'. Cmt calcium chloride, 0.2% fluid localcium chloride, .25 pps cellobbls cmt to surface. WOC. PT BC 3/6/04 Drill 6 ¼" hole to TD 6 Underream hole from 6 ½" to 9 ½ TD after underreaming. 3/7/04 TIH w/8 jts of 5 ½" 15. @ 2877'KB. 3/8/04 Run 90 jts 2 3/8" 4.7#, 3/9/04 ND BOP. NU WH. RD Rig r	TD @ 2590'. Circ hole clean. TOOH. TIH w/60 jts 7" 20 and w/305 sxs Type III cmt w/0.25 pps celloflake, 1% cleans (650 cu. ft.). Tail w/90 sxs Type III cmt. w/1% cellake, 0.4% SMS, 0.2% fluid loss (124 cu. ft.) Circ 350 ps csg to 1500 psi/30 mins, OK. Drilling ahead. 2877'. Circ hole clean. TOOH. TIH w/underreamer. cm from 2603' to 2877'. TOOH w/underreamer. Circ well. 5# K-55 LT&C liner. Top of liner @ 2550', bottom of Included the content of the cleased. Title Regulatory Specialist Company of the content of