

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-045-31316
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator ConocoPhillips Company 217817		6. State Oil & Gas Lease No. E-501-13
3. Address of Operator 5525 Highway 64, NBU 3004, Farmington, NM 87401		7. Lease Name or Unit Agreement Name: San Juan 32-7 Unit 31329
4. Well Location Unit Letter P : 690 feet from the South line and 1315 feet from the East line Section 32 Township 32N Range 7W NMPM County San Juan		8. Well No. SJ 32-7 Unit #234A
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6672' GL		9. Pool name or Wildcat Basin Fruitland Coal 71629

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐

OTHER: ☐ OTHER: 7" casing report ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

3/24/03 RIH w/8-3/4" bit & tagged cement @ 179'. D/O cement & drilled formation to 3238'. Circ. hole. RIH w/7", 203, J-55 casing and set @ 3233'. RU Schlumberger to cement. Pumped a preflush 15 bbls FW & 10 bbls FW w/dye ahead of Lead - 410 sx (1070. cf - 190.6 bbl slurry) G cement w/3% D079, 0.25#/sx C029, 0.05 GPS D047 & 0.2% D046 Flocele. Tail - 105 sx (133.4 cf - 23.8 bbls) 50/50/G/POZ Cement w/2% D020, 2% S001, 5#/sx D024, 1/4#/sx D029 0.1% D046. Released wiper plug & displaced w/20 bbls FW & 109.2 bbls slightly polymerized drill water. Bumped plug w/2000# @ 1245 hrs 3/27/03. Circulated 11 sx (5 bbls) good cement to surface. RD Schlumberger. ND BOP, Set slips and cut off casing. Installed trash cap. RD & released rig 2000 hrs 3/27/03. Will show casing PT on next report.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Patsy Clugston TITLE SHEAR Administrative Assistant DATE 4/1/03

Type or print name Patsy Clugston Telephone No. 505-599-3454

(This space for State use)

APPROVED BY Charlie Plon TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 63 DATE APR - 3 2003

Conditions of approval, if any: