UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No. NMSF079004	
6. If Indian, Allottee or Tribe Name	

abandoned we	n. Ose form 3 100-3 (AF)	o) ioi sacii p	opusais.		·		
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No. NMNM78424B		
Type of Well ☐ Oil Well ☐ Gas Well ☑ Oth		8. Well Name and No. SAN JUAN 32-8 223A					
Oil Well Gas Well Other: COAL BED METHANE 2. Name of Operator Contact: PATSY CLUG CONOCOPHILLIPS COMPANY E-Mail: plclugs					9. API Well No. 30-045-32152-00-X1		
5525 HWY		3b. Phone No. (include area code) Ph: 505.599.3454 Fx: 505-599-3442		ide)	10. Field and Pool, or Exploratory BASIN FRUITLAND COAL		
4. Location of Well (Footage, Sec., 7	., R., M., or Survey Description	L			11. County or Parish, a	and State	
Sec 10 T31N R8W SWNW 17 36.91383 N Lat, 107.66817 W			SAN JUAN COUNTY, NM				
12. CHECK APPI	ROPRIATE BOX(ES) TO) INDICATE	NATURE O	F NOTICE, RE	PORT, OR OTHER	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
☐ Notice of Intent	☐ Acidize	□ Deep	en	Production	on (Start/Resume)	☐ Water Shut-Off	
-	Alter Casing	Frac	ure Treat	□ Reclamat	tion	☐ Well Integrity	
Subsequent Report	☐ Casing Repair	□ New	Construction	Recompl	ete	Other	
☐ Final Abandonment Notice	☐ Change Plans	□ Plug	and Abandon	☐ Tempora	rily Abandon	Drilling Operations	
_	Convert to Injection	□ Plug	Back	□ Water Di	sposal		
5/6/04 RIH w/8-3/4" bit & tagg Circ hole. RIH w/7", 20# J-55 preflush of 30 bbls FW w/dye Class G cement w/3% Chemic purpose antifoam. Tail - pum Bentonite, 2% CaCl2, 5#/sx G plug and displaced w/20 bbls psi @ 2355 hrs 5/8/04. Did no 5/9/04. TOC @ 200' (inside the circ hole)	ST&C casing and set @ in last 10 bbls. Pumped l cal extender, 0.25#/sx Ce ped 100 sx (127 cf - 22.6 bilsonite, 0.25#/sx Celloph FW & 112.1 bbls slightly l of circulated cement to sur	3309'. RU So Lead - 435 sx llophane flake bbl slurry) 50, ane flake & 0 poly-merized rface. Ran te	chlumberger t (1135 cf - 20 c, 0.05 gps an 50/G/POZ ce .1% antifoam drill water. Bu mperature su	o cement. Pum 2.2 bbl slurry) utifoam & 0.2% a ment w/2% . Released wipe umped plug w/1 rvey @ 1200 hr	all	75 26 27 200A	
14. I hereby certify that the foregoing is	true and correct. Electronic Submission # For CONOCOPH	30546 verified	by the BLM W	/ell Information S	System	211111532	
	nitted to AFMSS for proces	ssing by ADR	NNE GARCIA	on 05/20/2004 (0	•	•	
Name (Printed/Typed) PATSY CI	LUGSTON		Title AUTH	ORIZED REPF	RESENTATIVE		
Signature (Electronic S	Submission)	į	Date 05/11	/2004			
	THIS SPACE FO	R FEDERA	L OR STAT	E OFFICE US	E		
Approved By ACCEPT	ED			INE GARCIA LEUM ENGINEI	ER	Date 05/20/2004	
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduction	uitable title to those rights in the uct operations thereon.	e subject lease	Office Farmi				
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a statements or representations as	crime for any pe	rson knowingly thin its jurisdicti	and willfully to mai	ke to any department or	agency of the United	