

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other		5. Lease Serial No. NMNM012710
2. Name of Operator BURLINGTON RESOURCES O&G CO LP		6. If Indian, Allottee or Tribe Name
3a. Address PO BOX 4289 FARMINGTON, NM 87499		7. If Unit or CA/Agreement, Name and/or No.
3b. Phone No. (include area code) Ph: 505.599.4068 Fx: 505.599.4062		8. Well Name and No. SJ 30-6 64
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 11 T30N R7W NENE 0990FNL 1090FEL 36.83156 N Lat, 107.53421 W Lon		9. API Well No. 30-039-07896-00-S1
		10. Field and Pool, or Exploratory BLANCO MESAVERDE
		11. County or Parish, and State RIO ARRIBA COUNTY, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

4-14-04 MIRU. TOO H w/99 3/4" rods, 157 5/8" rods & pump. ND WH. NU BOP. PT BOP, OK. SDON.
4-15-04 TOO H w/199 jts 2 3/8" tbg. TIH w/4 1/2" cmt retainer, set @ 5519'. Load tbg w/wtr. PT tbg to 1000 psi, OK. Circ csg w/85 bbl wtr. PT csg to 500 psi/30 min, OK. (Gabriel Trujillo, BLM on location). SDON.
4-16-04 Circ hole clean. Plug #1: pump 13 sx Class "B" neat cmt inside csg @ 5361-5519' to cover Mesaverde top & cover 7" csg shoe. TOO H. TIH, perf 3 sqz holes @ 4407'. Load hole w/wtr. Attempt to establish injection, failed. (Verbal approval to change plans from Gabriel Trujillo, BLM). TIH to 4450'. Plug #2: pump 30 sx Class "B" neat cmt w/4055-4450' to cover Chacra top. TOO H. WOC. SD for weekend.
4-19-04 TIH, tag TOC @ 4407'. Circ hole clean w/35 bbl wtr. PT csg to 600 psi/15 min, OK. SDON.
4-20-04 Plug #3: pump 12 sx Class "B" neat cmt inside csg @ 4249-4407' to cover Chacra. TOO H. TIH, perf 3 sqz holes @ 3719'. (Verbal approval from Gabriel Trujillo, BLM to change plans). Plug #4:



14. I hereby certify that the foregoing is true and correct. Electronic Submission #30764 verified by the BLM Well Information System For BURLINGTON RESOURCES O&G CO LP, sent to the Farmington Committed to AFMSS for processing by STEVE MASON on 05/19/2004 (04SXM1035S)	
Name (Printed/Typed) NANCY OLTMANNS	Title SENIOR STAFF SPECIALIST
Signature (Electronic Submission)	Date 05/14/2004

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By ACCEPTED Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Title STEPHEN MASON PETROLEUM ENGINEER	Date 05/19/2004
	Office Farmington	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

NMOCD

Additional data for EC transaction #30764 that would not fit on the form

32. Additional remarks, continued

pump 33 sx Class "B" neat cmt inside csg @ 3373-3783' to cover Pictured Cliffs top. TOOH. WOC. TIH, tag TOC @ 3534'. PT csg to 500 psi/15 min, OK. TOOH. TIH, perf 3 sqz holes @ 3370'. Attempt to establish injection. (Verbal approval from Gabriel Trujillo, BLM to change plans). TIH to 3437'. Establish circ. Plug #5: pump 24 sx Class "B" neat cmt w/2% calcium chloride inside csg @ 3120-3437' to cover Fruitland top. TOOH. WOC. SDON.
4-22-04 TIH, tag TOC @ 3219'. Circ hole clean. PT csg to 500 psi/15 min, OK. Plug #6: pump 28 sx Class "B" neat cmt inside csg @ 2471-2840' to cover Kirtland & Ojo Alamo tops. TOOH. TIH, perf 3 sqz holes @ 1305'. Attempt to establish injection. Plug #7: pump 16 sx Class "B" neat cmt @ 1150-1360' to cover Nacimiento top. TOOH. TIH, perf 3 sqz holes @ 226'. Establish circ down csg & out bradenhead. Plug #8: pump 180 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Cmt down 12' in 4 1/2" csg & down 8' in annulus. Pump 30 sx Class "B" Neat cmt to fill csg & install dry hole marker. (Gabriel Trujillo, BLM on location). RD. Rig released.

Well plugged and abandoned 4-22-04.