UNITED STATES DEPARTMENT OF THE INTERIOR		
BUREAU OF LAND MANAGEMENT	DEOFNED	
Sundry Notices and Reports or	Wells	
	2014 APR 27 PM 3531	Lease Number
1. Type of Well	6	NMSF-079002 NMNM 03403 If Indian, All. or
GAS	070 FARMINGTON, NM	Tribe Name
	7.	Unit Agreement Name
2. Name of Operator	16.25.26.27.20	
BURLINGTON		
OIL & GAS COMPANY	MAY 2004	Well Name & Number
3. Address & Phone No. of Operator	6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	San Juan 30-6 Unit #4518
PO Box 4289, Farmington, NM 87499 (505) 326-9	100 S. DIV. 9. A)	API Well No.
A Torontion of Well Ecotogo Cos M D M		30-039- 27656 Field and Pool
4. Location of Well, Footage, Sec., T, R, M 1560'FSL, 1815'FEL, Sec.7, T30N, R6W, NMPM	Car Sour Barry	Basin Fruitland Coal
	11.	County and State
<i>;</i>		JRio Arriba Co, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NO	TTOE REPORT OTHER	> 2 T 2
	of Action	
X Notice of IntentAbandonment	_X Change of Pla	
Recompletion Subsequent Report Plugging Back	New Construction Non-Routine Frac	
Casing Repair	Water Shut off	C carang
Final Abandonment Altering Casin	ng Conversion to :	I njection
Other		
13. Describe Proposed or Completed Operations		
The BOP configuration has been revised for the sub	eject well according	to the following and
attached diagram: BOP and tests:		
DOT and tests.		
Surface to intermediate TD - 11" 2000 psi (minimum) double gate I surface casing, test BOPE to 600 psi for 30 min.	BOP stack (Reference Figure	⇒ #1). Prior to drilling out
, ,		
Intermediate TD to Total Depth - 7 1/6" 2000 psi (minimum) compleout intermediate casing, test BOPE and casing to 1500 psi for 30 n		Figure #2). Prior to drilling
From surface to 7" TD – a choke manifold will be installed in accommodation the cavitation completion rig drills the production hole, the capture (#4).	dance with Onshore Order Nompletion rig configuration w	ill be used (Reference Figure #3).
Pipe rams will be actuated at least once each day and blind rams a upper kelly cock valve with handle and drill string safety valves to the st	ctuated once each trip to tes it each drill string will be ma	st proper functioning. An irrained and available on the

(This space for Federal or State Office use)

APPROVED BY

CONDITION OF APPROVAL if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agen by of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

I hereby certify that the foregoing is true and correct.

rig floor.

Title Regulatory Specialist Date

04/013/04

BURLINGTON RESOURCES Cavitation Rig

Cavitation Rig
BOP Configuration
2,000 psi Minimum System

