UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

Lease Serial No. NMSF079382

7	If Indian	Allotton on Tribo Nome	

				- I					
SUBMIT IN TRI	7. If Unit or CA/Agreement, Name and/or No. NMNM78420B								
1. Type of Well ☐ Oil Well ☐ Gas Well ☐ Oth	ner		8. Well Name and No. SAN JUAN 30-6 UNIT 413S						
Name of Operator BURLINGTON RESOURCES	O&G CO LP	S t@br-inc.com		9. API Well No. 30-039-27681-00-X1					
3a. Address PO BOX 4289 FARMINGTON, NM 87499		(include area cod).4068 .4062	de)	10. Field and Pool, or Exploratory BASIN FRUITLAND COAL					
4. Location of Well (Footage, Sec., T	., R., M., or Survey Descriptio			11. County or Parish, and State					
Sec 23 T30N R7W NENW 58	0FNL 1595FWL			RIO ARRIBA COUNTY, NM					
12. CHECK APPI	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF	NOTICE, RE	EPORT, OR OTHER	R DATA			
TYPE OF SUBMISSION			TYPE OF ACTION						
NI-4: of Indone	☐ Acidize ☐ Deepen		en	Production (Start/Resum		☐ Water Shut-Off			
□ Notice of Intent			ture Treat Reclam		ation	☐ Well Integrity			
Subsequent Report			Construction	☐ Recomp	lete	Other Drilling Operations			
☐ Final Abandonment Notice	Change Plans				arily Abandon Drilling Operation				
J	Convert to Injection Plug			☐ Water D					
Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 7" CASING REPORT & COMPLETION DETAILS 5/6/04 MIRU Bearcat #4. Tighten WH & NU BOP. PT Blind rams and casing to 600# - OK. RIH w/8-3/4" bit & D/O cement & then formation to 2804'. Circ. hole. NU to run casing. RIH w/7", 20#, J-55 ST&C casing and set @# 2874'. RU BJ to cement. Pumped a preflush of 10 bbls water, 10 bbls chemical wash, & 10 bbls water ahead of Lead - 325 sx (692 cf - 124 bbls)Premium Lite w/0.4% FL-52, 5.3#/sx LCM-1, 0.25% Celloflake, 0.4% Sodium Metasiliate, 8% Bentonite & 3% CaCl2, Tailed w/90 sx (124 cf - 22 bbls) Type 3 w/1% CaCl2, 0.25% Cello-flake, 0.2% FL-52. Dropped plug and bumped w/800#. Circ. 29 bbls cement to surface. ND cement head & NU B section. RD & released rig on drilling @ 1900 hrs 5/9/04. 5/9/04 Installed B Section & NU to Air. PT BOP - Ok. RIH w/6-1/4" bit & PT pipe rams and casing									
, , ,	Electronic Submission For BURLINGTON R mitted to AFMSS for proce	ESOURCES OF	G CO LP, sen	nt to the Farmin	gton				
Name (Printed/Typed) PATSY C	LUGSTON		Title SR. F	REGULATORY	SPECIALIST				
Signature (Electronic S	Submission)		Date 06/11	/2004					
	THIS SPACE F	OR FEDERA	L OR STAT	E OFFICE US	SE				
Approved By ACCEPT	ED			INE GARCIA LEUM ENGINE	=====================================	Date 06/14/2004			
Conditions of approval, if any, are attache certify that the applicant holds legal or eq which would entitle the applicant to cond	uitable title to those rights in thuct operations thereon.	Office Farmi							
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it statements or representations a	a crime for any posts to any matter w	erson knowingly thin its jurisdicti	and willfully to m	ake to any department or	agency of the United			

Additional data for EC transaction #31839 that would not fit on the form

32. Additional remarks, continued

to 1500# for 30 minutes @ 0630 5/10/04. Good test. Tagged TOC @ 2830'. D/O cement then formation to 3220' (TD). TD reached 5/10/04. Circ. hole. RIH w/underreamer & underreamed 6-1/4" hole to 9-1/2" from 2880' - 3220'. C/O to TD. RIH w/5-1/2", 15.5#, J-55 Perforated liner & set @ 3220' w/TOL @ 2834' (7" shoe @ 2874') 40' overlap. Perforations from 2920' - 3130'; Total 338 (.5") holes. RIH w/2-3/8", 4.7# J-55 EUE tubing and set @ 3163'. ND BOP, NU WH. RD & released rig @ 2359 hrs 5/13/04.