Form 3160-5 (November 1994)

INITED STATES

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals.

0111122 0111120
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

4-20-603-3	21

8: Well Name and No.

Central Bisti Unit #10

If Indian,	Allottee	or Tri	be Nam	e	
20011	1633	$\hat{}$	רותו	^	0

7. If Unit or CA/Agreement, Name and/or N RECEIVED

CentraPBiSti WARMINGTON NM

FORM APPROVED

OMB No. 1004-0135 Expires July 31, 1996

į	į,					li i	V 10		úψ						460	Y.		ć	Ų.						4.5		Ñ.			Ĵ.					愸	
	÷	ı	J	Ы	M	11	3	IN	ŀ	Ш	ч	Щ	ر)	4	ľŁ	~	- 11	<u> </u>	th	e.	r. II	15	tri	uc	ŧк	O I	15	0	n	re	V	ers	е	SI	đ€)

Type of Well X Oil Well Gas Well Name of Operator Elm Ridge Resources, Inc. Address PO Box 189, Farmington, NM 87499 505-632-3476

Location of Well (Footage, Sec., T., R., M., or Survey Description)

9. API Well No. 30-045-05543

10. Field and Pool, or Exploratory Area

Bisti[®]Lower Gallup 11. County or Parish, State

San Juan County, New Mexico

1980 FSL & 1880 FWL Sec. 4 - T25N- R12W

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
☐ Notice of Intent	Acidize	Deepen	Production (Start/Resume)	☐ Water Shut-Off
■ Subsequent Report	Alter Casing Casing Repair	☐ Fracture Treat ☐ New Construction	Reclamation Recomplete	☐ Well Integrity ☐ Other
Final Abandonment Notice	Change Plans Convert to Injection	■ Plug and Abandon ■ Plug Back	☐ Temporarily Abandon ☐ Water Disposal	
12 Describe Browned or Completed County	Coloredo por all president des			

The above referenced well has been Pluged and Abandoned by Elm Ridge Resources, Inc. as follows: Plug 1) Set retainer @ 4669'. Pumped 60 sks. Of Class B 15.6 cement under retainer. Pumped 24 sks. Left on top of TOC 4484'. Plug 2) Shot 2 holes @ 1879' . Set cement retainer @ 1821'. Pumped 46 sks. under retainer. Left 2 sks. on top. Plug 3) Shot 2 holes @ 1140'. Set Retainer @ 1077'. Pumped 46 sks. of cement under and 2 sks. on top. Plug 4) Shot 2 holes @ 832'. Set retainer @ 785'. Pumped 46 sks. of cement under retainer. Left 58 sks. on top of retainer. Plug 5) Shot 2 holes @ 107' pumped 50 sks. of cement in annulas to surface. All cement Class 'B' 15.6 #/gal. 1.18 cu.ft./sk. All cement witnessee by Bobby Vigil.

14. I hereby certify that the	ne foregoing is true and correct			
Name (Printed/Typed)		Title		
	Amy Mackey		Production Assistant	
Signature	lacker	Date	June 30, 2004	
	THIS S	PACE FOR FEDERAL OR STATE U	SE	
Approved by		Title	Date	
certify that the applicant holds	are attached. Approval of this notice legal or equitable title to those rights and to conduct operations thereon.			

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse,

ACCEPTED FOR RECORD JUL 0 6 2004 FARMINGTON FIELD OFFICE

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones.

Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days Following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)