Form 3160-5 (August 1999)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

5. Lease Serial No. NMSF079491

abandoned well. Use form 3160-3 (APD) for such proposals.			6. If Indian, Allottee	6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRI	7. If Unit or CA/Agre NMNM78409A	7. If Unit or CA/Agreement, Name and/or No. NMNM78409A			
1. Type of Well ☐ Oil Well ☐ Gas Well ☐ Oth	8. Well Name and No. SAN JUAN 27-5	8. Well Name and No. SAN JUAN 27-5 UNIT 102N			
2. Name of Operator Contact: TAMMY JONES BURLINGTON RESOURCES O&G CO LP E-Mail: twimsatt@br-inc.com			9. API Well No. 30-039-27683-	9. API Well No. 30-039-27683-00-X1	
3a. Address PO BOX 4289 FARMINGTON, NM 87499	Phone No. (include area code 505.599.4068 505.599.4062	BASIN DAKOT	10. Field and Pool, or Exploratory BASIN DAKOTA BLANCO MESAVERDE		
4. Location of Well (Footage, Sec., 7 Sec 12 T27N R5W SWSE 53:	•		11. County or Parish, RIO ARRIBA C		
12. CHECK APPI	ROPRIATE BOX(ES) TO INI	DICATE NATURE OF	NOTICE, REPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
Nation of Intent	☐ Acidize	Deepen	Production (Start/Resume)	☐ Water Shut-Off	
□ Notice of Intent	Alter Casing	Fracture Treat	Reclamation	☐ Well Integrity	
Subsequent Report	Casing Repair	☐ New Construction	Recomplete	Other	
Final Abandonment Notice	Change Plans	Plug and Abandon	☐ Temporarily Abandon	Drilling Operations	
<b>.</b>	Convert to Injection	Plug Back	☐ Water Disposal		
condition hole. RIH w/7", 20# condition hole. RIH w/7", 20# cement. Pumped 1st Stage @ Cello-flake, .5#/sx LCM-1, .4% w/1% CaCl2, .25%#/sx Celloto surface. Bumped plug & o 0.25#/sx Cello-flake, .5#/sx LC	i. NU BOP. PT BOP, rams, & 6 d TOC @ 120'. D/O cement & d TOS ST&C casing and set @ 0 31 sx (686 cf - 122 bbl slurry % FL-52, .4% SMS. Tailed w/9 flake, .2% FL-52. Dropped plu pened stage collar. 2nd Stage CM-1, 4% FL-52, .4% SMS. D VOC. ND BOP, installed B Sec	then formation to 392/ 3922' w/stage tool @ 3 ) Premium Lite w/3% C 0 sx (124 cf - 22 bbl slu ug and displaced w/FW e - pumped 371 sx Prem isplaced both w/FW. Ci	ium Lite w/3% Cacher c. 30 bbls cement	2004	
	s true and correct. Electronic Submission #3271 For BURLINGTON RESOU nitted to AFMSS for processing	RCES O&G CO LP, sent by ADRIENNE BRUMLEY	to the Farmington		
Name (17 meas 19 peas) 1 A 101 C	20001014	71110 511.111			
Signature (Electronic	Submission)	Date 07/06/2	2004		
	THIS SPACE FOR F	EDERAL OR STATE	OFFICE USE		
Approved By ACCEPT	ED		IE GARCIA EUM ENGINEER	Date 07/13/2004	
Conditions of approval, if any, are attache certify that the applicant holds legal or eq which would entitle the applicant to cond	uitable title to those rights in the subj		gton		
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent				or agency of the United	

## Additional data for EC transaction #32710 that would not fit on the form

## 32. Additional remarks, continued

4-1/2" - 6/26/04 RIH w/6-1/4" bit & D/O stage tool 3319', & shoe. Then ahead to 8166' (TD). TD reached 6/29/04. Circ. hole. RIH w/ 4-1/2" 11.6# & 10.5#, J-55 LT &C & ST&C casing and set @ 8163. RU BJ to cement. Pumped 1 preflush of 10 bbls chemical wash & 2 bbls water ahead of 5 bbls scavenger cement w/278 sx (550.27 cf - 98 bbls) Premium Lite HS w/.25#/ss Cello-flake, .3% CD-32, 6.25#/sx LCM -1, 1% FL-52. Dropped plug and displaced w/130 bbls water. Bumped plug w/1016 psi. Plug down @ 1945 hrs 6/29/04. RD & released rig @ 0145 hrs 6/30/04. The Completion rig w/PT casing before completion begins. Will also show PT results and TOC on next report.