Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

Lease Serial No. NMSF079419

6.	If Indian.	Allottee o	or Tribe	Name

abandoned wel	6. If Indian, Allottee or Tribe Name					
SUBMIT IN TRII	7. If Unit or CA/Agreement, Name and/or No. NMNM78412A					
1. Type of Well		T.V		8. Well Name and No. 3 SJ 28-6 94		
Oil Well Gas Well Oth	The second secon		AUG 2004	ં)		
2. Name of Operator BURLINGTON RESOURCES		TAMMY JONES E-Mail: twimsatt@br-inc.com	ENTERN MARKET	9 API Well No. 30-039-07267-0		
3a. Address PO BOX 4289 FARMINGTON, NM 87499	Fx: 505.599.4062	code).	A.9. Field and Pool, or Exploratory BASIN DAKOTA BLANCO MESAVERDE			
4. Location of Well (Footage, Sec., 7 Sec 36 T28N R6W NWNE 09 36.62233 N Lat, 107.41461 W	90FNL 1650FEL		£ 27.12 18 ST 525	11. County or Parish, a		
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE	OF NOTICE, RE	PORT, OR OTHER	R DATA	
TYPE OF SUBMISSION		TYPE OF ACTION				
Notice of Intent	☐ Acidize	Deepen	☐ Producti	on (Start/Resume)	Water Shut-Off	
□ Notice of Intent	Alter Casing	Fracture Treat	☐ Reclama	tion	☐ Well Integrity	
Subsequent Report	Casing Repair	☐ New Construction	_		Other	
☐ Final Abandonment Notice	☐ Change Plans	Plug and Abando	_	arily Abandon	Warkovar Operations	
D .	Convert to Injection	Plug Back	☐ Water D			
determined that the site is ready for f DETAILS OF PROCEDURE L BEFOREHAND. DHC THE M' 5/4/04 MIRU Aztec #449. ND Shale @ 4305' - 5057' @ 1 sp Frac. Tried to PT - circulated the Moved down casing to isolate 5/7/04 Cemented w/206 sx (C TOC on 7" (outside casing) @ 5082'. Spotted 750 gal 15% he w/cement - established circ the	USED TO ADD ADDITION V/DK INTERVALS OF TH WH & NU BOP, TOOH w of .34" holes = 25 holes; A thru interm casing valve. leak. Tested good to ab tirc. 15 bbls to surface). To 2 3295'. D/O cement from HCL over LS perfs w/acid	E SUBJECT WELL. WE /tubing. Ran & set RPB .cidized LS perfs w/750 c RIH w/FBP & set @ 60'; ove top perf. Set packer 'OOH w/packer @ 4050' 4530' - 5060' (22' short of (opened up LS perfs squ	© 5082'. PT-OK.  3 15% HCL. RU PT to surf - OK.  4050'.  Logged well, sh of RBP; C/O to RI  Jeeze had covere	C'D PER DHC ORD Perf'd Lewis to  nowed BP @	IENT ER 558 AZ.	
14. Thereby certify that the foregoing is  Cot  Name (Printed/Typed) TAMMY J	Electronic Submission # For BURLINGTON RE mmitted to AFMSS for prod		sent to the Farmin	gton SXM1830SE)		
Signature (Electronic S	Submission)	Date 06	/17/2004			
	THIS SPACE FO	OR FEDERAL OR STA	ATE OFFICE US	SE.		
Approved By ACCEPT	ED		PHEN MASON ROLEUM ENGINE	ER	Date 08/03/200	
Conditions of approval, if any, are attache certify that the applicant holds legal or eq which would entitle the applicant to conductive the conductive conductive the applicant to conduct the applicant the ap	uitable title to those rights in th		mington			
Title 18 II S.C. Section 1001 and Title 43	U.S.C. Section 1212 make it	crime for any person knowing	also and willfully to m	oka to any denortment o	a against of the United	

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## Additional data for EC transaction #31910 that would not fit on the form

## 32. Additional remarks, continued

75% foam pad w/20,000# 20/40 AZ sand. Displaced w/41 bbls fluid & 78,600 scf N2.

Flowed back for 1-1/2 days, C/O fill to 5082' w/air & mist. COOH w/RBP (difficult to COOH). TIH w/4-1/2" mill. Cement had circulated through perfs below RBP into casing below. TOOH w/mill. TIH w/6-1/4" mill and milled cement & dresssed casing from 5080' - 5350'. D/O cement to 6860' to TOL; Blew clean. TIH w/4-1/2" mill - milled junk (scale) to 7790'. Spotted acid over DK perfs & TOOH w/mill. TIH w/RBP @ 5630'. Spotted 15% HCL over PT lookout interval. Set packer @ 5515'. Spotted CH perfs w/acid. Unset packer & RBP & COOH. TIH w/tubing & C/O to PBTD @ 7818'. Broach tubing to SN -OK. Land tubing @ 7761'. ND BOP, NU WH & PT tubing to 500 psi. Pumped off exp. check. RD & released rig @ 2130 hrs 6/1/04.