Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

۷.	NMSF079049A	
	Marine Alleston on Tribo	Vama

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use form 3160-3 (APD) for such proposals

abandoned well. Use form 3160-3 (APD) for such proj					6. If Indian, Allottee or T	ribe Name		
SUBMIT IN TRIF	erse side.		7. If Unit or CA/Agreement, Name and/or No. NMNM78412C					
1. Type of Well		- non-rej	8. Well Name and No. SAN JUAN 28-6 UNIT 150N					
Oil Well Gas Well Oth	MMY JONI							
2. Name of Operator BURLINGTON RESOURCES	=S t@br-inc.com		9. API Well No. 30-039-27611-00-X1					
3a. Address PO BOX 4289 FARMINGTON, NM 87499	(include area code 9.4068 .4062	e)	10. Field and Pool, or Exploratory BASIN DAKOTA BLANCO MESAVERDE					
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)			11. County or Parish, an	d State			
Sec 35 T28N R6W SENE 148	5FNL 655FEL				RIO ARRIBA COL	JNTY, NM		
12. CHECK APPR	ROPRIATE BOX(ES) TO IN	IDICATE	NATURE OF	NOTICE, RI	EPORT, OR OTHER	DATA		
TYPE OF SUBMISSION	i		ТҮРЕ О	F ACTION				
☐ Notice of Intent	Acidize	□ Deep	en	Product	ion (Start/Resume)	☐ Water Shut-Off		
- :	☐ Alter Casing	□ Frace	ture Treat	Reclamation		☐ Well Integrity		
Subsequent Report	☐ Casing Repair	□ New	Construction	□ Recomp	olete	Other Drilling Operations		
Final Abandonment Notice	☐ Change Plans	☐ Change Plans ☐ Plug and Abandon ☐ Temporarily Abandon		arily Abandon	Drilling Operations			
	Convert to Injection	□ Plug	Back	■ Water Disposal				
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 7" & 4-1/2" CASING REPORT 8/1/04 MIRU Bearcat #5. NU BOP, PT blind rams & 9-5/8" casing to 600 psi for 30 minutes. Good test. RIH w/8-3/4" bit tagged cement @ 95'. Drilled cement & shoe, then formation to 3600'. Circ hole. RIH w/7", 20#, J-55 ST&C casing (98 jts) and set @ 3593' w/stage tool @ 2814'. 8/5/04 RU BJ to cement. Pumped 1st stage preflush - 10 bbls gel & 2 bbls water. Lead - 53 sx (112.3 cf - 20 bbls slurry)Premimum Lite w/3% CaCl2, 0.25#/sx Cello-flake. 5#/sx LCM-1, 0.4% FL-52, 0.4% SMS. Tailed w/90 sx (124 cf - 22 bbl slurry) Type III w/1% CaCl2, 0.25#/sx celloflake, 0.2% FL-52, Displaced w/FW. Bumped plug and opened stage tool, circ. 23 bbls cement. 2nd Stage - 10 bbls FW, 10 bbls mud flush & 10 bbls FW. Pumped 317 sx (676.6 cf - 120.5 bbl slurry) Premium Lite FM, 3% CaCl2, 0.25#/sx Celloflake, 5#/s/x LCM-1, 0.4% FL-52, 0.4% SMS. Displaced w/FW, bumped plug and closed stage tool. Circ. 15 bbls cement to surface. WOC. NU BOP - PT-OK. WOC. 8/6/04 PT blind rams,								
14. Thereby certify that the foregoing is	Electronic Submission #345	03 verified	by the BLM We	II Information	Svstem			
For BURLINGTON RESOURCES OBG CO LP, sent to the Farmington Committed to AFMSS for processing by ADRIENNE BRUMLEY on 08/16/2004 (04AXB3157SE)								
Name (Printed/Typed) PATSY CI	LUGSTON		Title SR. RE	EGULATORY	' SPECIALIST			
Signature (Electronic S	Submission)	į	Date 08/12/2	2004				
	THIS SPACE FOR	FEDERA	L OR STATE	OFFICE U	SE			
Approved By ACCEPT	ED		ADRIENN _{Title} PETROLE	IE BRUMLE' EUM ENGINI		Date 08/16/2004		
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduction.	uitable title to those rights in the suluct operations thereon.	Office Farmington						
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a crit statements or representations as to a	me for any pe any matter w	erson knowingly ar ithin its jurisdiction	nd willfully to m n.	ake to any department or a	gency of the United		

Additional data for EC transaction #34503 that would not fit on the form

32. Additional remarks, continued

casing & manifold to 1500 psi - 30 minutes. Good test.

8/6/04 RIH w/6-1/4" bit & tagged cement. D/O cement & then formation to 7790' (TD). TD reached 8/8/04. Circ. hole. RIH w/182 fts 4-1/2", 10.5#. J-55 casing and set @ 7787' w/PBTD @ 7786'. RU BJ to cement. Pumped 9 sx (28 cf - 5 bbl slurry) Scavenger cement. Tailed w/274 sx (550 cf - 98 bbl slurry) Premium Lite HS FM w/.25#/sx Cello-flake, 0.3% CD-32, 6.25#/sx LCM-1 & 1% FL-52. Displaced w/FW, 25# sugar in first 10 bbls. Bumped plug . RD & released rig @ 0600 hrs 8/9/04. Will show casing PT & TOC on next report. The completion rig will conduct the PT before completion operations begin.