

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
 Sundry Notices and Reports on Wells


2004 AUG 27 AM 11:04

1. **Type of Well**
 WIW

2. **Name of Operator**
 Central Resources, Inc. c/o NMOCD Aztec District Office
 PIAYIA

3. **Address & Phone No. of Operator**
 1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178

4. **Location of Well, Footage, Sec., T, R, M**
 660' FNL and 1980' FEL, Section 29, T-31-N, R-16-W,



5. **Base Number**
 BIA #14-20-603-734

6. **If Indian, All. or**

Tribe Name
 Navajo

7. **Unit Agreement Name**
 Horseshoe Gallup Unit

8. **Well Name & Number**
 HSGU #26

9. **API Well No.**
 30-045-10425

10. **Field and Pool**
 Horseshoe Gallup Unit

11. **County & State**
 San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement: 04-521-0700028; Purchase Document: 04-199-000549.

7/22/04 MOL and spot rig.

7/23/04 RU rig. Relief line to steel pit. ND wellhead. Note: while pulling tubing head slips, one slip fell down hole. Release packer. NU BOP, test. TOH and LD 19 joints 2-3/8" tubing. Packer hung up. Backed off packer at safety joint. LD remaining tubing, total 42 joints. Tally and PU 40 joints A+ workstring and round-trip 4-1/2" casing scraper to 1267'. TOH with tubing and scraper. Shut in well.

7/26/04 TIH with tubing and 4-1/2" DHS cement retainer to 1248'. Sting out of retainer. Load casing and circulate well clean with 20 bbls of water. Pressure test casing to 500# for 5 minutes, held OK. Sting into retainer and pump waste fluid below retainer. Displace to CR with water. Plug #1 with CR at 1248', spot 19 sxs (25 cf) cement inside casing above CR up to 973' to isolate the Gallup interval. TOH and LD tubing. Perforate squeeze holes at 150'. Establish circulation out bradenhead with 4 bbl of water. Pump additional 6 bbls of water. Wait 15 minutes. Pump additional 1 bbl to circulate BH annulus clean. Plug #2 with 50 sxs (66 cf) cement pump down the 4-1/2" casing from 150' to surface, circulate good cement out bradenhead. ND BOP. Dig out and cut off wellhead. Found cement at surface in both the casing and annulus. Mix 10 sxs cement to install the P&A marker. RD and MOL.

H. Villanueva, NMOCD; W. Ashley, Navajo Minerals; and L. Lee, Navajo EPA were on location.

SIGNATURE

William F. Clark
 William F. Clark

Contractor

July 27, 2004

(This space for Federal or State Office use)

ACCEPTED FOR RECORD

APPROVED BY _____ Title _____

Date
 AUG 30 2004

CONDITION OF APPROVAL, if any:

NMOCD

FARMINGTON FIELD OFFICE
 BY *Sm*