

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

2004 AUG 27 PM 5:11 06

1. Type of Well

NW Oil Well

RECEIVED

070 FARMINGTON NM

Lease Number

BIA #14-20-603-2022

If Indian, All. or**Tribe Name**

Navajo

7. Unit Agreement Name

Horseshoe Gallup Unit

2. Name of Operator

Central Resources, Inc. C/O NMOCD

3. Address & Phone No. of Operator

1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178

4. Location of Well, Footage, Sec., T, R, M

2250' FSL and 2630' FWL, Section 14, T31N, R17W,

8. Well Name & Number

HSGU #74

9. API Well No.

30-045-10755

10. Field and Pool

Horseshoe Gallup Unit

11. County & State

San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**Type of Submission**☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment**Type of Action**☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other -☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement: 04-521-0700028; Purchase Document: 04-199-000549.

7/6/04 MOL and RU. Relief line to steel pit. ND wellhead. Release packer. NU BOP, test. TOH and LD 41 joints 2-3/8" tubing and packer. PU 40 joints A+ workstring and round-trip 4-1/2" casing scraper to 1271'.

7/7/04 No pressure. TIH with tubing and set 4-1/2" DHS cement retainer at 1253'. Sting out of retainer. Sting into retainer and inject fluid from pit. Repair cementing pump. Continue injecting waste fluid from pit. Sting out of retainer. Establish circulation and circulate well clean with 20 bbls of water. Pressure test casing to 500# for 5 minutes, held OK. Shut in well. SDFD.

7/8/04 No pressure. Plug #1 with CR at 1253', spot 25 sxs cement Type III (33 cf) inside casing above CR up to 891' to isolate the Gallup interval. TOH and LD tubing. Perforate squeeze holes at 121'. Establish circulation out bradenhead with 13 bbls of water. Plug #2 with 40 sxs Type III cement (53 cf) pump down 4-1/2" casing from 121' to surface, circulate good cement out bradenhead. ND BOP. Dig out and cut off wellhead. Found cement at surface in casing and in annulus. Mix 10 sxs cement to fill casing and install P&A marker.

H. Villanueva, NMOCD; L. Lee, Navajo EPA; Jim Walker, EPA; and W. Ashley, Navajo Minerals were on location.

SIGNATURE

William F. Clark
William F. Clark

Contractor

Date July 31, 2004

(This space for Federal or State Office use)

APPROVED BY

Title

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

Date

AUG 30 2004

NMOCD

FARMINGTON FIELD OFFICE
BY *Sm*