1625 N. French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210
District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy Minerals and Natural Resources

Oil Conservation Division

1220 South St. Francis Dr.

Santa Fe, NM 87505

Oil Conservation Division

Form C-144

June 1, 2004

For thilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe

Santa Fe, NM 87505

Form C-144

your are burying in place) onsite offsite If offsite, name of facility_ remediation start date and end date. (4) Groundwater encountered: No Attach soil sample results and a diagram of sample locations and excavations Additional Comments:	es If yes, show depth below ground surface_	•
your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No Y Attach soil sample results and a diagram of sample locations and excavations	es If yes, show depth below ground surface_	•
your are burying in place) onsite \(\square\) offsite \(\square\) If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No \(\square\) Y	es If yes, show depth below ground surface_	•
your are burying in place) onsite offsite If offsite, name of facility_		•
		al description of remedial action taken including
VC 41 * *	relationship to other equipment and tanks. (2) Inc	
-	Ranking Score (Total Points)	20 POINTS
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet 1000 feet or more	(10 points) (0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.) Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)◀
	No	(0 points)◀
Wallhard restaction area. (Loss than 200 fact from a minute dayti-	Yes	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	50 feet or more, but less than 100 feet 100 feet or more	(10 points) 《 (0 points) 《
Pit Volumebbl	Less than 50 feet	(20 points)
Liner type: Synthetic Thicknessmil Clay		
Lined Unlined	Double-walled, with leak detection? Yes If not, explain why not.	
Type: Drilling ☐ Production ☐ Disposal ☐ Workover ☐ Emergency ☐	Volume: 45 bbl Type of fluid: H2O Construction material: STEEL	
Pit	Below-grade tank	
	00-039-25403 U/L or Qtr/Qtr E NAD: 1927 ☐ 1983 ☐ Surface Owner	Sec 33 T 27N R 7W r Federal ⊠ State □ Private □ Indian □
Operator: PURE RESOURCES Telephone: 432 498-8600 Address: 500 WEST ILLINOIS, MIDLAND, TEXAS 79701	e-mail address: RLECHWAR@PURERE	SOURCES.COM
	\$60 mg	
	k covered by a "general plan"? Yes 🔯 N r below-grade tank 🔯 Closure of a pit or below-	Vo. □ prade tank □
Is pit or below-grade tank Type of action: Registration of a pit or	z covered by a Treneral night@7 V ec/(X) N	T_ (15-3)

Printed Name/Title RON LECHWAR HES COORDINATOR Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval:

Printed Name/Title

Signature

Date: __