## 5. Lease UNITED STATES NMSF-079035-A DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT 6. If Indian, Allottee or Tribe Name SUNDRY NOTICES AND REPORTS ON WELLS 7. Unit Agreement Name (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals) 8. Well Name and No. 1. Oil Well [] Gas Well [] Other [] **GAS WELL** BREECH "A" 136-F 2. Name of Operator: 9. API Well No. 30-039-26621-00C1 **Caulkins Oil Company** 3. Address of Operator: 10. Field and Pool, Exploratory Area (505) 334-4323 1409 W. Aztec Blvd. Ste B7, Aztec, NM 87410 DAKOTA, TOCITO 11. Country or Parish, State 4. Location of Well (Footage, Sec., Twp., Rge.) 1879' F/S 1769' F/E SEC. 10-26N-6W Rio Arriba Co., New Mexico 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION [ ] Notice of Intent [ ] Abandonment [ ] Change of Plans [X] Recompletion [ ] New Construction [X] Subsequent Report [ ] Non-Routine Fracturing [ ] Plugging Back [ ] Casing Repair [ ] Water Shut-Off [ ] Altering Casing [ ] Conversion to Injection [ ] Final Abandonment Notice 1 Other [ ] Dispose Water 17. Describe Proposed or Completed Operations: Rigged up. 7-26-04 T. O. H. with 114 stands and single. Run cast iron bridge plug set 6890'. Perforated Tocito zone with 4 shots per foot, 6712' to 6706' and 6703' to 6697 7-27-04 Frac'd Tocito zone with 21,150# 20/40 sand and 7,025 m/sfc N2 foam. 7-28-04 Flowed back well through 1/2" choke for 5 hours. Killed well. T. I. H. with tubing and bit. Cleaned out to cast iron bridge plug set at 6880' with air foam unit. ACCEPTED FOR RECORD Flowing well back through tubing to clean up. AUG 2 4 2004 FARMINGTON FIELD OFFICE (continued on page 2) NOTE: The format is issued in lieu of U.S. BLM Form 3160-5 18. I HEREBY CERTIFY THE FOREGOING IS TRUE AND CORRECT SIGNED: Robert I Veras TITLE: Superintendent DATE: August 3, 2004 APPROVED BY: TITLE: DATE: CONDITIONS OF APPROVAL, IF ANY

Caulkins Oil Company BLM Sundry Notice Breech "A" 136-F August 3, 2004 Page 2

7-29-04

Tested well through 3/4" choke.

Drilled out cast iron bridge plug set at 6880'.

Cleaned out to TD with air foam unit.

T.O.H. with bit.

7-30-04

T. I. H. with production tubing.

Landed tubing on doughnut at 7432'.

Rigged down and moved.

Now flowing to clean up.

Well will be turned to sales upon approval of NMOCD C-107-A for downhole commingle.