

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

2004 SEP 8 PM 1 42

1. Type of Well
WIW

2. Name of Operator
Central Resources, Inc. c/o NMOCD Aztec District Office

3. Address & Phone No. of Operator
Vulcan
1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178

4. Location of Well, Footage, Sec., T, R, M
1980' FNL and 417' FEL, Section 29, T-31-N, R-16-W,

RECEIVED
070 FARMINGTON, NM
5. Lease Number
BIA #14-20-603-734
6. If Indian, All. or
Tribe Name
Navajo
7. Unit Agreement Name
Horseshoe Gallup Unit
8. Well Name & Number
HSGU #25
9. API Well No.
30-045-10393
10. Field and Pool
Horseshoe Gallup Unit
11. County & St
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement Number: 04-521-0700028, Purchase Document: 04-199-000549.

7/30/04 MOL and RU. Relief line to steel pit. ND wellhead. NU BOP, test. LD 43 joints 2-3/8 EUE tubing and packer. PU 40 joints A+ workstring to round-trip 5-1/2" casing scraper to 1255'. TIH with workstring and set 5-1/2" DHS cement retainer at 1255'. Sting out of CR. Load casing with 31 bbls of water. Pressure test casing to 500#, held OK. Sting into retainer and pump fluid below retainer, displace to CR. Sting out of retainer. Shut in well.

8/2/04 Open well. No pressure. Plug #1 with CR at 1255', spot 29 sxs Type III cement (38 cf) inside casing above CR up to 976' to isolate the Gallup interval. TOH and LD tubing. Perforate 2 squeeze holes at 148'. Establish circulation out bradenhead with 15 bbls of water; circulate BH annulus clean. Plug #2 with 44 sxs Type III cement (58 cf) pump down 5-1/2" casing from 148' to surface, circulate good cement out bradenhead. ND BOP. Dig out and cut off wellhead. Found cement at 5' in casing and at the surface in the annulus. Mix 10 sxs cement to install P&A marker.

H. Villanueva, NMOCD; L. Lee, Navajo EPA; W. Ashley, Navajo Minerals; and G. Shay, Navajo Minerals were on location.

SIGNATURE

William F. Clark

Contractor

August 3, 2004

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY

Title

CONDITION OF APPROVAL, if any:

SEP 14 2004

Date
FARMINGTON FIELD OFFICE
BY
NMOCD