

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. <b>30-045-05394</b>
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. <b>E-6597</b>
Lease Name or Unit Agreement Name <b>Central Bisti Unit</b>
7. Well Number <b>#44</b>
9. OGRID Number
10. Pool name or Wildcat <b>Bisti Lower Gallup</b>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <b>6245 GLE</b>
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/>
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Elm Ridge Resources, Inc. plans to Plug and Abandon the above referenced well as follows: Plug 1) Set retainer @ 4700'. Pump 65 sks of cement. Leave 2 sks. on top of retainer. Plug 2) Top of Mesa Verde. Shoot 2 holes @ 2950'. Set retainer @ 2940'. Pump 25 sks. of cement under retainer and leave 20 sks. on top of retainer. 45 sks total 100' inside and out. Plug 3) P.C. Shoot 2 holes @ 1150'. Set retainer @ 1140'. Pump 25 sks under retainer and leave 20 sks on top. Plug 4) Ojo Alamo and surface shoe. Shoot 2 holes @ 225'. Set retainer @ 220'. Pump 40 sks. of cement. Circulate to surface. Leave 2 sks. on top of retainer. Plug 5) Set a 50' plug @ surface. Cut off wellhead, place marker, clear, and reclaim location.

Plug 1 - to 4545'  
Plug 2 - Top @ 1930' (Cliff House top - 1980')  
Plug - Chacha Top 1550'-1450' Set retainer 1400'  
Plug 3 PC/FC Top @ 960' *AK*

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE *Amey Mackey* TITLE **Production Assistant** DATE **9-03-2004**

Type or print name  
For State Use Only

E-mail address: **amackey@elmridge.net** Telephone No. **505-632-3476**

**DEPUTY OIL & GAS INSPECTOR, DIST. 87** ext. 201

APPROVED BY: *Charles H. [Signature]* TITLE \_\_\_\_\_ DATE **SEP - 9 2004**

Conditions of Approval (if any):