District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 South First, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 copy to appropriate District Office and 1 copy to the Santa Fe Office

(Revised 3/9/94)

PIT REMEDIATION AND CLOSURE REPORT 30 045- 22314

Operator: Burlington Resources Telephone: 505-326-9841 Address: 3401 East 30th St., Farmington, NM 87402 Facility Or: DAVIS Well No: 6A Pit No: 1 Well Name Location: Unit or Qtr/Qtr Sec B Sec 12 T 031N R 012W County San Juan Pit Type: tank (Separator, Dehydrator, Tank, Vent, Other) Land Type: → BLM (BLM, State, Fee, Other) Pit Location: Pit Dimension length 12 width 12 depth 3 Reference: wellhead Other Footage from reference: 100 Direction from reference (azimuth): 110 degrees Depth To Ground Water: (Vertical distance from contaminants to seasonal Less than 50 feet (20 points) high water elevation of 50 feet to 99 feet (10 points) ground water.) Greater than 100 feet (0 points) 0 Wellhead Protection Area: (Less than 200 feet from a private domestic water source, or; less than Yes (20 points) 1000 feet from all other water No (0 points) 0sources.) OIL COM. DIV. DIM. 3 Distance to Surface Water: (Horizontal distance to perennial Less than 200 feet (20 points) 200 feet to 1000 feet lakes, ponds, rivers, streams, creeks, (10 points) Greater than 1000 feet irrigation canals and ditches.) (0 points) 0 RANKING SCORE (TOTAL POINTS): 0

Davis CA

Date Remediation Started	d: 3/16/2002 Date completed:			
Remediation Method:	Excavation Approx. cubic yards:			
(Check all appropriate sections.)	Landfarmed Insitu Bioremediation			
•	Other			
Remediation Location: (i.e. landfarmed onsite, name and location of offsite facility)	Onsite Offsite			
is detailed below. The	Remedial Action: The lab data from the initial assessment of the pit pit is NOT located inside the OCD defined Vulnerable Area. Based K ANALYSIS, it is proposed to close the pit by backfilling with			
Ground Water Encountered: No (yes or no) Depth:				
Final Pit: Closure Sampling: (if multiple samples, attach sample results and diagram of sample locations and depths)	Sample location center of pit Sample depth 3 Sample Date 3/16/2002 Sample time 1:30:00 PM			
	Sample Results: Benzene(ppm) <5			
	Total BTEX(ppm) 290			
Field Headspace(ppm) 1241				
	TPH <u>1397</u>			
Ground Water Sample: N	No (If yes, attach sample results)			
I hereby certify that the ir belief. Date: 2/24/63	nformation above is true and complete to the best of my knowledge and Signature			
Title: Environmental S	,			

RISK ANALYSIS FOR EARTHEN PIT CLOSURE

Burlington Resources requests closure of the earthen pit at this location using a limited risk analysis based upon the following conditions:

- 1. The pit is <u>not</u> located inside the NMOCD defined Vulnerable Areas.
- 2. Groundwater is estimated to be at a depth greater than 100 feet.
- 3. The pit is <u>not</u> located within the Wellhead Protection Area within 200 feet of a private domestic water source or within 1000 feet of all other water sources.
- 4. The pit is located greater than 1000 feet to surface water.
- 5. The soils from below the pit bottom were analyzed and the only parameter above NMOCD closure guidelines was total BTEX, which exceeded 50 ppm. The benzene and Total Petroleum Hydrocarbons (TPH) levels were within the NMOCD closure guidelines.

Burlington Resources believes that the earthen pit poses minimal threat to groundwater, human health and the environment.

Client:

Burlington Resources

Project:

Pit Closure

Sample ID:

Davis 6A 4-73 1161101-1

Lab ID:

0302W01051

Matrix:

Soil

Condition:

Cool/Intact

Date Reported: 04/12/02

Date Sampled: 03/16/02

Date Received: 03/18/02

Date Extracted: N/A

Date Analyzed: 04/02/02

	Analytical		
Parameter	Result	PQL	Units
BTEX - METHOD 8021B			
Benzene	<5	5	mg/Kg
Toluene	32	5	mg/Kg
Ethylbenzene	11	5	mg/Kg
Kylenes (total)	239	15	mg/Kg
Total BTEX	290	30	mg/Kg
GRO/DRO - METHOD 8015M			
Gasoline Range Organics(C6-C10)	1,180	50	mg/Kg
Diesel Range Organics (C10 - C22)	217	50	mg/Kg
Total Petroleum Hydrocarbons (C6-C22)	1,397	100	mg/Kg

Reference: Method 8021b, Volatile Organic Compounds, Test Methods for Evaluating

Solid Waste, Physical/Chemical Methods, United States Environmental

Protection Agency, SW-846, Volume IB.

Reviewed By: