outside

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 South First, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM

87505

State of New Mexico **Energy Minerals and Natural Resources**

Submit 1 copy to appropriate District Office and 1 copy to the Santa Fe Office

(Revised 3/9/94)

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

PIT REMEDIATION AND CLOSURE REPORT 30-045-23873

Operator: Burlington Resources Telephone: 505-326-9841 Address: 3401 East 30th St., Farmington, NM 87402 Facility Or: **DAVIS** Well No: 7E Pit No: 3 Well Name Location: Unit or Qtr/Qtr Sec L Sec 11 T 031N R 012W County San Juan Pit Type: tank (Separator, Dehydrator, Tank, Vent, Other) Land Type: BLM (BLM, State, Fee, Other) Pit Location: Pit Dimension length 12 width 12 depth 3 Reference: wellhead Other Footage from reference: 80 Direction from reference (azimuth): 350 degrees Depth To Ground Water: (Vertical distance from contaminants to seasonal Less than 50 feet (20 points) 50 feet to 99 feet high water elevation of (10 points) ground water.) Greater than 100 feet (0 points)Wellhead Protection Area: (Less than 200 feet from a private domestic water source, or; less than Yes (20 points) 1000 feet from all other water OIL CON. DIV. No (0 points) 0 sources.) Distance to Surface Water: (Horizontal distance to perennial Less than 200 feet (20 points) lakes, ponds, rivers, streams, creeks, 200 feet to 1000 feet (10 points) Greater than 1000 feet irrigation canals and ditches.) (0 points) 0 RANKING SCORE (TOTAL POINTS): 0

Davis 7E (P. 43)

Date Remediation Started	d: 3/12/2002 Date completed:			
Remediation Method:	Excavation Approx. cubic yards:			
(Check all appropriate sections.)	Landfarmed Insitu Bioremediation			
,	Other			
Remediation Location: (i.e. landfarmed onsite, name and location of offsite facility)	Onsite Offsite			
is detailed below. The	Remedial Action: The lab data from the initial assessment of the pit pit is NOT located inside the OCD defined Vulnerable Area. Based K ANALYSIS, it is proposed to close the pit by backfilling with			
Ground Water Encounter	red: No (yes or no) Depth:			
Final Pit: Closure Sampling: (if multiple samples, attach sample results and diagram of sample locations and depths)	Sample location <u>center of pit</u> Sample depth <u>2</u> Sample Date <u>3/12/2002</u> Sample time <u>5:00:00 PM</u>			
	Sample Results:			
	Benzene(ppm) ≤ 5			
Total BTEX(ppm) 168				
Field Headspace(ppm) 433				
	TPH <u>1410</u>			
Ground Water Sample: N	No (If yes, attach sample results)			
l baliaf	nformation above is true and complete to the best of my knowledge and Signature Masely			
Title: Environmental Specialist Printed Name: Ed Hasely				

RISK ANALYSIS FOR EARTHEN PIT CLOSURE

Burlington Resources requests closure of the earthen pit at this location using a limited risk analysis based upon the following conditions:

- 1. The pit is <u>not</u> located inside the NMOCD defined Vulnerable Areas.
- 2. Groundwater is estimated to be at a depth greater than 100 feet.
- 3. The pit is <u>not</u> located within the Wellhead Protection Area within 200 feet of a private domestic water source or within 1000 feet of all other water sources.
- 4. The pit is located greater than 1000 feet to surface water.
- 5. The soils from below the pit bottom were analyzed and the only parameter above NMOCD closure guidelines was total BTEX, which exceeded 50 ppm. The benzene and Total Petroleum Hydrocarbons (TPH) levels were within the NMOCD closure guidelines.

Burlington Resources believes that the earthen pit poses minimal threat to groundwater, human health and the environment.

Client:

Burlington Resources

Project:

Pit Closure

Sample ID:

DAVIS 7E 1163201-3

Lab ID:

0302W00968

Matrix:

Soil

Condition: Cool/Intact

Date Reported: 03/26/02

Date Sampled: 03/12/02

Date Received: 03/14/02

Date Extracted: N/A

	Analytical	PQL	Units
Parameter	Result		
BTEX - METHOD 8021B			
Benzene	<5	5	mg/Kg
Toluene	27	5	mg/Kg
Ethylbenzene	10	5	mg/Kg
Xylenes (total)	131	15	mg/Kg
Total BTEX	168	30	mg/Kg
GRO/DRO - METHOD 8015M			
Gasoline Range Organics(C6-C10)	1,297	50	mg/Kg
Diesel Range Organics (C10 - C22)	113	50	mg/Kg
Total Petroleum Hydrocarbons (C6-C22)	1,410	100	mg/Kg

Reference: Method 8021b, Volatile Organic Compounds, Test Methods for Evaluating

Solid Waste, Physical/Chemical Methods, United States Environmental

Protection Agency, SW-846, Volume IB.

Reviewed By:

William Linns

Analyst