Form 3160- 5 (August 1999)

## DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004- 0135

Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

NO-G-0103-1465

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (ARD) for such proposals [ ]

6. If Indian, Allottee, or Tribe Name

SUBMIT IN TRIPL	7. If Unit or CA. Agreement Designation			
1. Type of Well Oil Well X Gas Well	Other	8. Well Name and No.		
2. Name of Operator Coleman Oil & Gas, Inc 3a. Address P.O. Drawer 3337, Farming	Meg Com #1  9. API Well No.  30-045-30999  10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T.,		Basin Fruitland Coal 11. County or Parish, State San Juan NM		
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent  Subsequent Report	Altering Casing Fracture Treat Reclamation  Casing Repair New Construction Recomplete  Change Plans Plug and abandon Temporarity	Other Abandon		
Final Abandonment Notice	Convert to Injection Plug back Water Dispo			

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths or pertinent markers and sands. Attach the Bond under which the work will performed or provide the Bond No. on file with the BLM/ BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamantion, have been completed, and the operator has

SPUD WELL JANUARY 18, 2003 @ 9:15 AM. DRILLED 8 3/4" HOLE TO 140 FT. GL. RAN 3 JTS OF 7" 20# J-55 ST&C NEW CASING. RAN A TOTAL FOOTAGE OF 132.80 FT. AND LANDED @ 133.80 FT. GL. CEMENTED W/ 85 SACKS CLASS B W/ 2% CALCIUM CHLORIDE AND 1/4# PER SACK CELLOFLAKE. CIRCULATED 4.5 BARRELS OF CEMENT TO RESERVE PIT. NIPPLED UP BOP AND MANIFOLD. PRESSURE TESTED BOP, MANIFOLD AND CASING TO 1000 PSIG. DRILLED 6 1/4" HOLE TO 1420 FT. GL. TD WELL @ 1420 FT.GL. @ 6:30 PM ON JANUARY 22, 2003. RAN A TOTAL OF 33 JTS 4 1/2" 10.50#/FT ST&C J-55. LANDED CASING AT 1414.70 FT. GL. CEMENTED W/ 115 SACKS CLASS G W/ 2% D79, .2% D46, 1/4# PER SACK D29. TAILED W/ 50 SACKS CLASS G W/ 1/4# PER SACK D29. CIRCULATED 10 BARRELS OF CEMENT TO SURFACE.

OPEN HOLE LOGS RAN SCHLUMBERGER GR/CAL/SP/TLD/AIT/CNL DATED 01/23/2003.

14. I hereby certify that the fore Name (Printed/ Typed)	going is true and co	priect.	Title	स्त्रीतः । सम्बद्धाः	
MICHAEL,T. H	IANSON	1 1000	ENGINEER		
Signature / What	UTI	Janon	Pate February 5, 20		ACCEPTED FOR RECORL
	7 3	THIS SPACE FOR FE	DERAL OF STATE OF FICE	USE	
Approved by	had te te	a espaini acomo marina para promission senso de As 1965 de 19 de larges espainis de 1988 de	Tille order und de service de la company de	ngarina salah dan mendelah dan salah s Kalah salah sa	DateFEBU ( 2003
Conditions of approval, if any an certify that the applicant holds le which would entitle the applican	egal or equitable tit	e to those rights in the subject		90 k yeharisi - Ituza III. III. III. III. III. III. III. III	FARMENTON FIELD OFFICE

Title 18 U.S.C. Section 1001 AND Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitiousor fraudulent statements or representations as to any matter within its jurisdiction.

determined that the site is ready for final inspection.)