

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator

Elm Ridge Resources, Inc.

3. Address of Operator

PO Box 156 Bloomfield, NM 87413

4. Well Location

Unit Letter D : 990 Feet From The North Line and 790 Feet From The West Line

Section 36 Township 25N Range 6W NMPM Rio Arriba County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6800 DF

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

11. NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent date, including estimated date of starting any proposed work) SEE RULE 1103.

Elm Ridge Resources Inc. plans to Plug and Abandon the above referenced well as follows: Please see attachment.

NOTIFY AZTEC OCD
IN TIME TO WITNESS

SIGNATURE

Amy Mackey

TITLE

Production Assistant

DATE

09/14/04

TYPE OR PRINT NAME

Amy Mackey

TELEPHONE NO. 505-632-3476 ext. 201

(This space for State Use)

APPROVED BY

Charles R.

TITLE

DEPUTY OIL & GAS INSPECTOR, DIST. #3

DATE

SEP 17 2004

CONDITIONS OF APPROVAL, IF ANY:

Plugging Procedure for the Havey State #2

Surface csg: 10 3/4" 32.72 #/ft. J-55 @ 320'.

Production csg: 5 1/2" 15.5 #/ft. J-55 @ 6174'.

Perfs: {6025' - 6125'}

Plug 1) Set retainer @ 6000' pump 75 sks cement. Leave 2 sks on top of retainer. *6 min 50' above Retainer*

Plug 2) Cliff house. Shoot 2 holes @ 4200'. Set retainer @ 4100'. Pump 40 sks cement. Leave 2 sks on top of retainer.

Chalk plug top to 3470'
Plug 3) P C. Shoot 2 holes @ 3650'. Set retainer @ 5555'. Pump 40 sks. Leave 2 sks on top of retainer *+ to 0.50' top + 50' @ 2100'*

Nac top 395'
Plug 4) Surface Shoe. Shoot 2 holes @ 370'. Set retainer @ 270'. Pump 140 sks. Circulate cement to surface.

Plug 5) Set 50' plug @ surface inside 5 1/2" casing.

Cut off wellhead, set marker, and reclaim location.